


71540 Type Compact Fan Heater



- Compact Design
- Clip fixing
- Long service life
- Maintenance free
- Temperature safety cut-out

Compact fan heater prevents formation of condensation. The integrated high performance axial fan provides forced air circulation and so guarantees an even temperature in enclosures. With internal terminal connector.


Size chart



Operating voltage	230V AC 50/60Hz
Heating element	PTC resistor, self regulating and temperature limiting
Temperature safety cut-out	to protect against overheating in case of fan failure
Heater body	anodised extruded aluminium profile
Surface temperature	max. 75 °C(400W)
Axial fan, ball bearing	Airflow, free flow AC: 45m ³ /h (50HZ) or 54m ³ /h (60Hz) DC: 54m ³ /h service life 50 000h at 25°C (77°F)
Connection	internal connection terminal 1.5mm ² with strain relief clamping torque 0.8Nm max.
Connection casing	plastic according to UL94 V-0,black
Mounting	clip for 35mm DIN rail, EN 50022
Fitting position	vertical
Operating/Storage temperature	-45 to +70 °C(-49 to +158°F)
Protection type/Protection class	IP20 / I (earthed)

Type	Operating voltage	Heating capacity	Length (L)	Weight (approx.)
71540	230VAC, 50/60HZ	400W	85x222x85mm	1.40kg

Control contact,
e.g. Temperature
regulator **71400**



Heater
Fan Heater **71540** (AC 230V
and 120V) with temperature
safety cut-out