



PATENTED

SPECIFICATION

	RANGE	ACCURACY
AC Current(40~65Hz)	60A/600A	$\pm (1.5\%+5)$ ($<10A \pm (2.0\%+10)$)
	3000A	$\pm (2.0\%+5)$
AC Current(65~200Hz)	60A/600A	$\pm (2.5\%+5)$
	3000A	$\pm (3.0\%+5)$
AC Current(200~1000Hz)	60A/600A	$\pm (3.0\%+5)$
	3000A	$>1000A$ No verification
Frequency	40Hz~1000Hz	$\pm (0.5\%+2)$

FEATURE

Display	6000 Counts
Data Hold	✓
Work Light	✓
Back Light	✓

GENERAL

Power Supply	3 x 1.5V AAA Batteries
Weight	Approx. 175g
Size	324x180x28mm
Jaw Size	Ø150mm
Safety Standard/Rating	EN61010-1, EN61010-2-032, EN61326, CAT.III 1000V



SPECIFICATION

	RANGE	ACCURACY
DC Voltage	6V/60V/600V	$\pm (0.8\%+3)$
AC Voltage (45~65Hz)	6V/60V/600V	$\pm (1.2\%+3)$
AC Voltage (40~2000Hz)	6V/60V/600V	$\pm (2.0\%+5)$
AC Current(40~65Hz)	60A/600A	$\pm (1.5\%+5)$
	$<10A$	$\pm (2.0\%+10)$
	3000A	$\pm (2.0\%+5)$
AC Current(65~200Hz)	60A/600A	$\pm (2.5\%+5)$
	3000A	$\pm (3.0\%+5)$
AC Current(200~1000Hz)	60A/600A	$\pm (3.0\%+5)$
	3000A	$>1000A$ Not verified
Resistance	6kΩ/60kΩ/600kΩ/6MΩ	$\pm (1.0\%+3)$
Frequency	40Hz~1 kHz	$\pm (0.5\%+2)$

FEATURE

Display	6000 Counts
True RMS	✓
Data Hold	✓
Worklight	✓
Back Light	✓


GENERAL

Power Supply	3 x 1.5V AAA Batteries
Weight	Approx. 178g
Size	324x180x28mm
Jaw Size	Ø150mm
Safety Standard/Rating	EN61010-1, EN61010-2-032, EN61326, CAT.IV 600V

AC Voltage Measurement



AC Current Measurement



AC Voltage&AC Current Measurement

