



**SPECIFICATIONS**

|            | RANGE      | ACCURACY   |
|------------|------------|------------|
| DC Voltage | 1000V      | ± (1.0%+2) |
| AC Voltage | 750V       | ± (1.0%+5) |
| AC Current | 20A/200A   | ± (2.0%+5) |
|            | 1000A      | ± (2.0%+7) |
| Resistance | 200Ω/2000Ω | ± (1.0%+3) |

**FEATURE**

|            |             |
|------------|-------------|
| Display    | 2000 Counts |
| Data Hold  | ✓           |
| Diode      | ✓           |
| Continuity | ✓           |
| Back Light | ✓           |

**GENERAL**

|                        |                                                 |
|------------------------|-------------------------------------------------|
| Power                  | 1x9V 6F22 Battery                               |
| Weight                 | Approx. 385g                                    |
| Size                   | 248mm×90mm×44mm                                 |
| Jaw Size               | Ø42mm                                           |
| Safety Standard/Rating | EN61010-1, EN61010-2-032, EN61326, CAT.III 600V |



**SPECIFICATIONS**

|                 | RANGE                        | ACCURACY    |
|-----------------|------------------------------|-------------|
| DC Voltage      | 400mV/4V/40V/400V            | ± (0.7%+1)  |
|                 | 1000V                        | ± (0.8%+3)  |
| AC Voltage      | 4V/40V/400V                  | ± (0.8%+5)  |
|                 | 700V                         | ± (1.0%+10) |
| DC Current      | 400A/1000A                   | ± (3.0%+3)  |
| AC Current      | 400A/1000A                   | ± (3.0%+3)  |
| Resistance      | 400Ω/4kΩ/40kΩ/400kΩ/4MΩ      | ± (1.2%+1)  |
|                 | 40MΩ                         | ± (2.0%+3)  |
| Frequency       | 40Hz/400Hz/4kHz/40kHz/100kHz | ± (2.0%+1)  |
| Capacitance     | 4nF/40nF/400nF/4uF/40uF      | ± (4.0%+10) |
| Temperature(°C) | -40°C ~ 0°C                  | ± (1.0%+6)  |
|                 | 0°C ~ 400°C                  | ± (1.0%+3)  |
|                 | 400°C ~ 750°C                | ± (1.0%+5)  |

**FEATURE**

|            |             |
|------------|-------------|
| Display    | 4000 Counts |
| Data Hold  | ✓           |
| Diode      | ✓           |
| Continuity | ✓           |
| Back Light | ✓           |

**GENERAL**

|                        |                                                 |
|------------------------|-------------------------------------------------|
| Power                  | 1x9V 6F22 Battery                               |
| Weight                 | Approx. 395g                                    |
| Size                   | 248mm×89mm×44mm                                 |
| Jaw Size               | Ø42mm                                           |
| Safety Standard/Rating | EN61010-1, EN61010-2-032, EN61326, CAT.III 600V |

