

PM2016A/S

Mini AC Digital Clamp Meter

PEAKMETER®



SPECIFICATIONS

	RANGE	ACCURACY	
		PM2016A	PM2016S
DC Voltage	0.5~600.0V	±(0.5%+3)	
	0.5~600.0V		±(0.5%+3)
AC Voltage	1.0~600V	±(0.8%+5)	±(0.8%+5)
AC Current	10mA~200A	±(2.5%+8)	±(2.5%+8)
Resistance	0~6kΩ	±(0.8%+3)	±(0.8%+3)
Continuity	<50.0Ω		
Frequency	40Hz~1000Hz		±(1.0%+5)

FEATURE

	PM2016A	PM2016S
Counts	6000 Counts	6000 Counts
AutoRange	√	√
AC Current	6A/60A/200A	6A/60A/200A
DC Voltage	600.0V	600.0V
AC Voltage	600.0V	600.0V
Continuity	√ <50.0Ω	√ <50.0Ω
Resistance	6kΩ	6kΩ
V/Ω/A Auto Scan	√	√
Frequency(Clamp)		1kHz
Frequency(Voltage)		1kHz
Data Hold	√	√
BackLight	√	√
NCV		√

GENERAL

Power Supply	2 x 1.5V AAA Batteries
Weight	Approx. 122g
Size	158mm×55mm×29mm
Jaw Size	Ø20mm
Safety Standard/Rating	EN61010-1, EN61010-2-032, EN61326, CAT.III 600V



PEAKMETER®

PM2116S

Smart Mini AC/DC Digital Clamp Meter



SPECIFICATIONS

	RANGE	ACCURACY
DC Voltage	0.5~600.0V	±(0.5%+3)
AC Voltage	1.0~600V	±(0.8%+5)
AC Current	6A/60A/100A	±(2.5%+8)
DC Current	6A/60A/100A	±(3.0%+8)
Resistance	0~6kΩ	±(0.8%+3)
Continuity	<50Ω	
Frequency	40Hz~1000Hz	±(1.0%+5)

FEATURE

Counts	6000 Counts
AutoRange	√
AC Current	6A/60A/100A
DC Current	6A/60A/100A
DC Voltage	600.0V
AC Voltage	600.0V
Continuity	√ <50.0Ω
Resistance	6kΩ
V/Ω/A Auto Scan	√
Frequency(Clamp)	1kHz
Frequency(Voltage)	1kHz
Data Hold	√
BackLight	√
NCV	√

GENERAL

Power Supply	2 x 1.5V AAA Batteries
Weight	Approx. 115g
Size	158mm×55mm×29mm
Jaw Size	Ø20mm
Safety Standard/Rating	EN61010-1, EN61010-2-032, EN61326, CAT.III 600V

