

## Logic panel

# LP Series

## Instruction Manual





# Preface

Thank you very much for selecting Autonics products.

This user manual contains information about the product and its proper use, and should be kept in a place where it will be easy to access.

# LP series Instruction Manual Guide

- Please familiarize yourself with the information in this manual before using the product.
- This manual provides detailed information on the product's features. It does not offer any guarantee concerning matters beyond the scope of this manual.
- This manual may not be edited or reproduced in either part or whole without permission.
- This programming manual is not provided as part of the product package. Please visit our home-page ([www.autonics.com](http://www.autonics.com)) to download a copy.
- The manual's content may vary depending on changes to the product's software and other unforeseen developments within Autonics, and is subject to change without prior notice. Upgrade notice is provided through our homepage.
- We contrived to describe this manual more easily and correctly. However, if there are any corrections or questions, please notify us these on our homepage.

# LP series Instruction Manual Symbols

Symbol	Description
 Note	Supplementary information for a particular feature.
 Warning	Failure to follow instructions can result in serious injury or death.
 Caution	Failure to follow instructions can lead to a minor injury or product damage.
 Ex.	An example of the concerned feature's use.
※1	Annotation mark.

※The specifications and dimensions of this manual are subject to change without any notice.

# Table of Contents

Preface .....	iii
LP series Instruction Manual Guide .....	iv
LP series Instruction Manual Symbols .....	v
Table of Contents .....	vi
<b>1 Structures of instruction name .....</b>	<b>13</b>
1.1    Structure by data type.....	13
1.2    Structure by data processing .....	14
<b>2 Instruction.....</b>	<b>15</b>
2.1    Basic instruction list .....	15
2.1.1    Non processing instruction .....	15
2.1.2    Contact instruction.....	15
2.1.3    Output instruction .....	16
2.1.4    Reversal instruction.....	16
2.1.5    Stack instruction .....	17
2.1.6    Exit instruction .....	17
2.2    Application instruction.....	18
2.2.1    Counter instruction .....	18
2.2.2    Timer instruction .....	18
2.2.3    Control instruction .....	18
2.2.4    Branch instruction.....	19
2.2.5    Loop instruction .....	19
2.2.6    Master control instruction .....	19
2.2.7    Interrupt instruction.....	19
2.2.8    Watchdog timer .....	20
2.2.9    Input comparison instruction .....	20
2.2.10    Comparison instruction.....	23
2.2.11    Transmission instruction.....	23
2.2.12    Exchange instruction.....	24
2.2.13    Rotation instruction.....	25
2.2.14    Movement instruction .....	26
2.2.15    Arithmetic operation instruction .....	26
2.2.16    Logical operation instruction.....	30
2.2.17    BIN/BCD instruction .....	31
2.2.18    String conversion instruction .....	32
2.2.19    Code conversion instruction .....	33
2.2.20    Sign reversal instruction .....	33
2.2.21    Data conversion instruction .....	33
2.2.22    Refresh instruction .....	33
2.2.23    Display instruction .....	33
2.2.24    Clock instruction .....	34
2.2.25    Motion instruction .....	34
<b>3 Instruction Description .....</b>	<b>37</b>
3.1    Basic instruction.....	37
3.1.1    Non processing instruction (NOP).....	37

3.1.2	Contact instruction(LOAD) .....	38
3.1.3	Contact instruction(LOADN).....	39
3.1.4	Contact instruction(LOADP).....	40
3.1.5	Contact instruction(LOADF) .....	41
3.1.6	Contact instruction(AND) .....	42
3.1.7	Contact instruction(ANDN).....	43
3.1.8	Contact instruction(ANDP).....	44
3.1.9	Contact instruction(ANDF) .....	45
3.1.10	Contact instruction(ANDL) .....	46
3.1.11	Contact instruction(OR).....	47
3.1.12	Contact instruction(ORN) .....	48
3.1.13	Contact instruction(ORP) .....	49
3.1.14	Contact instruction(ORF) .....	50
3.1.15	Contact instruction(ORL).....	51
3.1.16	Output instruction(OUT) .....	52
3.1.17	Output instruction(OUT Syy.yx).....	53
3.1.18	Output instruction(OUTP).....	54
3.1.19	Output instruction(OUTF).....	55
3.1.20	Output instruction(SET).....	56
3.1.21	Output instruction(SET Syy.yx) .....	57
3.1.22	Output instruction(RST) .....	58
3.1.23	Reversal instruction(ALT) .....	59
3.1.24	Reversal instruction(NOT).....	60
3.1.25	Stack instruction(MPUSH).....	61
3.1.26	Stack instruction(MLOAD).....	62
3.1.27	Stack instruction(MPOP) .....	63
3.1.28	Exit instruction(END).....	64
3.2	Application instruction.....	65
3.2.1	Counter instruction(CTU) .....	65
3.2.2	Counter instruction(CTD) .....	66
3.2.3	Counter instruction(CTUD).....	67
3.2.4	Counter instruction(CTR) .....	68
3.2.5	Timer instruction(TON) .....	69
3.2.6	Timer instruction(TOFF) .....	70
3.2.7	Timer instruction(TMR).....	71
3.2.8	Timer instruction(TMON).....	72
3.2.9	Timer instruction(TRTG).....	73
3.2.10	Control instruction(JMP).....	74
3.2.11	Control instruction(LABEL).....	75
3.2.12	Control instruction(FCALL).....	76
3.2.13	Control instruction(FUNC).....	77
3.2.14	Branch instruction(CALL) .....	78
3.2.15	Branch instruction(SUBRT).....	79
3.2.16	Branch instruction(RET) .....	80
3.2.17	Loop instruction(FOR) .....	81
3.2.18	Loop instruction(NEXT).....	82
3.2.19	Loop instruction(BREAK) .....	83
3.2.20	Master control instruction(MCS).....	84
3.2.21	Master control instruction(MCR) .....	85
3.2.22	Interrupt instruction(EI).....	86
3.2.23	Interrupt instruction(DI) .....	87
3.2.24	Interrupt instruction(ETI) .....	88

3.2.25	Interrupt instruction(EEI) .....	89
3.2.26	Interrupt instruction(DTI) .....	90
3.2.27	Interrupt instruction(DEI) .....	91
3.2.28	Interrupt instruction(TINT) .....	92
3.2.29	Interrupt instruction(EINT).....	93
3.2.30	Interrupt instruction(IRET).....	94
3.2.31	Watchdog timer(WDT).....	95
3.2.32	Input comparison instruction(LOAD=).....	96
3.2.33	Input comparison instruction(LOAD>).....	97
3.2.34	Input comparison instruction(LOAD<).....	98
3.2.35	Input comparison instruction(LOAD<>).....	99
3.2.36	Input comparison instruction(LOAD>=).....	100
3.2.37	Input comparison instruction(LOAD<=).....	101
3.2.38	Input comparison instruction(DLOAD=).....	102
3.2.39	Input comparison instruction(DLOAD>).....	103
3.2.40	Input comparison instruction(DLOAD<).....	104
3.2.41	Input comparison instruction(DLOAD<>).....	105
3.2.42	Input comparison instruction(DLOAD>=).....	106
3.2.43	Input comparison instruction(DLOAD<=).....	107
3.2.44	Input comparison instruction(AND=) .....	108
3.2.45	Input comparison instruction(AND>) .....	109
3.2.46	Input comparison instruction(AND<) .....	110
3.2.47	Input comparison instruction(AND<>) .....	111
3.2.48	Input comparison instruction(AND>=) .....	112
3.2.49	Input comparison instruction(AND<=) .....	113
3.2.50	Input comparison instruction(DAND=).....	114
3.2.51	Input comparison instruction(DAND>).....	115
3.2.52	Input comparison instruction(DAND<).....	116
3.2.53	Input comparison instruction(DAND<>) .....	117
3.2.54	Input comparison instruction(DAND>=) .....	118
3.2.55	Input comparison instruction(DAND<=) .....	119
3.2.56	Input comparison instruction(OR=) .....	120
3.2.57	Input comparison instruction(OR>) .....	121
3.2.58	Input comparison instruction(OR<) .....	122
3.2.59	Input comparison instruction(OR<>) .....	123
3.2.60	Input comparison instruction(OR>=) .....	124
3.2.61	Input comparison instruction(OR<=) .....	125
3.2.62	Input comparison instruction(DOR=).....	126
3.2.63	Input comparison instruction(DOR>).....	127
3.2.64	Input comparison instruction(DOR<).....	128
3.2.65	Input comparison instruction(DOR<>).....	129
3.2.66	Input comparison instruction(DOR>=).....	130
3.2.67	Input comparison instruction(DOR<=).....	131
3.2.68	Comparison instruction(CMP) .....	132
3.2.69	Comparison instruction(DCMP).....	133
3.2.70	Comparison instruction(ACMP).....	134
3.2.71	Comparison instruction(CMPL) .....	135
3.2.72	Comparison instruction(DCMPL).....	136
3.2.73	Comparison instruction(BWCMP) .....	137
3.2.74	Comparison instruction(DBWCMP).....	139
3.2.75	Transmission instruction(BMOV).....	141
3.2.76	Transmission instruction(MOV) .....	142

3.2.77	Transmission instruction(DMOV) .....	143
3.2.78	Transmission instruction(BMOVL) .....	144
3.2.79	Transmission instruction(MOVL).....	145
3.2.80	Transmission instruction(DMOVL) .....	146
3.2.81	Transmission instruction(BMOVG).....	147
3.2.82	Transmission instruction(MOVG).....	148
3.2.83	Transmission instruction(DMOVG) .....	149
3.2.84	Transmission instruction(BCMOV).....	150
3.2.85	Transmission instruction(CMOV) .....	151
3.2.86	Transmission instruction(DCMOV).....	152
3.2.87	Exchange instruction(XCH).....	153
3.2.88	Exchange instruction(DXCH) .....	154
3.2.89	Exchange instruction(AXCH) .....	155
3.2.90	Exchange instruction(SWAP) .....	156
3.2.91	Exchange instruction(DSWAP) .....	157
3.2.92	Rotation instruction(ROR) .....	158
3.2.93	Rotation instruction(DROR) .....	159
3.2.94	Rotation instruction(AROR).....	160
3.2.95	Rotation instruction(RORC) .....	161
3.2.96	Rotation instruction(DRORC).....	162
3.2.97	Rotation instruction(ARORC) .....	163
3.2.98	Rotation instruction(ROL).....	164
3.2.99	Rotation instruction(DROL) .....	165
3.2.100	Rotation instruction(AROL) .....	166
3.2.101	Rotation instruction(ROLC) .....	167
3.2.102	Rotation instruction(DROLC) .....	168
3.2.103	Rotation instruction(AROLC).....	169
3.2.104	Movement instruction(SFTR) .....	170
3.2.105	Movement instruction(ASFTR).....	171
3.2.106	Movement instruction(SFTL).....	172
3.2.107	Movement instruction(ASFTL) .....	173
3.2.108	Movement instruction(WSFTR).....	174
3.2.109	Movement instruction(WSFTL) .....	175
3.2.110	Arithmetic operation instruction(ADD).....	176
3.2.111	Arithmetic operation instruction(DADD) .....	177
3.2.112	Arithmetic operation instruction(ADDU) .....	178
3.2.113	Arithmetic operation instruction(DADDU) .....	179
3.2.114	Arithmetic operation instruction(ADDL).....	180
3.2.115	Arithmetic operation instruction(DADDL) .....	181
3.2.116	Arithmetic operation instruction(ADDLU) .....	182
3.2.117	Arithmetic operation instruction(DADDLU) .....	183
3.2.118	Arithmetic operation instruction(SUB) .....	184
3.2.119	Arithmetic operation instruction(DSUB) .....	185
3.2.120	Arithmetic operation instruction(SUBU) .....	186
3.2.121	Arithmetic operation instruction(DSUBU).....	187
3.2.122	Arithmetic operation instruction(SUBL) .....	188
3.2.123	Arithmetic operation instruction(DSUBL) .....	189
3.2.124	Arithmetic operation instruction(SUBLU) .....	190
3.2.125	Arithmetic operation instruction(DSUBLU).....	191
3.2.126	Arithmetic operation instruction(MUL).....	192
3.2.127	Arithmetic operation instruction(DMUL) .....	193
3.2.128	Arithmetic operation instruction(MULU) .....	194

3.2.129 Arithmetic operation instruction(DMULU).....	195
3.2.130 Arithmetic operation instruction(MULL).....	196
3.2.131 Arithmetic operation instruction(DMULL).....	197
3.2.132 Arithmetic operation instruction(MULLU).....	198
3.2.133 Arithmetic operation instruction(DMULLU).....	199
3.2.134 Arithmetic operation instruction(DIV) .....	200
3.2.135 Arithmetic operation instruction(DDIV).....	201
3.2.136 Arithmetic operation instruction(DIVU).....	202
3.2.137 Arithmetic operation instruction(DDIVU) .....	203
3.2.138 Arithmetic operation instruction(DIVL) .....	204
3.2.139 Arithmetic operation instruction(DDIVL).....	205
3.2.140 Arithmetic operation instruction(DIVLU).....	206
3.2.141 Arithmetic operation instruction(DDIVLU).....	207
3.2.142 Arithmetic operation instruction(INC) .....	208
3.2.143 Arithmetic operation instruction(DINC).....	209
3.2.144 Arithmetic operation instruction(DEC).....	210
3.2.145 Arithmetic operation instruction(DDEC).....	211
3.2.146 Arithmetic operation instruction(ADDB) .....	212
3.2.147 Arithmetic operation instruction(DADDDB).....	213
3.2.148 Arithmetic operation instruction(ADDBL) .....	214
3.2.149 Arithmetic operation instruction(DADDBL).....	215
3.2.150 Arithmetic operation instruction(SUBB).....	216
3.2.151 Arithmetic operation instruction(DSUBB).....	217
3.2.152 Arithmetic operation instruction(SUBBL).....	218
3.2.153 Arithmetic operation instruction(DSUBBL).....	219
3.2.154 Arithmetic operation instruction(MULB) .....	220
3.2.155 Arithmetic operation instruction(DMULB).....	221
3.2.156 Arithmetic operation instruction(MULBL) .....	222
3.2.157 Arithmetic operation instruction(DMULBL).....	223
3.2.158 Arithmetic operation instruction(DIVB) .....	224
3.2.159 Arithmetic operation instruction(DDIVB) .....	225
3.2.160 Arithmetic operation instruction(DIVBL) .....	226
3.2.161 Arithmetic operation instruction(DDIVBL) .....	227
3.2.162 Arithmetic operation instruction(INCB) .....	228
3.2.163 Arithmetic operation instruction(DINCB) .....	229
3.2.164 Arithmetic operation instruction(DECB) .....	230
3.2.165 Arithmetic operation instruction(DDECBC) .....	231
3.2.166 Logical operation instruction(WAND) .....	232
3.2.167 Logical operation instruction(DAND) .....	233
3.2.168 Logical operation instruction(AAND) .....	234
3.2.169 Logical operation instruction(WANDL) .....	235
3.2.170 Logical operation instruction(DANDL) .....	236
3.2.171 Logical operation instruction(WOR) .....	237
3.2.172 Logical operation instruction(DOR) .....	238
3.2.173 Logical operation instruction(AOR) .....	239
3.2.174 Logical operation instruction(WORL) .....	240
3.2.175 Logical operation instruction(DORL) .....	241
3.2.176 Logical operation instruction(XOR) .....	242
3.2.177 Logical operation instruction(DXOR).....	243
3.2.178 Logical operation instruction(AXOR).....	244
3.2.179 Logical operation instruction(XORL) .....	245
3.2.180 Logical operation instruction(DXORL).....	246

3.2.181 Logical operation instruction(XNR) .....	247
3.2.182 Logical operation instruction(DXNR).....	248
3.2.183 Logical operation instruction(AXNR).....	249
3.2.184 Logical operation instruction(XNRL) .....	250
3.2.185 Logical operation instruction(DXNRL).....	251
3.2.186 BIN/BCD conversion instruction(BIN2BCD).....	252
3.2.187 BIN/BCD conversion instruction(DBIN2BCD).....	253
3.2.188 BIN/BCD conversion instruction(BCD2BIN).....	254
3.2.189 BIN/BCD conversion instruction(DBCD2BIN).....	255
3.2.190 String conversion instruction(BIN2HASC).....	256
3.2.191 String conversion instruction(DBIN2HASC).....	257
3.2.192 String conversion instruction(HASC2BIN).....	258
3.2.193 String conversion instruction(DHASC2BIN).....	259
3.2.194 String conversion instruction(BCD2DASC) .....	260
3.2.195 String conversion instruction(DBCD2DASC) .....	261
3.2.196 String conversion instruction(DASC2BIN).....	262
3.2.197 String conversion instruction(DDASC2BIN) .....	263
3.2.198 String conversion instruction(STR2ASC) .....	264
3.2.199 String conversion instruction(DASC2BCD) .....	265
3.2.200 String conversion instruction(DDASC2BCD) .....	266
3.2.201 String conversion instruction(BIN2DASC).....	267
3.2.202 String conversion instruction(DBIN2DASC).....	268
3.2.203 Code conversion instruction(GRY2BIN).....	269
3.2.204 Code conversion instruction(DGRY2BIN).....	270
3.2.205 Code conversion instruction(BIN2GRY).....	271
3.2.206 Code conversion instruction(DBIN2GRY) .....	272
3.2.207 Sign reversal instruction(NEG).....	273
3.2.208 Sign reversal instruction(DNEG) .....	274
3.2.209 Data conversion instruction(DECO).....	275
3.2.210 Data conversion instruction(ENCO).....	276
3.2.211 Data conversion instruction(EXT) .....	277
3.2.212 Refresh instruction(REF).....	278
3.2.213 Display instruction(SEG) .....	279
3.2.214 Clock instruction(TCMP) .....	281
3.2.215 Clock instruction(TADD) .....	282
3.2.216 Clock instruction(TSUB) .....	283
3.2.217 Clock instruction(TRD) .....	284
3.2.218 Clock instruction(TWR) .....	285
3.2.219 Clock instruction(HOUR) .....	286
3.2.220 Clock instruction(TZCP) .....	287
3.2.221 Motion instruction(MTVDM) .....	289
3.2.222 Motion instruction(MTPDM) .....	289
3.2.223 Motion instruction(MTIDM) .....	291
3.2.224 Motion instruction(MTMEC) .....	292
3.2.225 Motion instruction(MTEMS) .....	293
3.2.226 Motion instruction(MTCPP) .....	294
3.2.227 Motion instruction(MTFOS) .....	295
3.2.228 Motion instruction(MTSRS) .....	296
3.2.229 Motion instruction(MTOBC) .....	297
3.2.230 Motion instruction(MTOVV) .....	299
3.2.231 Motion instruction(MTOVP) .....	300
3.2.232 Motion instruction(MTIPT) .....	301

3.2.233 Motion instruction(MTUAI).....	302
--	-----

# 1 Structures of instruction name

The structure of instruction name is divided into three parts and each part represents data type, instruction name, and data processing method respectively. The data type is usually located in front of instruction name, and the data processing method is located after the instruction name(Limited to a few of them).

## 1.1 Structure by data type

### (1) By data size

- 1) Bit data type instruction  
It has an instruction structure of Bxxxx after Bit's B.  
Ex) **BMOV**, **BMOVL**, **BMOVG** .... etc.
- 2) Nibble data type instruction (4bit)  
It has an instruction structure of Nxxxx after Nibble's N.
- 3) Half word data type instruction (8bit)  
It has an instruction structure of Hxxxx after Half Word's H.
- 4) Word data type instruction (1word)  
It has an instruction structure of xxxx without Word name.  
Ex) **MOV**, **MOVL**, **MOVG** .... etc.
- 5) Double word data instruction (2word)  
It has an instruction structure of Dxxx after Double word's D.  
Ex) **DMOV**, **DMOVL**, **DMOVG** .... etc.
- 6) User-defined data type instruction  
It has an instruction structure of Axxxx, after Any bit's A.  
Ex) **AOR**, **AAND**, **AXOR**, .... etc.

### (2) By data sign

There are signed and unsigned data types, and the former is typically used with omitting its name. On the other hand, the latter is used with "U" and "U" is positioned in the far last part of the instruction name.

If there is name according to data processing, in case of (xxxL, xxxG) it is placed to the back  
For further details, refer to '1.2 Structure by data processing'.

- If there is no data processing method part: **MULU**, **ADDU**, **SUBU**, .... etc.
- If there is a data processing method part: **MULLU**, **ADDLU**, **SUBLU** .... etc.

### (3) By BCD data

BCD data has an instruction structure of xxxB after BCD's B.

Be sure that the data processing method part(List, Group) is always positioned after the BCD part.

- If there is no data processing method name.(1 : 1 process): **ADDB**, **MULB**, **SUBB**, .... etc.
- If the data processing method name is 'List': **ADD<sub>BL</sub>**, **MUL<sub>BL</sub>**, **SUB<sub>BL</sub>**, .... etc.



## 1.2 Structure by data processing

### (1) 1:1 processing instruction

It has an instruction structure of xxx with omitting the name.

Ex) MOV, ...


### (2) 1:N processing instruction



It has an instruction structure of xxxL after List's "L".

Ex) MOVL, ....

### (3) N:N processing instruction



It has an instruction structure of xxxG after Group's "G".

Ex) MOVG, ...



### Note

#### Operand

- S: Represents source device
- D: Represents destination device
- N: Represents the number of devices

## 2 Instruction

### 2.1 Basic instruction list

#### 2.1.1 Non processing instruction

Instruction	Ladder symbol	Step	Page
NOP		1	37

#### 2.1.2 Contact instruction

Instruction	Ladder symbol	Step	Page
LOAD		1	38
LOADN		1	39
LOADP		2	40
LOADF		2	41
AND		1	42
ANDN		1	43
ANDP		2	44
ANDF		2	45
ANDL		1	46
OR		1	47
ORN		1	48

Instruction	Ladder symbol	Step	Page
ORP		2	49
ORF		2	50
ORL		1	51

### 2.1.3 Output instruction

Instruction	Ladder symbol	Step	Page
OUT		1	52
OUT Syy.yx		1	53
OUTP		2	54
OUTF		2	55
SET		1	56
SET Syy.yx		1	57
RST		1	58

### 2.1.4 Reversal instruction

Instruction	Ladder symbol	Step	Page
ALT		3	59
NOT		1	60

### 2.1.5 Stack instruction

Instruction	Ladder symbol	Step	Page
MPUSH		1	61
MLOAD		1	62
MPOP		1	63

### 2.1.6 Exit instruction

Instruction	Ladder symbol	Step	Page
END		1	64

## 2.2 Application instruction

### 2.2.1 Counter instruction

Instruction	Ladder symbol	Step	Page
CTU		5	65
CTD		5	66
CTUD		5	67
CTR		5	68

### 2.2.2 Timer instruction

Instruction	Ladder symbol	Step	Page
TON		5	69
TOFF		5	70
TMR		5	71
TMON		5	72
TRTG		5	73

### 2.2.3 Control instruction

Instruction	Ladder symbol	Step	Page
JMP		3	74
LABEL		3	75
FCALL		3	76

Instruction	Ladder symbol	Step	Page
FUNC	- [ FUNC ] - [ LABEL ] -	3	77

## 2.2.4 Branch instruction

Instruction	Ladder symbol	Step	Page
CALL	- [ CALL ] - [ LABEL ] -	3	78
SUBRT	- [ SUBRT ] - [ LABEL ] -	3	79
RET	- [ RET ] -	1	80

## 2.2.5 Loop instruction

Instruction	Ladder symbol	Step	Page
FOR	- [ FOR ] - [ N ] -	3	81
NEXT	- [ NEXT ] -	1	82
BREAK	- [ BREAK ] -	1	83

## 2.2.6 Master control instruction

Instruction	Ladder symbol	Step	Page
MCS	- [ MCS ] - [ N ] -	2	84
MCR	- [ MCR ] - [ N ] -	2	85

## 2.2.7 Interrupt instruction

Instruction	Ladder symbol	Step	Page
EI	- [ EI ] -	1	86
DI	- [ DI ] -	1	87

Instruction	Ladder symbol	Step	Page
ETI	- ETI N -	1	88
EEI	- EEI N -	1	89
DTI	- DTI N	1	90
DEI	- DEI N	1	91
TINT	- TINT N	1	92
EINT	- EINT N	1	93
IRET	- IRET	1	94


## 2.2.8 Watchdog timer

Instruction	Ladder symbol	Step	Page
WDT	- WDT	1	95

## 2.2.9 Input comparison instruction




Instruction	Ladder symbol	Step	Page
LOAD=	= S1 S2	5	96
LOAD>	> S1 S2	5	97
LOAD<	< S1 S2	5	98
LOAD<>	<> S1 S2	5	99
LOAD>=	>= S1 S2	5	100

Instruction	Ladder symbol	Step	Page
LOAD<=	<= S1 S2	5	101
DLOAD=	= S1 S2	5	102
DLOAD>	> S1 S2	5	103
DLOAD<	< S1 S2	5	104
DLOAD<>	<> S1 S2	5	105
DLOAD>=	>= S1 S2	5	106
DLOAD<=	<= S1 S2	5	107
AND=	= S1 S2	5	108
AND>	> S1 S2	5	109
AND<	< S1 S2	5	110
AND<>	<> S1 S2	5	111
AND>=	>= S1 S2	5	112
AND<=	<= S1 S2	5	113
DAND=	= S1 S2	5	114
DAND>	> S1 S2	5	115






Instruction	Ladder symbol	Step	Page
DAND<		5	116
DAND<>		5	117
DAND>=		5	118
DAND<=		5	119
OR=		5	120
OR>		5	121
OR<		5	122
OR<>		5	123
OR>=		5	124
OR<=		5	125
DOR=		5	126
DOR>		5	127
DOR<		5	128
DOR<>		5	129
DOR>=		5	130

Instruction	Ladder symbol	Step	Page
DOR<=		5	131

## 2.2.10 Comparison instruction

Instruction	Ladder symbol	Step	Page
CMP		7	132
DCMP		7	133
ACMP		7	134
CMPL		9	135
DCMPL		9	136
BWCMP		9	137
DBW CMP		9	139

## 2.2.11 Transmission instruction

Instruction	Ladder symbol	Step	Page
BMOV		5	141
MOV		5	142
DMOV		5	143
BMOVL		7	144
MOVL		7	145

Instruction	Ladder symbol	Step	Page
DMOVL	— DMOVL S D N —	7	146
BMOVG	— BMOVG S D N —	7	147
MOVG	— MOVG S D N —	7	148
DMOVG	— DMOVG S D N —	7	149
BCMOV	— BCMOV S D —	5	150
CMOV	— CMOV S D —	5	151
DCMOV	— DCMOV S D —	5	152

### 2.2.12 Exchange instruction

Instruction	Ladder symbol	Step	Page
XCH	— XCH S D —	5	153
DXCH	— DXCH S1 S2 —	5	154
AXCH	— AXCH S1 S2 N —	7	155
SWAP	— SWAP D —	3	156
DSWAP	— DSWAP D —	3	157

### 2.2.13 Rotation instruction

Instruction	Ladder symbol	Step	Page
ROR	— ROR S C —	5	158
DROR	— DROR S C —	5	159
AROR	— AROR S N C —	7	160
RORC	— RORC S C —	5	161
DRORC	— DRORC S C —	5	162
ARORC	— AROSC S N C —	7	163
ROL	— ROL S C —	5	164
DROL	— DROL S C —	5	165
AROL	— AROL S N C —	7	166
ROLC	— ROLC S C —	5	167
DROLC	— DROLC S C —	5	168
AROLC	— AROLCSNC —	7	169

## 2.2.14 Movement instruction

Instruction	Ladder symbol	Step	Page
SFTR	— SFTR S N —	9	170
ASFTR	— ASFTR S N1 N2 —	9	171
SFTL	— SFTL S N1 N2 —	9	172
ASFTL	— ASFTL S N1 N2 —	9	173
WSFTR	— WSFTR S N1 N2 —	9	174
WSFTL	— WSFTL S N1 N2 —	9	175

## 2.2.15 Arithmetic operation instruction

Instruction	Ladder symbol	Step	Page
ADD	— ADD S1 S2 D —	7	176
DADD	— DADD S1 S2 D —	7	177
ADDU	— ADDU S1 S2 D —	7	178
DADDU	— DADDU S1 S2 D —	7	179
ADDL	— ADDL S1 S2 D N —	9	180
DADDL	— DADDL S1 S2 D N —	9	181
ADDLU	— ADDLU S1 S2 D N —	9	182
DADDLU	— DADDLU S1 S2 D N —	9	183

Instruction	Ladder symbol	Step	Page
SUB		7	184
DSUB		7	185
SUBU		7	186
DSUBU		7	187
SUBL		9	188
DSUBL		9	189
SUBLU		9	190
DSUBLU		9	191
MUL		7	192
DMUL		7	193
MULU		7	194
DMULU		7	195
MULL		9	196
DMULL		9	197
MULLU		9	198

Instruction	Ladder symbol	Step	Page
DMULLU	— DMULLU S1 S2 D N —	9	199
DIV	— DIV S1 S2 D —	7	200
DDIV	— DDIV S1 S2 D —	7	201
DIVU	— DIVU S1 S2 D —	7	202
DDIVU	— DDIVU S1 S2 D —	7	203
DIVL	— DIVL S1 S2 D —	9	204
DDIVL	— DDIVL S1 S2 D N —	9	204
DIVLU	— DIVLU S1 S2 D N —	9	206
DDIVLU	— DDIVLU S1 S2 D N —	9	207
INC	— INC D —	3	208
DINC	— DINC D —	3	209
DEC	— DEC D —	3	210
DDEC	— DDEC D —	3	211
ADD	— ADD S1 S2 D —	7	212
DADD	— DADD S1 S2 D —	7	213

Instruction	Ladder symbol	Step	Page
ADDBL		9	214
DADDBL		9	215
SUBB		7	216
DSUBB		7	217
SUBBL		9	218
DSUBBL		9	219
MULB		7	220
DMULB		7	221
MULBL		9	222
DMULBL		9	223
DIVB		7	224
DDIVB		7	225
DIVBL		9	226
DDIVBL		9	227
INCB		3	228

Instruction	Ladder symbol	Step	Page
DINCB		3	229
DECB		3	230
DDECB		3	231

## 2.2.16 Logical operation instruction

Instruction	Ladder symbol	Step	Page
WAND		7	232
DAND		7	233
AAND		9	234
WANDL		9	235
DANDL		9	236
WOR		7	237
DOR		7	238
AOR		9	239
WORL		9	240
DORL		9	241
XOR		7	242

Instruction	Ladder symbol	Step	Page
DXOR	— DXOR S1 S2 D —	7	243
AXOR	— AXOR S1 S2 D N —	9	244
XORL	— XORL S1 S2 D N —	9	245
DXORL	— DXORL S1 S2 D N —	9	246
XNR	— XNR S1 S2 D —	7	247
DXNR	— DXNR S1 S2 D —	7	248
AXNR	— AXNR S1 S2 D N —	9	249
XNRL	— XNRL S1 S2 D N —	9	250
DXNRL	— DXNRL S1 S2 D N —	9	251

## 2.2.17 BIN/BCD instruction

Instruction	Ladder symbol	Step	Page
BIN2BCD	— BIN2BCD S D —	5	252
DBIN2BCD	— DBIN2BCD S D —	5	253
BCD2BIN	— BCD2BIN S D —	5	254
DBCD2BIN	— DECD2BIN S D —	5	255

## 2.2.18 String conversion instruction

Instruction	Ladder symbol	Step	Page
BIN2HASC		5	256
DBIN2HASC		5	257
HASC2BIN		5	258
DHASC2BIN		5	259
BCD2DASC		5	260
DBCD2DASC		5	261
DASC2BIN		5	262
DDASC2BIN		5	263
STR2ASC		7	264
DASC2BCD		5	265
DDASC2BCD		5	266
BIN2DASC		5	267
DBIN2DASC		5	268

## 2.2.19 Code conversion instruction

Instruction	Ladder symbol	Step	Page
GRY2BIN	— GRY2BIN S D —	5	269
DGRY2BIN	— DGRY2BIN S D —	5	270
BIN2GRY	— BIN2GRY S D —	5	271
DBIN2GRY	— DBIN2GRY S D —	5	272

## 2.2.20 Sign reversal instruction

Instruction	Ladder symbol	Step	Page
NEG	— NEG D —	3	273
DNEG	— DNEG D —	3	274

## 2.2.21 Data conversion instruction

Instruction	Ladder symbol	Step	Page
DECO	— DECO S D N —	7	275
ENCO	— ENCO S D N —	7	276
EXT	— EXT D —	3	277

## 2.2.22 Refresh instruction

Instruction	Ladder symbol	Step	Page
REF	— REF D N —	5	278

## 2.2.23 Display instruction






Instruction	Ladder symbol	Step	Page
SEG	— SEG S D N —	7	279

## 2.2.24 Clock instruction

Instruction	Ladder symbol	Step	Page
TCMP	— TCMP S1 S2 S3 S4 D —	7	281
TADD	— TADD S1 S2 D —	7	282
TSUB	— TSUB S1 S2 D —	7	283
TRD	— TRD D —	3	284
TWR	— TWR D —	3	285
HOUR	— HOUR S D1 D2 —	7	286
TZCP	— TZCP S1 S2 S3 D —	9	287

## 2.2.25 Motion instruction

Instruction	Ladder symbol	Step	Page
MTVDM	— MTVDM S0 S1 S2 S3 S4 S5 —	9	289
MTPDM	— MTPDM S0 S1 S2 S3 S4 S5 —	9	289
MTIDM	— MTIDM S0 S1 —	5	290
MTMEC	— MTMEC S0 —	5	292
MTEMS	— MTEMS S0 —	5	293
MTCPP	— MTCPP S0 S1 —	5	294
MTFOS	— MTFOS S0 —	5	295
MTSRS	— MTSRS S0 —	5	296

Instruction	Ladder symbol	Step	Page
MTOBC		5	297
MTOVV		5	299
MTOVP		5	300
MTIPT		7	301
MTUAI		5	302



## 3 Instruction Description

### 3.1 Basic instruction

#### 3.1.1 Non processing instruction (NOP)

Non  
processing NOP  
instruction

Applicable model

LP-S044, LP-S070

1. It is non processing instruction.
2. It is available only for mnemonic program.

### 3.1.2 Contact instruction(LOAD)


**Contact instruction**    **LOAD**    **S**

Applicable model

LP-S044, LP-S070


OP	DATA type	Available device / Description / Range	Error	Zero	Carry	Borrow	Step
<b>S</b>	BIT	X, Y, M, S, T, C, F, UB Contact of bit device Not applicable					1

<Ladder>



When the contact(S) is ON, the corresponding output bit becomes 1.


<Time chart>



### 3.1.3 Contact instruction(LOADN)


Contact instruction	LOADN	S	Applicable model LP-S044, LP-S070				
OP	DATA type	Available device / Description / Range	Error	Zero	Carry	Borrow	Step
S	BIT	X, Y, M, S, T, C, F, UB					
		Contact of bit device					
		Not applicable					1

#### <Ladder>



When the (S) bit turns OFF from ON, the operation result becomes ON from OFF.

#### <Time chart>



### 3.1.4 Contact instruction(LOADP)


Contact instruction    LOADP    S

Applicable model

LP-S044, LP-S070


OP	DATA type	Available device / Description / Range	Error	Zero	Carry	Borrow	Step
S	BIT	X, Y, M, S, T, C, F, UB Contact of bit device Not applicable					2

<Ladder>



As soon as the (S) contact turns ON from OFF, the operation result becomes ON.


<Time chart>



### 3.1.5 Contact instruction(LOADF)


Contact instruction	LOADF	S	Applicable model
OP	DATA type	Available device / Description / Range	
S	BIT	X, Y, M, S, T, C, F, UB	Error
		Contact of bit device	Zero
		Not applicable	Carry
			Borrow
			Step
			2

#### <Ladder>



As soon as the (S) contact turns OFF from ON, the operation result becomes ON.


#### <Time chart>



### 3.1.6 Contact instruction(AND)


Contact instruction AND S			Applicable model LP-S044, LP-S070				
OP	DATA type	Available device / Description / Range	Error	Zero	Carry	Borrow	Step
S	BIT	X, Y, M, S, T, C, F, UB Contact of bit device Not applicable					1

#### <Ladder>



Executes AND operation between the previous operation result and the designated contact(S), and considers it as the operation result.


#### <Time chart>



### 3.1.7 Contact instruction(ANDN)


Contact instruction	ANDN	S	Applicable model
OP	DATA type	Available device / Description / Range	
S	BIT	X, Y, M, S, T, C, F, UB	Error
		Contact of bit device	Zero
		Not applicable	Carry
			Borrow
			Step
			1

#### <Ladder>



Executes AND NOT operation between the previous operation result and the designated contact(S), and considers it as the operation result.


#### <Time chart>



### 3.1.8 Contact instruction(ANDP)


Contact instruction ANDP S			Applicable model LP-S044, LP-S070				
OP	DATA type	Available device / Description / Range	Error	Zero	Carry	Borrow	Step
S	BIT	X, Y, M, S, T, C, F, UB Contact of bit device Not applicable					2

#### <Ladder>



On the rising edge of a pulse, it executes AND operation between the previous operation result and the designated contact(S), and considers it as the operation result.


#### <Time chart>



### 3.1.9 Contact instruction(ANDF)


Contact instruction	ANDF	S	Applicable model				
OP	DATA type	Available device / Description / Range	Error	Zero	Carry	Borrow	Step
S	BIT	X, Y, M, S, T, C, F, UB					
		Contact of bit device					
		Not applicable					2

#### <Ladder>



On the falling edge of a pulse, it executes AND operation between the previous operation result and the designated contact(S), and considers it as the operation result.

#### <Time chart>



### 3.1.10 Contact instruction(ANDL)


#### Contact instruction ANDL

Applicable model  
LP-S044, LP-S070

#### <Mnemonic & Ladder>

Step	Instruction	OP1	OP2
0	LOAD	X00000	
1	LOAD	X00001	
2	OR	X00002	
3	ANDL		
4	OUT	Y00000	
5	END		


Executes the AND operation between the block and the block.



#### [Note]

- You cannot add as device input in ladder.
- Input for instruction is available only for mnemonic.


#### <Time chart>



### 3.1.11 Contact instruction(OR)


Contact instruction	OR	S	Applicable model				
OP	DATA type	Available device / Description / Range	Error	Zero	Carry	Borrow	Step
		X, Y, M, S, T, C, F, UB					
<b>S</b>	BIT	Contact of bit device					
		Not applicable					1

#### <Ladder>



Executes the OR operation between the previous operation result and the designated contact(S), and considers it as the operation result.


#### <Time chart>



### 3.1.12 Contact instruction(ORN)


Contact instruction	ORN	S	Applicable model				
OP	DATA type	Available device / Description / Range	Error	Zero	Carry	Borrow	Step
S	BIT	X, Y, M, S, T, C, F, UB Contact of bit device Not applicable					1

#### <Ladder>



Executes the ORN operation between the previous operation result and the designated contact(S), and considers it as the operation result.


#### <Time chart>



### 3.1.13 Contact instruction(ORP)


Contact instruction	OP	S	Applicable model
OP	DATA type	Available device / Description / Range	Error
S	BIT	X, Y, M, S, T, C, F, UB Contact of bit device Not applicable	Zero Carry Borrow Step 2

#### <Ladder>



On the rising edge of a pulse, executes OR or ORN operation between the previous operation result and designated contact(S), and considers it as the operation result.


#### <Time chart>



### **3.1.14 Contact instruction(ORF)**


Contact instruction	ORF	S	Applicable model
OP	DATA type	Available device / Description / Range	
S	BIT	X, Y, M, S, T, C, F, UB	
		Contact of bit device	
		Not applicable	
	Error	Zero	Step
		Carry	
	Borrow		2

## <Ladder>



On the falling edge of a pulse, executes OR or ORN operation between the previous operation result and the designated contact(S), and considers it as the operation result.

## <Time chart>



### 3.1.15 Contact instruction(ORL)


Contact  
instruction    ORL

Applicable model  
LP-S044, LP-S070

#### <Mnemonic & Ladder>

Step	Instruction	OP1	OP2
0	LOAD	X00000	
1	AND	X00001	
2	LOAD	X00002	
3	AND	X00003	
4	ORL		
5	OUT	Y00000	
6	END		


Executes the OR operation between the block and the block.



#### [Note]

- You cannot add as device input in ladder.
- Input for instruction is available only for mnemonic.


#### <Time chart>



### 3.1.16 Output instruction(OUT)


Output instruction OUT D			Applicable model LP-S044, LP-S070				
OP	DATA type	Available device / Description / Range	Error	Zero	Carry	Borrow	Step
D	BIT	Y, F, S, M, UB					
		ON/OFF contact of device					
		Not applicable					1

#### <Ladder>



Outputs the operation result executed to the OUT instruction to the (S) device.

#### <Time chart>



### 3.1.17 Output instruction(OUT Syy.yx)

**Output  
instruction**


**OUT Syy.yx D**

Applicable model

LP-S044, LP-S070

OP	DATA type	Available device / Description / Range	Error	Zero	Carry	Borrow	Step
		S					
<b>D</b>	BIT	yyy is group number(0 to 255), xx is step number (0 to 99)					
		Not applicable					1

#### <Ladder>



Step device

yyy: Group number(0 to 255)

xx: Step number(0 to 99)


1. Unlike the Sequential Control(Set Syy.yx) Instructions, if input condition turns ON, the corresponding step becomes ON regardless of the step order.

2. Although a number of input condition contacts become ON in the same group, the last programmed contact is output firstly.

3. Even if the input condition turns OFF, the step number retains ON.

4. In order to clear the OUT Syy.yx instruction, the input contact of Syy.00 should become ON.


#### <Time chart>



### 3.1.18 Output instruction(OUTP)


Output instruction OUTP D			Applicable model LP-S044, LP-S070				
OP	DATA type	Available device / Description / Range	Error	Zero	Carry	Borrow	Step 2
D	BIT	Y, F, S, M, UB Contact to be ON for one scan on the rising edge of a pulse Not applicable					

#### <Ladder>



When the operation result executed to the OUTP turns OFF from ON, the output contact becomes ON for only one scan and then becomes OFF for any other cases.


#### <Time chart>



### 3.1.19 Output instruction(OUTF)


Output instruction	OUTF	D	Applicable model					
			LP-S044, LP-S070					
OP	DATA type	Available device / Description / Range	Error	Zero	Carry	Borrow	Step	2
		Y, F, S, M, UB						
D	BIT	Contact to be ON for one scan on the falling edge of a pulse						
		Not applicable						

#### <Ladder>



When the operation result executed to the OUTF turns OFF from ON, the output contact becomes ON for only one scan and then becomes OFF for any other cases.


#### <Time chart>



### 3.1.20 Output instruction(SET)


Output instruction SET D			Applicable model LP-S044, LP-S070				
OP	DATA type	Available device / Description / Range	Error	Zero	Carry	Borrow	Step
D	BIT	Y, F, S, T, C, M, UB					
		Contact to be maintained ON status					
		Not applicable					1

#### <Ladder>



- Once the contact is SET, even if the input condition turns OFF, it retains SET status.
- In order to turn OFF the contact, you should execute the RST instruction.


#### <Time chart>



### 3.1.21 Output instruction(SET Syyy.xx)

Output instruction    SET Syyy.xx    D			Applicable model LP-S044, LP-S070				
OP	DATA type	Available device / Description / Range	Error	Zero	Carry	Borrow	Step
D	BIT	S					
		yyy is group number(0 to 255), xx is step number (0 to 99)					
		Not applicable					1

#### <Ladder>




Step device

yyy: Group number(0 to 255)

xx: Step number(0 to 99)

1. If the input contact of current step number is ON while the previous step number is retaining ON status, the current step number turns ON and the previous step number turns OFF.
2. Even if the input contact turns OFF, S device at ON status still retains ON.
3. Syyy.00 is always ON status when starting the program.
4. In order to reset the Syyy.xx instruction, the input contact of Syyy.00 should become ON.


#### <Time chart>



### 3.1.22 Output instruction(RST)


Output instruction RST D			Applicable model LP-S044, LP-S070				
OP	DATA type	Available device / Description / Range	Error	Zero	Carry	Borrow	Step
D	BIT	Y, F, S, T, C, M, UB					
		Contact to be maintained OFF status					
		Not applicable					1

#### <Ladder>



1. If the input condition turns ON, the corresponding contact becomes OFF.
2. Even if the input condition turns OFF, the corresponding contact still retains OFF.


#### <Time chart>



### 3.1.23 Reversal instruction(ALT)


Reversal instruction	ALT	D	Applicable model				
OP	DATA type	Available device / Description / Range	Error	Zero	Carry	Borrow	Step
D	BIT	Y, F, M ,UB					
		Data address to execute the operation					
		Not applicable					3

#### <Ladder>



Whenever the input condition turns ON from OFF, the output is reversed according to this, and this event is consecutively executed every operation cycle.

#### <Time chart>



### 3.1.24 Reversal instruction(NOT)

Reversal  
instruction    NOT


Applicable model  
LP-S044, LP-S070

<Ladder>



1. Transfers input by reversing.
2. A contact circuit is reversed as B contact circuit,  
B contact circuit is reversed as A contact circuit.

<Time chart>



### 3.1.25 Stack instruction(MPUSH)

Stack  
instruction    MPUSH

Applicable model  
LP-S044, LP-S070

The operation results executed to current are stored in the stack.

### 3.1.26 Stack instruction(MLOAD)

**Stack  
instruction**    **MLOAD**

Applicable model  
LP-S044, LP-S070

Loads the value stored in the stack.

### 3.1.27 Stack instruction(MPOP)

Stack  
instruction    MPOP

Applicable model  
LP-S044, LP-S070

Removes the data in the stack after reading it.

### 3.1.28 Exit instruction(END)

**Exit  
instruction END**

Applicable model  
LP-S044, LP-S070


Exits the program.

## 3.2 Application instruction

### 3.2.1 Counter instruction(CTU)


Counter instruction		CTU	S	N	Applicable model LP-S044, LP-S070					
OP	DATA type	Available device / Description / Range				Error	Zero	Carry	Borrow	Step
<b>S</b>	WORD	C, UW								
		Counter contact you want to use								
		0(h0000) to 65535(hFFFF)								5
<b>N</b>	WORD	X, Y, M, S, T, C, D, Z, F, UW, integer								
		Setting value of counter								
		0(h0000) to 65535(hFFFF)								

#### <Ladder>



- If the pulse signal is applied to the input rung when the reset signal is OFF, the word value of S device is increased one by one, and then when it reaches the setting value N, the corresponding counter contact turns ON.
- If the reset signal turns ON, the word value of S device becomes 0.


#### <Time chart>



### 3.2.2 Counter instruction(CTD)


Counter instruction		CTD	S	N	Applicable model					
OP	DATA type	Available device / Description / Range				LP-S044, LP-S070				
S	WORD	C, UW					Error	Zero	Carry	Borrow
		Counter contact you want to use								
		0(h0000) to 65535(hFFFF)								Step
N	WORD	X, Y, M, S, T, C, D, Z, F, UW, integer								
		Setting value of counter								
		0(h0000) to 65535(hFFFF)								5

#### <Ladder>



- If the pulse signal is applied to the input rung when the reset signal is OFF, the word value of S device is decreased one by one, and then when it reaches 0, the corresponding counter contact turns ON.
- If the reset signal is ON, the word value of S device becomes the setting value "N".


#### <Time chart>



### 3.2.3 Counter instruction(CTUD)


Counter instruction	CTUD	S	N	Applicable model	
OP	DATA type	Available device / Description / Range			
<b>S</b>	WORD	C, UW		LP-S044, LP-S070	
		Counter contact you want to use			
		0(h0000) to 65535(hFFFF)			
<b>N</b>	WORD	X, Y, M, S, T, C, D, Z, F, UW, integer		Error Zero Carry Borrow Step 5	
		Setting value of counter			
		0(h0000) to 65535(hFFFF)			

#### <Ladder>



1. If the count-up pulse is applied to the input rung when the reset signal is OFF, the the word value of S device is increased one by one. Likewise, if the count-down pulse is applied to the input rung, the word value of S device is decreased one by one.
2. If the word value of S device is greater than the setting value "N", the corresponding counter contact turns ON, and if the word value of S device is less than the setting value "N", the corresponding counter contact turns OFF.
3. If the reset signal is ON, the word value of S device becomes 0.


#### <Time chart>



### 3.2.4 Counter instruction(CTR)


Counter instruction		CTR	S	N	Applicable model					
OP	DATA type	Available device / Description / Range				LP-S044, LP-S070				
S	WORD	C, UW					Error	Zero	Carry	Borrow
		Counter contact you want to use								
		0(h0000) to 65535(hFFFF)								Step 5
N	WORD	X, Y, M, S, T, C, D, Z, F, UW, integer								
		Setting value of counter								
		0(h0000) to 65535(hFFFF)								

#### <Ladder>



- If the pulse signal is applied to the input rung when the reset signal is OFF, the word value of S device is increased one by one, and then when it reaches 0, the corresponding counter contact turns ON.
- If the pulse is continuously being input even after the reset signal is ON, the word value of S device is restarted at 0 again and the corresponding counter contact becomes OFF.
- Even if the reset signal turns ON, the word value of S device becomes 0.


#### <Time chart>



### 3.2.5 Timer instruction(TON)


Timer instruction TON S N			Applicable model LP-S044, LP-S070				
OP	DATA type	Available device / Description / Range	Error	Zero	Carry	Borrow	Step
<b>S</b>	WORD	T, UW					
		Timer contact you want to use					
		0(h0000) to 65535(hFFFF)					5
<b>N</b>	WORD	X, Y, M, S, T, C, D, Z, F, UW, integer					
		Setting value of timer					
		0(h0000) to 65535(hFFFF)					

#### <Ladder>



- As soon as the input condition is ON, S device value of the timer is increased one by one and then when it reaches the setting value "N", the corresponding timer contact turns ON.
- If the input condition becomes OFF or encounters RSTxxx instruction, the corresponding timer contact turns OFF and the current value becomes 0.


#### <Time chart>



### 3.2.6 Timer instruction(TOFF)


Timer instruction		TOFF	S	N	Applicable model					
OP	DATA type	Available device / Description / Range				LP-S044, LP-S070				
S	WORD	T, UW					Error	Zero	Carry	Borrow
		Timer contact you want to use								
		0(h0000) to 65535(hFFFF)								Step 5
N	WORD	X, Y, M, S, T, C, D, Z, F, UW, integer								
		Setting value of timer								
		0(h0000) to 65535(hFFFF)								

#### <Ladder>



- As soon as the input condition is ON, S device value of the timer is changed into the setting value "N" and the corresponding timer contact becomes ON.
- If the input condition becomes OFF, the current value of the timer is decreased one by one and when it reaches "0", the corresponding timer contact becomes OFF.
- If it encounters RST Txxxx instruction, the corresponding timer contact turns OFF and the setting value becomes "0".


#### <Time chart>



### 3.2.7 Timer instruction(TMR)


Timer instruction		TMR	S	N	Applicable model					
OP	DATA type	Available device / Description / Range				Error	Zero	Carry	Borrow	Step
<b>S</b>	WORD	T, UW								
		Timer contact you want to use								
		0(h0000) to 65535(hFFFF)								
<b>N</b>	WORD	X, Y, M, S, T, C, D, Z, F, UW, integer								
		Setting value of timer								
		0(h0000) to 65535(hFFFF)								

#### <Ladder>



- When the input signal is ON, the S device value of the timer is increased. And when the input signal is OFF, even if its value does not reach the setting value "N", it retains the current status of its value, and when the input signal is ON again it is increased from that value.
- When the S device value reaches the setting value "N", the corresponding timer contact turns ON. If it encounters RST Txxxx instruction, the corresponding timer contact turns OFF and the S device value becomes "0".


#### <Time chart>



### 3.2.8 Timer instruction(TMON)


Timer instruction TMON S N			Applicable model LP-S044, LP-S070				
OP	DATA type	Available device / Description / Range	Error	Zero	Carry	Borrow	Step
S	WORD	T, UW					
		Timer contact you want to use					
		0(h0000) to 65535(hFFFF)					5
N	WORD	X, Y, M, S, T, C, D, Z, F, UW, integer					
		Setting value of timer					
		0(h0000) to 65535(hFFFF)					

#### <Ladder>



- As soon as the input condition is ON, the corresponding timer contact turns ON, and the S device value of the timer is changed into the setting value "N" then it is decreasing.
- Although the input condition is changed into ON/OFF in the middle of the execution, the timer is continuously operating, and when S device value of the timer reaches "0", the timer contact is to be OFF.
- When it encounters RSTxxx instruction, the corresponding timer contact will be OFF and the S device value of the timer will be "0".


#### <Time chart>



### 3.2.9 Timer instruction(TRTG)


Timer instruction		TRTG	S	N	Applicable model					
OP	DATA type	Available device / Description / Range				Error	Zero	Carry	Borrow	Step
<b>S</b>	WORD	T, UW								
		Timer contact you want to use								
<b>N</b>	WORD	0(h0000) to 65535(hFFFF)								
		X, Y, M , S, T, C, D, Z, F, UW, integer								
		Setting value of timer								
		0(h0000) to 65535(hFFFF)								

#### <Ladder>



- As soon as the input condition is ON, the corresponding timer contact turns ON and the S device value is changed into the setting value "N" then it is decreasing.
- If the input condition turns OFF in the middle of the execution and then becomes ON, the S device value is changed into the setting value "N" again then it will be decreasing.
- If it encounters the RST instruction, the corresponding timer contact turns OFF and the S device value is changed into "0".


#### <Time chart>




### 3.2.10 Control instruction(JMP)

Control instruction JMP LABEL			Applicable model LP-S044, LP-S070				
OP	DATA type	Available device / Description / Range	Error	Zero	Carry	Borrow	Step
LABEL	STRING	LABEL name					
		Label for the place to jump					
		STRING	◎				3

&lt;Ladder&gt;




1. Jump to the place where the LABEL is matched.
2. When executing the JMP instruction, it does not process the instructions between JMP to LABEL.
3. If the LABEL does not exist, error flag occurs.



### 3.2.11 Control instruction(LABEL)

Control instruction	LABEL	Label name	Applicable model				
OP	DATA type	Available device / Description / Range	LP-S044, LP-S070				
Label name	STRING	LABEL name Label for the place to be jumped STRING	Error	Zero	Carry	Borrow	Step
							3

<Ladder>




It is a destination for the JMP instruction.

### 3.2.12 Control instruction(FCALL)

Control instruction    FCALL    LABEL			Applicable model LP-S044, LP-S070				
OP	DATA type	Available device / Description / Range	Error	Zero	Carry	Borrow	Step
LABEL	STRING	LABEL name Label for the function to call STRING	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	3

#### <Ladder>




1. Calls the registered user defined function.
2. If you call an unused function, error flag occurs.
3. When you input the instruction statement, the number of operands should be matched.

### 3.2.13 Control instruction(FUNC)

Control instruction	FUNC	LABEL	Applicable model				
OP	DATA type	Available device / Description / Range	Error	Zero	Carry	Borrow	Step
LABEL	STRING	LABEL name					
		Label for the starting position of the function					
		STRING					3

<Ladder>




1. Represents the starting position of the user defined function.
2. It should be located behind the END sentence.
3. The virtual function device “V” is being used.
4. The RET sentence should be located in the last part of the FUNC statement.


### 3.2.14 Branch instruction(CALL)

Branch instruction CALL LABEL			Applicable model LP-S044, LP-S070				
OP	DATA type	Available device / Description / Range	Error	Zero	Carry	Borrow	Step
LABEL	STRING	LABEL name					
		Label for the function to call					
		STRING					3

&lt;Ladder&gt;




1. Calls the subroutine, such as "LABEL" name.  
(Executing the program between the SUBRT LABEL to RET instructions)
2. CALL LABEL can be used in duplicating, and the program between SUBRT LABEL to RET instructions should be located behind the END instruction.



### 3.2.15 Branch instruction(SUBRT)

Branch instruction	SUBRT	LABEL	Applicable model				
OP	DATA type	Available device / Description / Range	Error	Zero	Carry	Borrow	Step
LABEL	STRING	LABEL name					
		A label for the called function					
		STRING					3

#### <Ladder>



1. Displays the starting point of the CALL subroutine.
2. It should be located behind END and can not be used in duplicate.(For CALL statement, it is able to be used in duplicate)

### 3.2.16 Branch instruction(RET)

**Branch  
instruction    RET**


Applicable model  
LP-S044, LP-S070

Exits the subroutine

### 3.2.17 Loop instruction(FOR)

Loop instruction	FOR	N	Applicable model
OP	DATA type	Available device / Description / Range	
		Integer	
N	WORD	0(h0000) to 65535(hFFFF)	Error Zero Carry Borrow Step 3


&lt;Ladder&gt;



1. Sets the number of repetitions for the program with the NEXT instruction.
2. The program is repeated N times until encountering the NEXT.
3. The range for the number of repetitions is from 0 to 65535.

[Note]

The scan time can be longer than you expected therefore please use the WDT instruction in order not to exceed the setting value.



### 3.2.18 Loop instruction(NEXT)

Loop  
instruction    NEXT

Applicable model  
LP-S044, LP-S070

The program is repeated from the FOR instruction to the NEXT instruction.

### 3.2.19 Loop instruction(BREAK)

Loop  
instruction    BREAK


Applicable model  
LP-S044, LP-S070

Repeat operation is executed with FOR, NEXT instruction. With BREAK instruction the repeated operation stops even though repeated execution is not complete.


### 3.2.20 Master control instruction(MCS)

Master control instruction MCS N			Applicable model
OP	DATA type	Available device / Description / Range	
N	Invariable number	Integer MCS number (0 to 7) 0 to 7	Error Zero Carry Borrow Step 2

#### <Ladder>




1. If the input condition of MCS is ON, the program is executed to the MCR instruction which has the same number of MCS. And if the input condition turns OFF, the program does not execute the instruction.
2. MCS number "0" has the highest priority and MCS number "15" has the lowest priority, therefore you should use them in order of priority, and should clear them in reverse order.
3. When you execute the MCR instruction, if you clear the higher priority the MCS block, which has the lower priority, is cleared too.
4. MCS or MCR instruction should be used in order of its priority.



### 3.2.21 Master control instruction(MCR)

Master control instruction			MCR	N	Applicable model
OP	DATA type	Available device / Description / Range			
N	Invariable number	Integer			Error
		MCR number (0 to 7)			Zero
		0 to 7			Carry
					Borrow
					Step
					2

#### <Ladder>




Master control reset

Clears the registered master control by using the MCS instruction.

### 3.2.22 Interrupt instruction(EI)

Interrupt instruction		EI	Applicable model				
OP	DATA type	Available device / Description / Range	Error	Zero	Carry	Borrow	Step
		Not applicable					

<Ladder>




Enable Interrupt

1. Enables all interrupts.
2. Enables the entire time interrupts and external interrupts.
3. In order to use the individual interrupt, you should use ETI and EEI instructions.

### 3.2.23 Interrupt instruction(DI)

Interrupt instruction DI			Applicable model LP-S044, LP-S070				
OP	DATA type	Available device / Description / Range	Error	Zero	Carry	Borrow	Step

<Ladder>




Disable Interrupt

1. Disables all interrupts.
2. Disables the entire time interrupts and external interrupts.
3. In order to disable the individual interrupt, you should use the DTI and DEI instructions.

### 3.2.24 Interrupt instruction(ETI)

Interrupt instruction		ETI	Applicable model				
OP	DATA type	Available device / Description / Range	Error	Zero	Carry	Borrow	Step
Invariable number		Integer					
		0 to 7					1

<Ladder>



Enable Time Interrupt


1. Enables the individual time interrupt.
2. In order to use ETI, you should activate all interrupts by using EI instruction first.
3. Structure of the instructions

ETI Time Interrupt Number(0 to 7)

### 3.2.25 Interrupt instruction(EEI)

Interrupt instruction		EEI	Applicable model				
OP	DATA type	Available device / Description / Range	Error	Zero	Carry	Borrow	Step
	Invariable number	Integer					
		0 to 15					
			Error	Zero	Carry	Borrow	Step
							1

<Ladder>




1. Enables the individual external interrupt.
2. In order to use the EEI, you should activate all interrupts by using EI instruction first.
3. Structure of the instructions  
EEI External Interrupt Number(0 to 15)

### 3.2.26 Interrupt instruction(DTI)

Interrupt instruction		DTI	Applicable model				
OP	DATA type	Available device / Description / Range	Error	Zero	Carry	Borrow	Step
Invariable number		Integer					
		0 to 7					1

&lt;Ladder&gt;



Disable Time Interrupt


1. Disables the individual time interrupt.
2. Structure of the instructions

DTI Time Interrupt Number(0 to 7)

### 3.2.27 Interrupt instruction(DEI)

Interrupt instruction		DEI	Applicable model				
OP	DATA type	Available device / Description / Range	Error	Zero	Carry	Borrow	Step
	Invariable number	Integer					
		0 to 15					
			Error	Zero	Carry	Borrow	Step 1

<Ladder>



Disable External Interrupt


1. Disables the individual external interrupt.
2. Structure of the instructions

DEI External Interrupt Number(0 to 15)

### 3.2.28 Interrupt instruction(TINT)

Interrupt instruction		TINT	Applicable model				
OP	DATA type	Available device / Description / Range	Error	Zero	Carry	Borrow	Step
	Invariable number	Integer 0 to 7					
							1


&lt;Ladder&gt;



Time Interrupt

1. Represents the starting point of the time interrupt block.
2. In order to indicate the end of block, you should use the IRET instruction at the end of TINT block.
3. Structure of the instructions


TINT Time Interrupt Number(0 to 7)



### 3.2.29 Interrupt instruction(EINT)

Interrupt instruction		EINT	Applicable model				
OP	DATA type	Available device / Description / Range	Error	Zero	Carry	Borrow	Step
	Invariable number	Integer					
		0 to 15					
			1				

<Ladder>




External Interrupt

1. Represent the starting point of the external interrupt block.
2. In order to indicate the end of block, you should use the IRET instruction at the end of EINT block.
3. Structure of the instructions  
EINT External Interrupt Number(0 to 15)

### 3.2.30 Interrupt instruction(IRET)

Interrupt instruction		IRET	Applicable model				
OP	DATA type	Available device / Description / Range	Error	Zero	Carry	Borrow	Step
							1

<Ladder>




Interrupt Return

1. Represents the end of time interrupt and external interrupt blocks.
  2. As below, it is generally being used with TINT or EINT instruction as a pair.
- TINT to IRET  
EINT to IRET

### 3.2.31 Watchdog timer(WDT)

Watchdog timer WDT			Applicable model LP-S044, LP-S070				
OP	DATA type	Available device / Description / Range	Error	Zero	Carry	Borrow	Step

<Ladder>




1. Resets watch dog timer during the program operation.
2. When the operation time from 0 step to END is over than max. watch dog setting time, program operation stops and WDT instruction should be used.
3. Watch dog setting value is able to change by special device.
4. When resupply power, watch dog setting value is reset as 200ms.

### 3.2.32 Input comparison instruction(LOAD=)

Input comparison instruction		LOAD=	S1	S2	Applicable model
OP	DATA type	Available device / Description / Range			LP-S044, LP-S070
S1	INT	X, Y, F, Z, T, C, M, S, L, D, UW, integer Data or address to compare with S2 -32768(h8000) to 32767(h7FFF)		Error Zero Carry Borrow	Step 5
S2	INT	X, Y, F, Z, T, C, M, S, L, D, UW, integer Data or address to compare with S1 -32768(h8000) to 32767(h7FFF)			

&lt;Ladder&gt;




1. Compares the word value of S1 with that of S2, and if they are equal it turns ON.
2. If the word values of S1 and S2 are not equal, it turns OFF.
3. Executes the Signed comparison.  
(h8000(-32768) to hFFFF(-1) < 0 to h7FFF(32767))

Ex)	LOAD= H0001 H3456	Comparision result	OFF
	LOAD= H0001 H0001	Comparision result	ON

### 3.2.33 Input comparison instruction(LOAD>)

Input comparison instruction		LOAD>	S1	S2	Applicable model
OP	DATA type	Available device / Description / Range			
S1	INT	X, Y, F, Z, T, C, M, S, L, D, UW, integer			
		Data or address to compare with S2			
		-32768(h8000) to 32767(h7FFF)			
S2	INT	X, Y, F, Z, T, C, M, S, L, D, UW, integer			
		Data or address to compare with S1			
		-32768(h8000) to 32767(h7FFF)			

#### <Ladder>




1. If the word value of S1 is greater than that of S2, it turns ON.
2. If the word value of S1 is less than or equal to that of S2, it turns OFF.
3. Execute the Signed comparison.  
(h8000(-32768) to hFFFF(-1) < 0 to h7FFF(32767))

Ex)	LOAD> H0001 H3456	Comparision result →	OFF
	LOAD> H0F5D H0001	Comparision result →	ON

### 3.2.34 Input comparison instruction(LOAD<)

<b>Input comparison instruction</b>			<b>LOAD&lt;</b>	<b>S1</b>	<b>S2</b>	Applicable model				
						LP-S044, LP-S070				
OP	DATA type	Available device / Description / Range				Error	Zero	Carry	Borrow	Step
<b>S1</b>	INT	X, Y, F, Z, T, C, M, S, L, D, UW, integer Data or address to compare with S2 -32768(h8000) to 32767(h7FFF)								5
<b>S2</b>	INT	X, Y, F, Z, T, C, M, S, L, D, UW, integer Data or address to compare with S1 -32768(h8000) to 32767(h7FFF)								

&lt;Ladder&gt;




1. If the word value of S1 is less than that of S2, it turns ON.
2. If the word value of S1 is greater than or equal to that of S2, it turns OFF.
3. Executes the Signed comparision.  
(h8000(-32768) to hFFFF(-1) < 0 to hFFFF(32767))

Ex)	LOAD< H0001 H3456	Comparision result	ON
	LOAD< H0F5D H0001	Comparision result	OFF

### 3.2.35 Input comparison instruction(LOAD<>)

Input comparison instruction			LOAD<>	S1	S2	Applicable model
OP	DATA type	Available device / Description / Range				
S1	INT	X, Y, F, Z, T, C, M, S, L, D, UW, integer				
		Data or address to compare with S2				
		-32768(h8000) to 32767(h7FFF)				
S2	INT	X, Y, F, Z, T, C, M, S, L, D, UW, integer				
		Data or address to compare with S1				
		-32768(h8000) to 32767(h7FFF)				

#### <Ladder>




1. If the word values of S1 and S2 are not equal, it turns ON.
2. If the word values of S1 and S2 are equal, it turns OFF.
3. Executes the Signed comparision.  
(h8000(-32768) to hFFFF(-1) < 0 to h7FFF(32767))

Ex)	LOAD<> H0001 H3456	Comparision result →	ON
	LOAD<> H0002 H0002	Comparision result →	OFF

### 3.2.36 Input comparison instruction(LOAD>=)

<b>Input comparison instruction</b>			<b>LOAD&gt;=</b>	<b>S1</b>	<b>S2</b>	Applicable model
						LP-S044, LP-S070
<b>OP</b>	<b>DATA type</b>	<b>Available device / Description / Range</b>			<b>Error</b>	
<b>S1</b>	INT	X, Y, F, Z, T, C, M, S, L, D, UW, integer			Zero	
		Data or address to compare with S2			Carry	
		-32768(h8000) to 32767(h7FFF)			Borrow	
<b>S2</b>	INT	X, Y, F, Z, T, C, M, S, L, D, UW, integer			Step	
		Data or address to compare with S1				
		-32768(h8000) to 32767(h7FFF)				5

#### <Ladder>



1. If the word value of S1 is less than or equal to that of S2, it turns ON.
2. If the word value of S1 is greater than that of S2, it turns OFF.
3. Executes the Signed comparision.  
(h8000(-32768) to hFFFF(-1) < 0 to h7FFF(32767))

Ex)

LOAD&gt;= H0001 H3456

Comparision result

OFF

LOAD&gt;= H0F5D H0001


Comparision result

ON

### 3.2.37 Input comparison instruction(LOAD<=)

<b>Input comparison instruction</b>	<b>LOAD&lt;=</b>	<b>S1</b>	<b>S2</b>	Applicable model
				LP-S044, LP-S070
<b>OP</b>	<b>DATA type</b>	<b>Available device / Description / Range</b>		
<b>S1</b>	INT	X, Y, F, Z, T, C, M, S, L, D, UW, integer		<input type="checkbox"/> Error <input type="checkbox"/> Zero <input type="checkbox"/> Carry <input type="checkbox"/> Borrow <b>Step 5</b>
		Data or address to compare with S2		
		-32768(h8000) to 32767(h7FFF)		
<b>S2</b>	INT	X, Y, F, Z, T, C, M, S, L, D, UW, integer		
		Data or address to compare with S1		
		-32768(h8000) to 32767(h7FFF)		

#### <Ladder>




1. If the word value of S1 is less than or equal to that of S2, it turns ON.
2. If the word value of S1 is greater than that of S2, it turns OFF.
3. Executes the Signed comparision.  
(h8000(-32768) to hFFFF(-1) < 0 to h7FFF(32767))

Ex)	LOAD<= H0001 H3456	Comparision result →	ON
	LOAD<= HFF00 H3456	Comparision result →	OFF

### 3.2.38 Input comparison instruction(DLOAD=)

Input comparison instruction			DLOAD=	S1	S2	Applicable model										
OP	DATA type	Available device / Description / Range														
S1	DINT	X, Y, F, Z, T, C, M, S, L, D, UW, integer				LP-S044, LP-S070  <table border="1"><tr><td>Error</td><td>Zero</td><td>Carry</td><td>Borrow</td><td>Step</td></tr><tr><td></td><td></td><td></td><td></td><td>5</td></tr></table>	Error	Zero	Carry	Borrow	Step					5
Error	Zero	Carry	Borrow	Step												
				5												
Data or address to compare with S2																
-2147483648(h80000000) to 2147483647(hFFFFFFF)																
S2	DINT	X, Y, F, Z, T, C, M, S, L, D, UW, integer														
		Data or address to compare with S1														
		-2147483648(h80000000) to 2147483647(hFFFFFFF)														

## &lt;Ladder&gt;




1. If the double word values of S1 and S2 are equal, it turns ON.
2. If the double word values of S1 and S2 are not equal, it turns OFF.
3. Executes the Signed comparision.  
(h80000000(-2147483648) to hFFFFFFF(-1) < 0 to h7FFFFFFF(2147483647))

Ex)	DLOAD= H000100FF H34561000	Comparision result	OFF
	DLOAD= H00014000 H00014000	Comparision result	ON

### 3.2.39 Input comparison instruction(DLOAD>)

Input comparison instruction			DLOAD>	S1	S2	Applicable model					
OP	DATA type	Available device / Description / Range									
S1	DINT	X, Y, F, Z, T, C, M, S, L, D, UW, integer						Error	Zero	Carry	Borrow
		Data or address to compare with S2									
		-2147483648(h80000000) to 2147483647(hFFFFFFF)									Step 5
S2	DINT	X, Y, F, Z, T, C, M, S, L, D, UW, integer									
		Data or address to compare with S1									
		-2147483648(h80000000) to 2147483647(hFFFFFFF)									

&lt;Ladder&gt;




1. If the double word value of S1 is greater than that of S2, it turns ON.
2. If the double word value of S1 is less than or equal to that of S2, it turns OFF.
3. Executes the Signed comparision.  
(h80000000(-2147483648) to hFFFFFFF(-1) < 0 to hFFFFFFF(2147483647))

Ex)	DLOAD> H0001FFFF H3456FFFF	Comparision result	OFF
	DLOAD> H0F5D0F0F H00010F0F	Comparision result	ON

### 3.2.40 Input comparison instruction(DLOAD<)

Input comparison instruction				DLOAD<	S1	S2	Applicable model										
OP	DATA type	Available device / Description / Range															
S1	DINT	X, Y, F, Z, T, C, M, S, L, D, UW, integer						Error	Zero	Carry	Borrow	Step 5					
		Data or address to compare with S2															
		-2147483648(h80000000) to 2147483647(hFFFFFFF)															
S2	DINT	X, Y, F, Z, T, C, M, S, L, D, UW, integer															
		Data or address to compare with S1															
		-2147483648(h80000000) to 2147483647(hFFFFFFF)															

&lt;Ladder&gt;




1. If the double word value of S1 is less than that of S2, it turns ON.
2. If the double word value of S1 is greater than that of S2, it turns OFF.
3. Executes the Signed comparision.  
(h80000000(-2147483648) to hFFFFFFF(-1) < 0 to h7FFFFFFF(2147483647))

Ex)	DLOAD< H00013422 H3456DA12	Comparision result	ON
	DLOAD< H0F5D3321 H00010010	Comparision result	OFF

### 3.2.41 Input comparison instruction(DLOAD<>)

Input comparison instruction			DLOAD<>	S1	S2	Applicable model					
OP	DATA type	Available device / Description / Range					LP-S044, LP-S070	Step	Step	Step	
S1	DINT	X, Y, F, Z, T, C, M, S, L, D, UW, integer					LP-S044, LP-S070	Error	Zero	Carry	
		Data or address to compare with S2						Borrow			
		-2147483648(h80000000) to 2147483647(hFFFFFFF)								5	
S2	DINT	X, Y, F, Z, T, C, M, S, L, D, UW, integer					LP-S044, LP-S070				
		Data or address to compare with S1									
		-2147483648(h80000000) to 2147483647(hFFFFFFF)									

#### <Ladder>




- If the double word values of S1 and S2 are not equal, it turns ON.
- If the double word value of S1 and S2 are equal, it turns OFF.
- Executes the Signed comparision.  
(h80000000(-2147483648) to hFFFFFFF(-1) < 0 to h7FFFFFFF(2147483647))

Ex)	DLOAD<>	H0001239	H34562342	Comparision result	ON
	DLOAD<>	H0002DCD1	H0002DCD1	Comparision result	OFF

### 3.2.42 Input comparison instruction(DLOAD>=)

<b>Input comparison instruction</b>		<b>DLOAD&gt;= S1 S2</b>	Applicable model
			LP-S044, LP-S070
<b>OP</b>	<b>DATA type</b>	<b>Available device / Description / Range</b>	
S1	DINT	X, Y, F, Z, T, C, M, S, L, D, UW, integer Data or address to compare with S2 -2147483648(h80000000) to 2147483647(hFFFFFF)	Error Zero Carry Borrow Step 5
S2	DINT	integer, *, Z, X, Y, M, D, L, F, T, C, UW Data or address to compare with S1 -2147483648(h80000000) to 2147483647(hFFFFFF)	

#### <Ladder>




1. If the double word value of S1 is greater than or equal to that of S2, it turns ON.
2. If the double word value of S1 is less than that of S2, it turns OFF.
3. Executes the Signed comparision.  
(h80000000(-2147483648) to hFFFFFF(-1) < 0 to h7FFFFFF(2147483647))

Ex)	<b>DLOAD&gt;= H00010000 H345632DD</b>	Comparision result	<b>OFF</b>
	<b>DLOAD&gt;= H0F5DD123 H00010000</b>	Comparision result	<b>ON</b>

### 3.2.43 Input comparison instruction(DLOAD<=)

Input comparison instruction		DLOAD<= S1 S2	Applicable model
OP	DATA type	Available device / Description / Range	
S1	DINT	X, Y, F, Z, T, C, M, S, L, D, UW, integer	
		Data or address to compare with S2	
		-2147483648(h80000000) to 2147483647(hFFFFFFF)	Error Zero Carry Borrow Step 5
S2	DINT	X, Y, F, Z, T, C, M, S, L, D, UW, integer	
		Data or address to compare with S1	
		-2147483648(h80000000) to 2147483647(hFFFFFFF)	

#### <Ladder>




1. If the double word value of S1 is less than or equal to that of S2, it turns ON.
2. If the double word value of S1 is greater than that of S2, it turns OFF.
3. Executes the Signed comparision.  
(h80000000(-2147483648) to hFFFFFFF(-1) < 0 to h7FFFFFF(2147483647))

Ex)	DLOAD<= H00010000 H34560000	Comparision result	ON
	DLOAD<= HFF00AD12 H3456D567	Comparision result	OFF

### 3.2.44 Input comparison instruction(AND=)

Input comparison instruction				AND=	S1	S2	Applicable model									
OP	DATA type	Available device / Description / Range														
S1	INT	X, Y, F, Z, T, C, M, S, L, D, UW, integer					Error	Zero	Carry	Borrow	Step 5					
		Data or address to compare with S2														
		-32768(h8000) to 32767(h7FFF)														
S2	INT	X, Y, F, Z, T, C, M, S, L, D, UW, integer														
		Data or address to compare with S1														
		-32768(h8000) to 32767(h7FFF)														

#### <Ladder>




1. If the word values of S1 and S2 are equal, it turns ON.
2. If the word values of S1 and S2 are not equal, it turns OFF.
3. Executes the Signed comparision.  
(h8000(-32768) to hFFFF(-1) < 0 to h7FFF(32767))

Instruction	Condition	Comparision result
AND =	S1 = S2	ON

### 3.2.45 Input comparison instruction(AND>)

Input comparison instruction				AND>	S1	S2	Applicable model
OP	DATA type	Available device / Description / Range					
<b>S1</b>	INT	X, Y, F, Z, T, C, M, S, L, D, UW, integer					LP-S044, LP-S070  Error      Zero      Carry      Borrow      Step                                     5
		Data or address to compare with S2					
		-32768(h8000) to 32767(h7FFF)					
<b>S2</b>	INT	X, Y, F, Z, T, C, M, S, L, D, UW, integer					
		Data or address to compare with S1					
		-32768(h8000) to 32767(h7FFF)					

#### <Ladder>




- If the word value of S1 is greater than that of S2, it turns ON.
- If the word value of S1 is less than or equal to that of S2, it turns OFF.
- Executes the Signed comparision.  
(h8000(-32768) to hFFFF(-1) < 0 to h7FFF(32767))

Instruction	Condition	Comparision result
AND >	S1 > S2	ON

### 3.2.46 Input comparison instruction(AND<)

Input comparison instruction				AND<	S1	S2	Applicable model									
OP	DATA type	Available device / Description / Range														
S1	INT	X, Y, F, Z, T, C, M, S, L, D, UW, integer					Error	Zero	Carry	Borrow	Step 5					
		Data or address to compare with S2														
		-32768(h8000) to 32767(h7FFF)														
S2	INT	X, Y, F, Z, T, C, M, S, L, D, UW, integer														
		Data or address to compare with S1														
		-32768(h8000) to 32767(h7FFF)														

#### <Ladder>




1. If the word value of S1 is less than that of S2, it turns ON.
2. If the word value of S1 is greater than or equal to that of S2, it turns OFF.
3. Executes the Signed comparision.  
(h8000(-32768) to hFFFF(-1) < 0 to h7FFF(32767))

Instruction	Condition	Comparision result
AND <	S1 < S2	ON

### 3.2.47 Input comparison instruction(AND<>)

Input comparison instruction				AND<>	S1	S2	Applicable model
OP	DATA type	Available device / Description / Range					
S1	INT	X, Y, F, Z, T, C, M, S, L, D, UW, integer					LP-S044, LP-S070  Error      Zero      Carry      Borrow      Step                                                                           5
		Data or address to compare with S2					
		-32768(h8000) to 32767(h7FFF)					
S2	INT	X, Y, F, Z, T, C, M, S, L, D, UW, integer					
		Data or address to compare with S1					
		-32768(h8000) to 32767(h7FFF)					

#### <Ladder>




1. If the word values of S1 and S2 are not equal, it turns ON.
2. If the word values of S1 and S2 are equal, it turns OFF.
3. Executes the Signed comparision.  
(h8000(-32768) to hFFFF(-1) < 0 to h7FFF(32767))

Instruction	Condition	Comparision result
AND <>	S1 <> S2	ON

### 3.2.48 Input comparison instruction(AND>=)

<b>Input comparison instruction</b> <b>AND&gt;=</b> <b>S1</b> <b>S2</b>				Applicable model																				
<table border="1"> <thead> <tr> <th>OP</th><th>DATA type</th><th>Available device / Description / Range</th><th></th></tr> </thead> <tbody> <tr> <td rowspan="3"><b>S1</b></td><td rowspan="3">INT</td><td>X, Y, F, Z, T, C, M, S, L, D, UW, integer</td><td></td></tr> <tr><td>Data or address to compare with S2</td><td></td></tr> <tr><td>-32768(h8000) to 32767(h7FFF)</td><td></td></tr> <tr> <td rowspan="3"><b>S2</b></td><td rowspan="3">INT</td><td>X, Y, F, Z, T, C, M, S, L, D, UW, integer</td><td></td></tr> <tr><td>Data or address to compare with S1</td><td></td></tr> <tr><td>-32768(h8000) to 32767(h7FFF)</td><td></td></tr> </tbody> </table>				OP	DATA type	Available device / Description / Range		<b>S1</b>	INT	X, Y, F, Z, T, C, M, S, L, D, UW, integer		Data or address to compare with S2		-32768(h8000) to 32767(h7FFF)		<b>S2</b>	INT	X, Y, F, Z, T, C, M, S, L, D, UW, integer		Data or address to compare with S1		-32768(h8000) to 32767(h7FFF)		LP-S044, LP-S070
OP	DATA type	Available device / Description / Range																						
<b>S1</b>	INT	X, Y, F, Z, T, C, M, S, L, D, UW, integer																						
		Data or address to compare with S2																						
		-32768(h8000) to 32767(h7FFF)																						
<b>S2</b>	INT	X, Y, F, Z, T, C, M, S, L, D, UW, integer																						
		Data or address to compare with S1																						
		-32768(h8000) to 32767(h7FFF)																						
				<table border="1"> <tr><td>Error</td><td>Zero</td><td>Carry</td><td>Borrow</td><td>Step</td></tr> <tr><td></td><td></td><td></td><td></td><td>5</td></tr> </table>	Error	Zero	Carry	Borrow	Step					5										
Error	Zero	Carry	Borrow	Step																				
				5																				

#### <Ladder>




1. If the word value of S1 is greater than or equal to that of S2, it turns ON.
2. If the word value of S1 is less than that of S2, it turns OFF.
3. Executes the Signed comparision.  
(h8000(-32768) to hFFFF(-1) < 0 to h7FFF(32767))

Instruction	Condition	Comparision result
AND > =	S1 > = S2	ON

### 3.2.49 Input comparison instruction(AND<=)

Input comparison instruction		AND<=	S1	S2	Applicable model
OP	DATA type	Available device / Description / Range			
S1	INT	X, Y, F, Z, T, C, M, S, L, D, UW, integer			
		Data or address to compare with S2			
		-32768(h8000) to 32767(h7FFF)			
S2	INT	X, Y, F, Z, T, C, M, S, L, D, UW, integer			
		Data or address to compare with S1			
		-32768(h8000) to 32767(h7FFF)			

#### <Ladder>




1. If the word value of S1 is less than or equal to that of S2, it turns ON.
2. If the word value of S1 is greater than that of S2, it turns OFF.
3. Executes the Signed comparision.  
(h8000(-32768) to hFFFF(-1) < 0 to h7FFF(32767))

Instruction	Condition	Comparision result
AND <=	S1 <= S2	ON

### 3.2.50 Input comparison instruction(DAND=)

<b>Input comparison instruction</b> <b>DAND=</b> <b>S1</b> <b>S2</b>				Applicable model
				LP-S044, LP-S070
<b>OP</b>	<b>DATA type</b>	<b>Available device / Description / Range</b>		
<b>S1</b>	DINT	X, Y, F, Z, T, C, M, S, L, D, UW, integer	Data or address to compare with S2  -2147483648(h80000000) to 2147483647(h7FFFFFFF)	<input type="checkbox"/> Error <input type="checkbox"/> Zero <input type="checkbox"/> Carry <input type="checkbox"/> Borrow <input type="checkbox"/> Step 5
<b>S2</b>	DINT	X, Y, F, Z, T, C, M, S, L, D, UW, integer	Data or address to compare with S1  -2147483648(h80000000) to 2147483647(h7FFFFFFF)	

#### <Ladder>




1. If the double word values of S1 and S2 are equal, it turns ON.
2. If the double word values of S1 and S2 are not equal, it turns OFF.
3. Executes the Signed comparision.  
(h80000000(-2147483648) to hFFFFFFF(-1) < 0 to h7FFFFFF(2147483647))

Instruction	Condition	Comparision result
<b>DAND =</b>	<b>S1 = S2</b>	<b>ON</b>

### 3.2.51 Input comparison instruction(DAND>)

Input comparison instruction			DAND>	S1	S2	Applicable model										
OP	DATA type	Available device / Description / Range					Error	Zero	Carry	Borrow	Step					
S1	DINT	X, Y, F, Z, T, C, M, S, L, D, UW, integer					Error	Zero	Carry	Borrow	Step					
		Data or address to compare with S2														
		-2147483648(h80000000) to 2147483647(hFFFFFFF)														
S2	DINT	X, Y, F, Z, T, C, M, S, L, D, UW, integer					Error	Zero	Carry	Borrow	Step					
		Data or address to compare with S1														
		-2147483648(h80000000) to 2147483647(hFFFFFFF)														

#### <Ladder>




1. If the double word value of S1 is greater than that of S2, it turns ON.
2. If the double word value of S1 is less than or equal to that of S2, it turns OFF..
3. Executes the Signed comparision.  
(h80000000(-2147483648) to hFFFFFFF(-1) < 0 to h7FFFFFFF(2147483647))

Instruction	Condition	Comparision result
DAND >	S1 > S2	ON

### 3.2.52 Input comparison instruction(DAND<)

<b>Input comparison instruction</b> <b>DAND&lt;</b> <b>S1</b> <b>S2</b>				Applicable model										
				LP-S044, LP-S070										
<b>OP</b>	<b>DATA type</b>	<b>Available device / Description / Range</b>												
<b>S1</b>	DINT	X, Y, F, Z, T, C, M, S, L, D, UW, integer		<table border="1"> <tr> <td>Error</td><td>Zero</td><td>Carry</td><td>Borrow</td><td>Step</td></tr> <tr> <td></td><td></td><td></td><td></td><td>5</td></tr> </table>	Error	Zero	Carry	Borrow	Step					5
		Error	Zero		Carry	Borrow	Step							
							5							
Data or address to compare with S2														
-2147483648(h80000000) to 2147483647(hFFFFFFF)														
<b>S2</b>	DINT	X, Y, F, Z, T, C, M, S, L, D, UW, integer												
		Data or address to compare with S1												
		-2147483648(h80000000) to 2147483647(hFFFFFFF)												

#### <Ladder>




1. If the double word value of S1 is less than that of S2, it turns ON.
2. If the double word value of S1 is greater than or equal to that of S2, it turns OFF.
3. Executes the Signed comparision.  
(h80000000(-2147483648) to hFFFFFFF(-1) < 0 to h7FFFFFFF(2147483647))

Instruction	Condition	Comparision result
DAND <	S1 < S2	ON

### 3.2.53 Input comparison instruction(DAND<>)

Input comparison instruction				DAND<>	S1	S2	Applicable model				
<b>OP</b>	<b>DATA type</b>	<b>Available device / Description / Range</b>					LP-S044, LP-S070				
<b>S1</b>	DINT	X, Y, F, Z, T, C, M, S, L, D, UW, integer Data or address to compare with S2 -2147483648(h80000000) to 2147483647(hFFFFFFF)					Error	Zero	Carry	Borrow	Step
<b>S2</b>	DINT	X, Y, F, Z, T, C, M, S, L, D, UW, integer Data or address to compare with S1 -2147483648(h80000000) to 2147483647(hFFFFFFF)								5	



#### <Ladder>




1. If the double word values of S1 and S2 are not equal, it turns ON.
2. If the double word values of S1 and S2 are equal, it turns OFF.
3. Executes the Signed comparision.  
(h80000000(-2147483648) to hFFFFFFF(-1) < 0 to hFFFFFFF(2147483647))

Instruction	Condition	Comparision result
<b>DAND &lt;&gt;</b>	<b>S1 &lt; &gt; S2</b>	<b>ON</b>

### 3.2.54 Input comparison instruction(DAND>=)

<b>Input comparison instruction</b> <b>DAND&gt;= S1 S2</b>			Applicable model
			LP-S044, LP-S070
<b>OP</b>	<b>DATA type</b>	<b>Available device / Description / Range</b>	
<b>S1</b>	DINT	X, Y, F, Z, T, C, M, S, L, D, UW, integer	    
		Data or address to compare with S2	
		-2147483648(h80000000) to 2147483647(hFFFFFFF)	
<b>S2</b>	DINT	X, Y, F, Z, T, C, M, S, L, D, UW, integer	
		Data or address to compare with S1	
		-2147483648(h80000000) to 2147483647(hFFFFFFF)	

#### <Ladder>



1. If the double word value of S1 is greater than or equal to that of S2, it turns ON.
2. If the double word value of S1 is less than that of S2, it turns OFF.
3. Executes the Signed comparision.  
(h80000000(-2147483648) to hFFFFFFF(-1) < 0 to h7FFFFFFF(2147483647))

Instruction	Condition	Comparision result
DAND > =	S1 > = S2	ON


### 3.2.55 Input comparison instruction(DAND<=)

<b>Input comparison instruction</b>	<b>DAND&lt;= S1 S2</b>	Applicable model LP-S044, LP-S070
<b>OP</b>	<b>DATA type</b>	<b>Available device / Description / Range</b>

<b>S1</b>	DINT	X, Y, F, Z, T, C, M, S, L, D, UW, integer	Error Zero Carry Borrow Step 5
		Data or address to compare with S2	
		-2147483648(h80000000) to 2147483647(hFFFFFFF)	
<b>S2</b>	DINT	X, Y, F, Z, T, C, M, S, L, D, UW, integer	Error Zero Carry Borrow Step 5
		Data or address to compare with S1	
		-2147483648(h80000000) to 2147483647(hFFFFFFF)	

#### <Ladder>




1. If the double word value of S1 is less than or equal to that of S2, it turns ON.
2. If the double word value of S1 is greater than that of S2, it turns OFF.
3. Executes the Signed comparision.  
(h80000000(-2147483648) to hFFFFFFF(-1) < 0 to h7FFFFFF(2147483647))

Instruction	Condition	Comparision
<b>DAND &lt;=</b>	<b>S1 &lt;= S2</b>	<b>ON</b>

### 3.2.56 Input comparison instruction(OR=)

Input comparison instruction				OR=	S1	S2	Applicable model	
OP	DATA type	Available device / Description / Range						
S1	INT	X, Y, F, Z, T, C, M, S, L, D, UW, integer					LP-S044, LP-S070	
		Data or address to compare with S2						
		-32768(h8000) to 32767(h7FFF)						
S2	INT	X, Y, F, Z, T, C, M, S, L, D, UW, integer					Error      Zero      Carry      Borrow      Step _____ 5	
		Data or address to compare with S1						
		-32768(h8000) to 32767(h7FFF)						

#### <Ladder>




1. If the word value of S1 is equal to that of S2, it turns ON.
2. If the word value of S1 is not equal to that of S2, it turns OFF.
3. Executes the Signed comparision.  
(h8000(-32768) to hFFFF(-1) < 0 to h7FFF(32767))

Instruction	Condition	Comparision
OR =	S1 = S2	ON

### 3.2.57 Input comparison instruction(OR>)

Input comparison instruction				OR>	S1	S2	Applicable model		
OP	DATA type	Available device / Description / Range							
S1	INT	X, Y, F, Z, T, C, M, S, L, D, UW, integer				Error	LP-S044, LP-S070		
		Data or address to compare with S2							
		-32768(h8000) to 32767(h7FFF)							
S2	INT	X, Y, F, Z, T, C, M, S, L, D, UW, integer				Zero	Step		
		Data or address to compare with S1							
		-32768(h8000) to 32767(h7FFF)							

#### <Ladder>




- If the word value of S1 is greater than that of S2, it turns ON.
- If the word value of S1 is less than or equal to that of S2, it turns OFF.
- Executes the Signed comparision.  
(h8000(-32768) to hFFFF(-1) < 0 to h7FFF(32767))

Instruction	Condition	Comparision
OR >	S1 > S2	ON

### 3.2.58 Input comparison instruction(OR<)

Input comparison instruction				OR<	S1	S2	Applicable model									
OP	DATA type	Available device / Description / Range														
S1	INT	X, Y, F, Z, T, C, M, S, L, D, UW, integer					Error	Zero	Carry	Borrow	Step 5					
		Data or address to compare with S2														
		-32768(h8000) to 32767(h7FFF)														
S2	INT	X, Y, F, Z, T, C, M, S, L, D, UW, integer														
		Data or address to compare with S1														
		-32768(h8000) to 32767(h7FFF)														

#### <Ladder>




1. If the word value of S1 is less than that of S2, it turns ON.
2. If the word value of S1 is greater than or equal to that of S2, it turns OFF.
3. Executes the Signed comparision.  
(h8000(-32768) to hFFFF(-1) < 0 to h7FFF(32767))

Instruction	Condition	Comparision
OR <	S1 < S2	ON

### 3.2.59 Input comparison instruction(OR<>)

Input comparison instruction		OR<>	S1	S2	Applicable model
OP	DATA type	Available device / Description / Range			
S1	INT	X, Y, F, Z, T, C, M, S, L, D, UW, integer			
		Data or address to compare with S2			
		-32768(h8000) to 32767(h7FFF)			
S2	INT	X, Y, F, Z, T, C, M, S, L, D, UW, integer			
		Data or address to compare with S1			
		-32768(h8000) to 32767(h7FFF)			

#### <Ladder>




1. If the word value of S1 is not equal to that of S2, it turns ON.
2. If the word value of S1 is equal to that of S2, it turns OFF.
3. Executes the Signed comparision.  
(h8000(-32768) to hFFFF(-1) < 0 to h7FFF(32767))

Instruction	Condition	Comparision
OR <>	S1 <> S2	ON

### 3.2.60 Input comparison instruction(OR>=)

<b>Input comparison instruction</b> <b>OR&gt;=</b> <b>S1</b> <b>S2</b>			Applicable model
			LP-S044, LP-S070
<b>OP</b>	<b>DATA type</b>	<b>Available device / Description / Range</b>	
<b>S1</b>	INT	X, Y, F, Z, T, C, M, S, L, D, UW, integer	<input type="checkbox"/> Error <input type="checkbox"/> Zero <input type="checkbox"/> Carry <input type="checkbox"/> Borrow <input type="checkbox"/> Step 5
		Data or address to compare with S2	
		-32768(h8000) to 32767(h7FFF)	
<b>S2</b>	INT	X, Y, F, Z, T, C, M, S, L, D, UW, integer	
		Data or address to compare with S1	
		-32768(h8000) to 32767(h7FFF)	

#### <Ladder>



1. If the word value of S1 is greater than or equal to that of S2, it turns ON.
2. If the word value of S1 is less than that of S2, it turns OFF.
3. Executes the Signed comparision.  
(h8000(-32768) to hFFFF(-1) < 0 to h7FFF(32767))


Instruction	Condition	Comparision
OR > =	S1 > = S2	ON

### 3.2.61 Input comparison instruction(OR<=)

Input comparison instruction		OR<=	S1	S2	Applicable model
OP	DATA type	Available device / Description / Range			
S1	INT	X, Y, F, Z, T, C, M, S, L, D, UW, integer			
		Data or address to compare with S2			
		-32768(h8000) to 32767(h7FFF)			
S2	INT	X, Y, F, Z, T, C, M, S, L, D, UW, integer			
		Data or address to compare with S1			
		-32768(h8000) to 32767(h7FFF)			

Error	Zero	Carry	Borrow	Step
				5

#### <Ladder>




1. If the word value of S1 is less than or equal to that of S2, it turns ON.
2. If the word value of S1 is greater than that of S2, it turns OFF.
3. Executes the Signed comparision.  
(h8000(-32768) to hFFFF(-1) < 0 to h7FFF(32767))

Instruction	Condition	Comparision
OR <=	S1 <= S2	ON

### 3.2.62 Input comparison instruction(DOR=)

Input comparison instruction				DOR=	S1	S2	Applicable model	
OP	DATA type	Available device / Description / Range						
S1	DINT	X, Y, F, Z, T, C, M, S, L, D, UW, integer					LP-S044, LP-S070	
		Data or address to compare with S2						
		-2147483648(h80000000) to 2147483647(h7FFFFFFF)						
S2	DINT	X, Y, F, Z, T, C, M, S, L, D, UW, integer					Error      Zero      Carry      Borrow      Step [ ]      [ ]      [ ]      [ ]      [ ]      5	
		Data or address to compare with S1						
		-2147483648(h80000000) to 2147483647(h7FFFFFFF)						

#### <Ladder>




1. If the double word value of S1 is equal to that of S2, it turns ON.
2. If the double word value of S1 is not equal to that of S2, it turns OFF.
3. Executes the Signed comparision.  
(h80000000(-2147483648) to hFFFFFFF(-1) < 0 to h7FFFFFFF(2147483647))

Instruction	Condition	Comparision
DOR =	S1 = S2	ON

### 3.2.63 Input comparison instruction(DOR>)

Input comparison instruction				DOR>	S1	S2	Applicable model				
OP	DATA type	Available device / Description / Range						LP-S044, LP-S070			
S1	DINT	X, Y, F, Z, T, C, M, S, L, D, UW, integer						Error	Zero	Carry	Borrow
		Data or address to compare with S2									
		-2147483648(h80000000) to 2147483647(h7FFFFFFF)									Step 5
S2	DINT	X, Y, F, Z, T, C, M, S, L, D, UW, integer									
		Data or address to compare with S1									
		-2147483648(h80000000) to 2147483647(h7FFFFFFF)									

#### <Ladder>




1. If the double word value of S1 is greater than that of S2, it turns ON.
2. If the double word value of S1 is less than or equal to that of S2, it turns OFF.
3. Executes the Signed comparision.  
(h80000000(-2147483648) to hFFFFFFF(-1) < 0 to h7FFFFFFF(2147483647))

Instruction	Condition	Comparision
DOR >	S1 > S2	ON

### 3.2.64 Input comparison instruction(DOR<)

Input comparison instruction				DOR<	S1	S2	Applicable model	
OP	DATA type	Available device / Description / Range						
S1	DINT	X, Y, F, Z, T, C, M, S, L, D, UW, integer					LP-S044, LP-S070	
		Data or address to compare with S2						
		-2147483648(h80000000) to 2147483647(h7FFFFFFF)						
S2	DINT	X, Y, F, Z, T, C, M, S, L, D, UW, integer						
		Data or address to compare with S1						
		-2147483648(h80000000) to 2147483647(h7FFFFFFF)						

#### <Ladder>




1. If the double word value of S1 is less than that of S2, it turns ON.
2. If the double word value of S1 is greater than or equal to that of S2, it turns OFF.
3. Executes the Signed comparision.  
(h80000000(-2147483648) to hFFFFFFF(-1) < 0 to h7FFFFFFF(2147483647))

Instruction	Condition	Comparision
DOR <	S1 < S2	ON

### 3.2.65 Input comparison instruction(DOR<>)

Input comparison instruction			DOR<>	S1	S2	Applicable model
OP	DATA type	Available device / Description / Range				
S1	DINT	X, Y, F, Z, T, C, M, S, L, D, UW, integer				
		Data or address to compare with S2				
		-2147483648(h80000000) to 2147483647(h7FFFFFFF)				
S2	DINT	X, Y, F, Z, T, C, M, S, L, D, UW, integer				
		Data or address to compare with S1				
		-2147483648(h80000000) to 2147483647(h7FFFFFFF)				

#### <Ladder>




1. If the double word value of S1 is not equal to that of S2, it turns ON.
2. If the double word value of S1 is equal to that of S2, it turns OFF.
3. Executes the Signed comparision.  
(h80000000(-2147483648) to hFFFFFFF(-1) < 0 to h7FFFFFFF(2147483647))

Instruction	Condition	Comparision
DOR <>	S1 <> S2	ON

### 3.2.66 Input comparison instruction(DOR>=)

<b>Input comparison instruction</b>	<b>DOR&gt;=</b>	<b>S1    S2</b>	Applicable model						
			LP-S044, LP-S070						
<b>OP</b>	<b>DATA type</b>	<b>Available device / Description / Range</b>							
<b>S1</b>	DINT	X, Y, F, Z, T, C, M, S, L, D, UW, integer	<table border="1" style="display: inline-table; vertical-align: middle;"> <tr><td>Error</td></tr> <tr><td>Zero</td></tr> <tr><td>Carry</td></tr> <tr><td>Borrow</td></tr> <tr><td>Step</td></tr> <tr><td>5</td></tr> </table>	Error	Zero	Carry	Borrow	Step	5
		Error							
		Zero							
Carry									
Borrow									
Step									
5									
Data or address to compare with S2									
-2147483648(h80000000) to 2147483647(h7FFFFFFF)									
<b>S2</b>	DINT	X, Y, F, Z, T, C, M, S, L, D, UW, integer							
		Data or address to compare with S1							
		-2147483648(h80000000) to 2147483647(h7FFFFFFF)							

#### <Ladder>




1. If the double word value of S1 is greater than or equal to that of S2, it turns ON.
2. If the double word value of S1 is less than that of S2, it turns OFF.
3. Executes the Signed comparision.  
(h80000000(-2147483648) to hFFFFFFF(-1) < 0 to h7FFFFFFF(2147483647))

Instruction	Condition	Comparision
<b>DOR &gt; =</b>	<b>S1 &gt; = S2</b>	<b>ON</b>

### 3.2.67 Input comparison instruction(DOR<=)

Input comparison instruction			DOR<=	S1	S2	Applicable model
OP	DATA type	Available device / Description / Range				
S1	DINT	X, Y, F, Z, T, C, M, S, L, D, UW, integer				
		Data or address to compare with S2				Error
		-2147483648(h80000000) to 2147483647(h7FFFFFFF)				Zero
S2	DINT	X, Y, F, Z, T, C, M, S, L, D, UW, integer				Carry
		Data or address to compare with S1				Borrow
		-2147483648(h80000000) to 2147483647(h7FFFFFFF)				Step
						5

#### <Ladder>




1. If the double word value of S1 is less than or equal to that of S2, it turns ON.
2. If the double word value of S1 is greater than that of S2, it turns OFF.
3. Executes the Signed comparision.  
(h80000000(-2147483648) to hFFFFFFF(-1) < 0 to h7FFFFFFF(2147483647))

Instruction	Condition	Comparision
DOR <=	S1 <= S2	ON

### 3.2.68 Comparison instruction(CMP)

Comparison instruction		CMP	S1	S2	D	Applicable model LP-S044, LP-S070										
OP	DATA type	Available device / Description / Range					Error	Zero	Carry	Borrow	Step					
S1	INT	X, Y, F, Z, T, C, M, S, L, D, UW, integer					Error	Zero	Carry	Borrow	Step 7					
		Data or address to compare with S2														
		-32768(h8000) to 32767(h7FFF)														
S2	INT	X, Y, F, Z, T, C, M, S, L, D, UW, integer					Error	Zero	Carry	Borrow	Step 7					
		Data or address to compare with S1														
		-32768(h8000) to 32767(h7FFF)														
D	BIT	Y, M, UB					Error	Zero	Carry	Borrow	Step 7					
		Lead address of bit device to save the comparison result														
		Not applicable														

#### <Ladder>



Compares the word value of S1 with that of S2. The result is as below :


1. If S1 < S2, D bit turns ON.
2. If S1 = S2, D+1 bit turns ON.
3. If S1 > S2, D+2 bit turns ON.
4. Comparison executes the Signed operation.  
(h8000(-32768) to h7FFF(-1) < 0 to h7FFF(32767))



### 3.2.69 Comparison instruction(DCMP)

Comparison instruction		DCMP	S1	S2	D	Applicable model										
OP	DATA type	Available device / Description / Range					Error	Zero	Carry	Borrow	Step					
S1	DINT	X, Y, F, Z, T, C, M, S, L, D, UW, integer									7					
		Data or address to compare with S2														
		-2147483648(h80000000) to 2147483647(h7FFFFFFF)														
S2	DINT	X, Y, F, Z, T, C, M, S, L, D, UW, integer														
		Data or address to compare with S1														
		-2147483648(h80000000) to 2147483647(h7FFFFFFF)														
D	BIT	Y, M, UB						Lead address of bit device to save the comparision result								
		Lead address of bit device to save the comparision result						Not applicable								

#### <Ladder>



Compares the double word value of S1 with that of S2. The result is as below :


1. If S1 < S2, D bit turns ON.
2. If S1 = S2, D+1 bit turns ON.
3. If S1 > S2, D+2 bit turns ON.
4. Comparision executes the Signed operation.  
(h8000(-32768) to h7FFF(-1) < 0 to h7FFF(32767))



### 3.2.70 Comparison instruction(ACMP)

Comparison instruction		ACMP	S1	S2	D	N	Applicable model					
OP	DATA type	Available device / Description / Range						Error	Zero	Carry	Borrow	Step
S1	BIT	X, Y, F, T, C, M, UB										
		Lead address of data or bit device to compare with S2										
		Not applicable										
S2	BIT	X, Y, F, T, C, M, UB										
		Lead address of data or bit device to compare with S1										
		Not applicable										
D	BIT	Y, M, UB										
		Lead address of bit device to save the comparison result										
		Not applicable										
N	WORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer										
		The number of devices to compare										
		1 to 32										


#### <Ladder>



Compares the number of N bit values beginning with S1 bit with the number of N bit values beginning with S2 bit. As a result :

1. If S1 < S2, D bit turns ON.
2. If S1==S2, D+1 bit turns ON.
3. If S1>S2, D+2 bit turns ON.


Ex) When N=3,



### 3.2.71 Comparison instruction(CMPL)

Comparison instruction		CMPL	S1	S2	D	N	Applicable model					
OP	DATA type	Available device / Description / Range						Error	Zero	Carry	Borrow	Step
S1	INT	X, Y, F, Z, T, C, M, S, L, D, UW, integer										
		Data or data address to compare with S2										
		-32768(h8000) to 32767(hFFFF)										
S2	INT	X, Y, F, Z, T, C, M, S, L, D, UW, integer										
		Data or data address to compare with S1										
		-32768(h8000) to 32767(hFFFF)										
D	BIT	Y, M, UB										
		Lead address of bit device to save comparison result										
		Not applicable										
N	WORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer										
		The number of S2 data to compare with S1 data										
		As many as the number of devices remained in S1, S2 and D area										

#### <Ladder>



Compares the word value of S1 with the number of N word values beginning with S2 word. As a result :

1. If S1 < S2, D bit turns ON.
2. If S1 == S2, D+1 bit turns ON.
3. If S1 > S2, D+2 bit turns ON.


The comparison result of S2+1 is stored in bits from D+3 to D+5, like this way, the operation results are sequentially stored in D bits.

4. Comparison executes the Signed operation.  
(h8000(-32768) to hFFFF(-1) < 0 to h7FFF(32767))

### 3.2.72 Comparison instruction(DCMPL)

Comparison instruction		DCMPL	S1	S2	D	N	Applicable model LP-S044, LP-S070										
OP	DATA type	Available device / Description / Range						Error	Zero	Carry	Borrow	Sep					
S1	DINT	X, Y, F, Z, T, C, M, S, L, D, UW, integer						Error	Zero	Carry	Borrow	Sep					
		Data or data address to compare with S2															
		-2147483648(h80000000) to 2147483647(h7FFFFFFF)															
S2	DINT	X, Y, F, Z, T, C, M, S, L, D, UW, integer						Error	Zero	Carry	Borrow	Sep					
		Data or data address to compare with S1															
		-2147483648(h80000000) to 2147483647(h7FFFFFFF)															
D	BIT	Y, M, UB						Error	Zero	Carry	Borrow	Sep					
		Lead address of bit device to save comparision result															
		Not applicable															
N	WORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer						Error	Zero	Carry	Borrow	Sep					
		The number of S2 data to compare with S1 data															
		As many as the number of devices remained in S1, S2 and D area															

&lt;Ladder&gt;




Compares the double word S1 with the number of N double words beginning with double word S2. As a result :

1. If S1 < S2, D bit turns ON.
2. If S1 == S2, D+1 bit turns ON.
3. If S1 > S2, D+2 bit turns ON.

The comparison result of S2+1 is stored in bits from D+3 to D+5, like this way, the operation results are sequentially stored in D bits.


4. Comparison executes the Signed operation.  
(h80000000(-2147483648) to hFFFFFF(-1) < 0 to h7FFFFFF(2147483647))



### 3.2.73 Comparison instruction(BWCMP)


Comparison instruction	BWCMP	S1	S2	S3	D	Applicable model
OP	DATA type	Available device / Description / Range				
<b>S1</b>	INT	X, Y, M, S, T, C, D, Z, F, UW, integer				Error
		Data to compare with S2 and S3				Zero
		-32768(h8000) to 32767(h7FFF)				Carry
<b>S2</b>	INT	X, Y, M, S, T, C, D, Z, F, UW, integer				Borrow
		Data to compare with S1 and S3				Step
		-32768(h8000) to 32767(h7FFF)				9
<b>S3</b>	INT	X, Y, M, S, T, C, D, Z, F, UW, integer				
		Data to compare with S1 and S2				
		-32768(h8000) to 32767(h7FFF)				
<b>D</b>	BIT	Y, M, UB				
		Bit device address to save comparision result				
		Not applicable				

#### <Ladder>



Compare word value of S3 with the limited area between S1 and S2 word values. As a result :

1. If the value of S3 is less than the smaller value of the two(S1, S2), D bit turns ON.
2. If the value of S3 is equal to the smaller value of the two, D+1 bit turns ON.
3. If the value of S3 is located between the two values, D+2 bit turns ON.
4. If the value of S3 is equal to the larger value of the two, D+3 bit turns ON.
5. If the value of S3 is greater than the larger value of the two, D+4 bit turns ON.
6. Comparision executes the Signed operation.



Ex) In case of S3=h3300, S1=h1011, S2=h2020,

0	0	0	0	0
D+4	D+3	D+2	D+1	D


→ S3 is placed at E area. Therefore D+4 bit is ON

1	0	0	0	0
D+4	D+3	D+2	D+1	D

### 3.2.74 Comparison instruction(DBWCMP)

Comparison instruction		DBWCMP	S1	S2	S3	D	Applicable model									
OP	DATA type	Available device / Description / Range						Error	Zero	Carry	Borrow	Step				
<b>S1</b>	DINT	X, Y, M, S, T, C, D, Z, F, UW, integer										9				
		Data to compare with S2 and S3														
		-2147483648(h80000000) to 2147483647(h7FFFFFFF)														
<b>S2</b>	DINT	X, Y, M, S, T, C, D, Z, F, UW, integer										9				
		Data to compare with S1 and S3														
		-2147483648(h80000000) to 2147483647(h7FFFFFFF)														
<b>S3</b>	DINT	X, Y, M, S, T, C, D, Z, F, UW, integer										9				
		Data to compare with S1 and S2														
		-2147483648(h80000000) to 2147483647(h7FFFFFFF)														
<b>D</b>	BIT	Y, M, UB										9				
		Bit device address to save comparision result														
		Not applicable														


#### <Ladder>



Compares the double word value of S3 with the limited area between S1 and S2 word values.

As a result :


1. If the value of S3 is less than the smaller value of the two(S1, S2), D bit turns ON.
2. If the value of S3 is equal to the smaller value of the two, D+1 bit turns ON.
3. If the value of S3 is located between the two values, D+2 bit turns ON.
4. If the value of S3 is equal to the larger value of the two, D+3 bit turns ON.
5. If the value of S3 is greater than the larger value of the two, D+4 bit turns ON.
6. Comparision executes the Signed operation.



### 3.2.75 Transmission instruction(BMOV)

Transmission instruction BMOV S D			Applicable model LP-S044, LP-S070				
OP	DATA type	Available device / Description / Range	Error	Zero	Carry	Borrow	Step
<b>S</b>	BIT	X, Y, F, T, C, M, UB					
		Bit device number you want to transmit					
		Not applicable					5
<b>D</b>	BIT	Y, F, T, C, M, UB					
		Bit device address to save the transmitted data					
		Not applicable					

#### <Ladder>



Transmits the source bit to the destination bit.



### 3.2.76 Transmission instruction(MOV)

**Transmission instruction** MOV S D


Applicable model

LP-S044, LP-S070

OP	DATA type	Available device / Description / Range
S	WORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer
		Data to transmit or device number which have the data
		0(h0000) to 65535(hFFFF)
D	WORD	Y, F, Z, T, C, M, S, L, D, UW
		Device number to save transmitted data
		0(h0000) to 65535(hFFFF)

Error	Zero	Carry	Borrow	Step
				5

#### <Ladder>




Transmits the source word to the destination word.

S word → D word

### 3.2.77 Transmission instruction(DMOV)

Transmission instruction DMOV S D			Applicable model LP-S044, LP-S070				
OP	DATA type	Available device / Description / Range	Error	Zero	Carry	Borrow	Step
<b>S</b>	DWORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer					
		Data to transmit or device number which have the data					
		0(h0000) to 4294967295(hFFFFFFF)					5
<b>D</b>	DWORD	Y, F, Z, T, C, M, S, L, D, UW					
		Device number to save transmitted data					
		0(h0000) to 4294967295(hFFFFFFF)					

#### <Ladder>




Transmits the source double word to the destination double word.




### 3.2.78 Transmission instruction(BMOVL)

Transmission instruction BMOVL S D N				Applicable model LP-S044, LP-S070					
OP	DATA type	Available device / Description / Range			Error	Zero	Carry	Borrow	Step
<b>S</b>	BIT	X, Y, F, T, C, M, UB							
		Bit device number you want to transmit							
		Not applicable							7
<b>D</b>	BIT	Y, F, T, C, M, UB							
		Bit device address to save the transmitted data							
		Not applicable							
<b>N</b>	WORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer							
		The number of destination bit devices to save the transmitted data							
		To the remained devices in corresponding D area							

#### <Ladder>




Transmits the source bit to the number of N bits beginning with D, one by one.




### 3.2.79 Transmission instruction(MOVL)

Transmission instruction			MOVL	S	D	N	Applicable model									
OP	DATA type	Available device / Description / Range						Error	Zero	Carry	Borrow	Step				
<b>S</b>	WORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer														
		Data to transmit or device number which have the data														
		0(h0000) to 65535(hFFFF)														
<b>D</b>	WORD	Y, F, Z, T, C, M, S, L, D, UW														
		Device number to save transmitted data														
		0(h0000) to 65535(hFFFF)														
<b>N</b>	WORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer														
		The number of destination bit devices to save the transmitted data														
		To the remained devices in corresponding D area														

#### <Ladder>




Transmits the source word to the number of N words beginning with D, one by one.




### 3.2.80 Transmission instruction(DMOVL)

Transmission instruction DMOVL S D N			Applicable model LP-S044, LP-S070				
OP	DATA type	Available device / Description / Range	Error	Zero	Carry	Borrow	Step
<b>S</b>	DWORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer					
		Data to transmit or device number which have the data					
		0(h0000) to 4294967295(hFFFFFFF)					7
<b>D</b>	DWORD	Y, F, Z, T, C, M, S, L, D, UW					
		Device number to save transmitted data					
		0(h0000) to 4294967295(hFFFFFFF)					
<b>N</b>	WORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer					
		The number of destination bit devices to save the transmitted data					
		To the remained devices in corresponding D area					

#### <Ladder>




Transmit the source double word to the number of N double words beginning with D, one by one.




### 3.2.81 Transmission instruction(BMOVG)

Transmission instruction BMOVG S D N					Applicable model LP-S044, LP-S070				
OP	DATA type	Available device / Description / Range			Error	Zero	Carry	Borrow	Step
<b>S</b>	BIT	X, Y, F, T, C, M, UB							
		Bit device number you want to transmit							
		Not applicable							7
<b>D</b>	BIT	Y, F, T, C, M, UB							
		Bit device address to save the transmitted data							
		Not applicable							
<b>N</b>	WORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer							
		The number of bit devices to save to be transmitted data and the transmitted data							
		To the remained devices in corresponding S, D areas							

#### <Ladder>



Transmits the number of N bit groups beginning with (S) to the number of N bit groups beginning with (D), in batches.



### 3.2.82 Transmission instruction(MOVG)

**Transmission instruction** **MOVG**      **S**    **D**    **N**


Applicable model

LP-S044, LP-S070


OP	DATA type	Available device / Description / Range
<b>S</b>	WORD	X, Y, F, Z, T, C, M, S, L, D, UW
		Data to transmit or device number which have the data
		0(h0000) to 65535(hFFFF)
<b>D</b>	WORD	Y, F, Z, T, C, M, S, L, D, UW
		Device number to save transmitted data
		0(h0000) to 65535(hFFFF)
<b>N</b>	WORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer
		The number of bit devices to save to be transmitted data and the transmitted data
		To the remained devices in corresponding S, D areas

Error	Zero	Carry	Borrow	Step
				7

#### <Ladder>




Transmit the number of N word groups beginning with (S), to the number of N word groups beginning with (D), in batches.




### 3.2.83 Transmission instruction(DMOVG)

Transmission instruction DMOVG S D N					Applicable model LP-S044, LP-S070				
OP	DATA type	Available device / Description / Range			Error	Zero	Carry	Borrow	Step
<b>S</b>	DWORD	X, Y, F, Z, T, C, M, S, L, D ,UW							
		Data to transmit or device number which have the data							
		0(h0000) to 4294967295(hFFFFFFF)							7
<b>D</b>	DWORD	Y, F, Z, T, C, M, S, L, D ,UW							
		Device number to save transmitted data							
		0(h0000) to 4294967295(hFFFFFFF)							
<b>N</b>	WORD	X, Y, F, Z, T, C, M, S, L, D ,UW, integer							
		The number of bit devices to save to be transmitted data and the transmitted data							
		To the remained devices in corresponding S, D areas							

#### <Ladder>




Transmit the number of N double word groups beginning with (S) to the number of N double word groups beginning with (D), in batches.




### 3.2.84 Transmission instruction(BCMOV)

Transmission instruction BMOV S D			Applicable model LP-S044, LP-S070				
OP	DATA type	Available device / Description / Range	Error	Zero	Carry	Borrow	Step
S	BIT	X, Y, F, T, C, M, UB					
		Bit device number you want to transmit					
		Not applicable					5
D	BIT	Y, F, T, C, M, UB					
		Bit device address to save the transmitted data					
		Not applicable					

#### <Ladder>





Reverses the source device and then transmits it to the destination bit.



### 3.2.85 Transmission instruction(CMOV)

Transmission instruction CMOV S D			Applicable model LP-S044, LP-S070				
OP	DATA type	Available device / Description / Range	Error	Zero	Carry	Borrow	Step
<b>S</b>	WORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer					
		Data to transmit or device number which have the data					
		0(h0000) to 65535(hFFFF)					5
<b>D</b>	WORD	Y, F, Z, T, C, M, S, L, D, UW					
		Device number to save transmitted data					
		0(h0000) to 65535(hFFFF)					


#### <Ladder>




### 3.2.86 Transmission instruction(DCMOV)

Transmission instruction DCMOV S D			Applicable model LP-S044, LP-S070				
OP	DATA type	Available device / Description / Range	Error	Zero	Carry	Borrow	Step
S	DWORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer					
		Data to transmit or device number which have the data					
		0(h0000) to 4294967295(hFFFFFFF)					5
D	DWORD	Y, F, Z, T, C, M, S, L, D, UW					
		Device number to save transmitted data					
		0(h0000) to 4294967295(hFFFFFFF)					

#### <Ladder>




Reverses the source double word and then transmits it to the destination double word.



### 3.2.87 Exchange instruction(XCH)

Exchange instruction		XCH	S1	S2	Applicable model				
OP	DATA type	Available device / Description / Range			Error	Zero	Carry	Borrow	Step
<b>S1</b>	WORD	Y, F, Z, T, C, M, S, L, D, UW							
		Data device number to be exchanged							
		0(h0000) to 65535(hFFFF)							5
<b>S2</b>	WORD	Y, F, Z, T, C, M, S, L, D, UW							
		Data device number to be exchanged							
		0(h0000) to 65535(hFFFF)							

#### <Ladder>




Exchanges a data in S1 word and a data in S2 word each other.



### 3.2.88 Exchange instruction(DXCH)

Exchange instruction		DXCH	S1	S2	Applicable model LP-S044, LP-S070									
OP	DATA type	Available device / Description / Range			Error	Zero	Carry	Borrow	Step					
S1	DWORD	Y, F, Z, T, C, M, S, L, D, UW			Error	Zero	Carry	Borrow	Step 5					
		Data device number to be exchanged												
		0(h0000) to 4294967295(hFFFFFFF)												
S2	DWORD	Y, F, Z, T, C, M, S, L, D, UW			Error	Zero	Carry	Borrow	Step 5					
		Data device number to be exchanged												
		0(h0000) to 4294967295(hFFFFFFF)												

#### <Ladder>




Exchanges a data in the double word S1 and a data in the double word S2 each other.




### 3.2.89 Exchange instruction(AXCH)

Exchange instruction		AXCH	S1	S2	N	Applicable model										
OP	DATA type	Available device / Description / Range					Error	Zero	Carry	Borrow	Step					
S1	BIT	Y, F, T, C, M, UB					Error	Zero	Carry	Borrow	Step					
		Bit device address of the data to be exchanged														
		Not applicable														
S2	BIT	Y, F, T, C, M, UB					Error	Zero	Carry	Borrow	Step					
		Bit device address of the data to be exchanged														
		Not applicable														
N	WORD	Y, F, Z, T, C, M, S, L, D, UW, integer					Error	Zero	Carry	Borrow	Step					
		The number of the data bits to be exchanged														
		To the device range remained in corresponding S1 and S2 areas.														

#### <Ladder>




Exchanges the number of N bits beginning with S1 with the number of N bits beginning from S2 each other.




### 3.2.90 Exchange instruction(SWAP)

Exchange instruction SWAP D			Applicable model LP-S044, LP-S070				
OP	DATA type	Available device / Description / Range	Error	Zero	Carry	Borrow	Step
D	WORD	Y, F, Z, T, C, M, S, L, D, UW Data address to exchange upper and lower bit 0(h0000) to 65535(hFFFF)					3

&lt;Ladder&gt;




Exchanges the high order bytes of the designated word with its low order bytes each other.




### 3.2.91 Exchange instruction(DSWAP)

<b>Exchange instruction</b>	<b>DSWAP</b>	<b>D</b>	Applicable model LP-S044, LP-S070
<b>OP</b>	<b>DATA type</b>	<b>Available device / Description / Range</b>	
<b>D</b>	DWORD	Y, F, Z, T, C, M, S, L, D, UW	Error
		Data address to exchange upper and lower bit	Zero
		0(h0000) to 4294967295(hFFFFFFF)	Carry
	Borrow		
	Step		
	3		

&lt;Ladder&gt;




Exchanges the high order word of the designated double word with its low order word.




### 3.2.92 Rotation instruction(ROR)

Rotation instruction		ROR	S	C	Applicable model LP-S044, LP-S070						
OP	DATA type	Available device / Description / Range					Error	Zero	Carry	Borrow	Step
<b>S</b>		Y, F, Z, T, C, M, S, L, D, UW									
<b>C</b>		Data address to execute the operation 0(h0000) to 65535(hFFFF)									
<b>C</b>		X, Y, F, Z, T, C, M, S, L, D, UW, integer The number of bits to rotate right side 0 to 255									

#### <Ladder>




Rotates the source word to the right side by the number of C bits.




### 3.2.93 Rotation instruction(DROR)

Rotation instruction		DROR	S	C	Applicable model					
OP	DATA type	Available device / Description / Range				Error	Zero	Carry	Borrow	Step
<b>S</b>	DWORD	X, F, Z, T, C, M, S, L, D, UW				Error	Zero	Carry	Borrow	Step
		Data address to execute the operation 0(h0000) to 4294967295(hFFFFFFF)								
<b>C</b>	WORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer				5				
		The number of bits to rotate right side 0 to 255								

#### <Ladder>




Rotates the source double word to the right side by the number of C bits.




### 3.2.94 Rotation instruction(AROR)

Rotation instruction		AROR	S	N	C	Applicable model LP-S044, LP-S070						
OP	DATA type	Available device / Description / Range						Error	Zero	Carry	Borrow	Step
S	BIT	Y, F, T, C, M, UB										
		Start address for bit device of the data to execute the operation										
		Not applicable										
N	WORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer										
		The number of bit device to execute the operation from start address										
		To the remained device range in corresponding S area										
C	WORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer										
		The number of bits to rotate right side										
		0 to 255										

#### <Ladder>




Within the number of N bits, bits rotate to the right side by the number of C bits beginning with S bit.




### **3.2.95 Rotation instruction(RORC)**

Rotation instruction		RORC	S	C	Applicable model
OP	DATA type	Available device / Description / Range			
<b>S</b>	WORD	Y, F, Z, T, C, M, S, L, D, UW			
		Data address to execute the operation			
		0(h0000) to 65535(hFFFF)			
<b>C</b>	WORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer			
		The number of bits to rotate right side			
		0 to 255			

## **<Ladder>**




Rotates the source word including carry bit, to the right side by the number of C bits.




### 3.2.96 Rotation instruction(DRORC)

Rotation instruction		DRORC	S	C	Applicable model LP-S044, LP-S070										
OP	DATA type	Available device / Description / Range				Error	Zero	Carry	Borrow	Step					
S	DWORD	Y, F, Z, T, C, M, S, L, D, UW								5					
		Data address to execute the operation													
		0(h0000) to 4294967295(hFFFFFFF)													
C	WORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer													
		The number of bits to rotate right side													
		0 to 255													

#### <Ladder>




Rotates the source double word including carry bit, to the right side by the number of C bits.




### 3.2.97 Rotation instruction(ARORC)

Rotation instruction		ARORC	S	N	C	Applicable model										
OP	DATA type	Available device / Description / Range					Error	Zero	Carry	Borrow	Step					
<b>S</b>	BIT	Y, F, T, C, M, UB					Error	Zero	Carry	Borrow	Step					
		Start address for bit device of the data to execute the operation														
		Not applicable														
<b>N</b>	WORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer									7					
		The number of bit device to execute the operation from start address														
		To the remained device range in corresponding S area														
<b>C</b>	WORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer														
		The number of bits to rotate right side														
		0 to 255														

#### <Ladder>




Within the number of N bits, rotates the designated bits including carry bit to the right side by the number of C bits.




### 3.2.98 Rotation instruction(ROL)

Rotation instruction		ROL	S	C	Applicable model LP-S044, LP-S070					
OP	DATA type	Available device / Description / Range				Error	Zero	Carry	Borrow	Step
S	WORD	Y, F, Z, T, C, M, S, L, D, UW								
		Data address to execute the operation								
		0(h0000) to 65535(hFFFF)								
C	WORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer								
		The number of bits to rotate left side								
		0 to 255								

#### <Ladder>




Rotates the source word to the left side by the number of C bits.




### 3.2.99 Rotation instruction(DROL)

Rotation instruction		DROL	S	C	Applicable model					
OP	DATA type	Available device / Description / Range				Error	Zero	Carry	Borrow	Step
<b>S</b>	DWORD	Y, F, Z, T, C, M, S, L, D, UW								5
		Data address to execute the operation 0(h0000) to 4294967295(hFFFFFFF)								
<b>C</b>	WORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer								5
		The number of bits to rotate left side 0 to 255								

#### <Ladder>




Rotates the source double word to the left side by the number of C bits.




### 3.2.100 Rotation instruction(AROL)

Rotation instruction		AROL	S	N	C	Applicable model LP-S044, LP-S070						
OP	DATA type	Available device / Description / Range						Error	Zero	Carry	Borrow	Step
S	BIT	Y, F, T, C, M, UB										
		Start address for bit device of the data to execute the operation										
		Not applicable										
N	WORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer										
		The number of bit device to execute the operation from start address										
		To the remained device range in corresponding S area										
C	WORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer										
		The number of bits to rotate left side										
		0 to 255										

#### <Ladder>




Within the number of N bits, rotates the designated bits beginning with the S bit to the left side by the number of C bits.




### 3.2.101 Rotation instruction(ROLC)

Rotation instruction	ROLC	S	C	Applicable model
				LP-S044, LP-S070
<b>OP</b>	<b>DATA type</b>	<b>Available device / Description / Range</b>		
<b>S</b>	WORD	Y, F, Z, T, C, M, S, L, D, UW Data address to execute the operation 0(h0000) to 65535(hFFFF)		Error Zero Carry Borrow Step
<b>C</b>	WORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer The number of bits to rotate right side 0 to 255		5

#### <Ladder>




Rotates the source word including carry bit to the left side by the number of C bits.




### 3.2.102 Rotation instruction(DROLC)

Rotation instruction		DROLC	S	C	Applicable model LP-S044, LP-S070									
OP	DATA type	Available device / Description / Range			Error	Zero	Carry	Borrow	Step					
S	DWORD	Y, F, Z, T, C, M, S, L, D, UW							5					
		Data address to execute the operation												
		0(h0000) to 4294967295(hFFFFFFF)												
C	WORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer												
		The number of bits to rotate left side												
		0 to 255												

#### <Ladder>




Rotates the source double word including the carry bit to the left side by the number of C bits.




### 3.2.103 Rotation instruction(AROLC)

Rotation instruction		AROLC	S	N	C	Applicable model										
OP	DATA type	Available device / Description / Range					Error	Zero	Carry	Borrow	Step					
S	BIT	Y, F, T, C, M, UB							<input checked="" type="checkbox"/>	<input type="checkbox"/>	7					
		Start address for bit device of the data to execute the operation														
		Not applicable														
N	WORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer							<input type="checkbox"/>	<input checked="" type="checkbox"/>	7					
		The number of bit device to execute the operation from start address														
		To the remained device range in corresponding S area														
C	WORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer							<input type="checkbox"/>	<input checked="" type="checkbox"/>	7					
		The number of bits to rotate left side														
		0 to 255														

#### <Ladder>




Within the range from the source bit to the N bit, rotates the designated bits including the carry bit to the left side by the number of C bits beginning with the S bit.




### 3.2.104 Movement instruction(SFTR)

Movement instruction	SFTR	S	N	Applicable model
				LP-S044, LP-S070
<b>OP</b>	<b>DATA type</b>	<b>Available device / Description / Range</b>		
<b>S</b>	WORD	Y, F, Z, T, C, M, S, L, D, UW		
		Data address to execute the operation		
		0(h0000) to 65535(hFFFF)		
<b>N</b>	WORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer		
		The number of bits to rotate right side		
		0 to 16		
		Error	Zero	Carry
				Borrow
				Step 9

#### <Ladder>




1. Within the S word, moves the 16-bit of S word to the right side by the number of N bits.
2. If the  $N_{th}$  bit from the low order bit is 1, carry bit is SET.




### 3.2.105 Movement instruction(ASFTR)

Movement instruction	ASFTR	S	N1	N2	Applicable model
OP	DATA type	Available device / Description / Range			
<b>S</b>		Y, F, T, C, M, UB			Error
		Start bit position of the data to execute the operation			Zero
		Not applicable			Carry
<b>N1</b>		X, Y, F, Z, T, C, M, S, L, D, UW, integer			Borrow
		The number of bits from the designated position as S			Step
		0 to 32			9
<b>N2</b>		X, Y, F, Z, T, C, M, S, L, D, UW, integer			
		The number of bits to rotate right side			
		0 to 32			

#### <Ladder>




- From the source bit, N1 bits moves to the right side as N2 in the range.
- The high order bits, which are the number of movement, have "0" as their value.
- If the value of N2 is greater than N1, the values from source bit to N bit are shifted to "0".




### 3.2.106 Movement instruction(SFTL)

Movement instruction	SFTL	S N	Applicable model
			LP-S044, LP-S070
<b>OP</b>	<b>DATA type</b>	<b>Available device / Description / Range</b>	
<b>S</b>	WORD	Y, F, Z, T, C, M, S, L, D, UW	Error Zero Carry Borrow Step 9
		Data address to execute the operation 0(h0000) to 65535(hFFFF)	
<b>N</b>	WORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer	
		The number of bits to rotate left side 0 to 16	

#### <Ladder>




1. Within the source word, move the 16 bits of source word to the left by the number of N bits.
2. If the  $N_{th}$  bit from the high order bit is 1, carry bit is SET.




### 3.2.107 Movement instruction(ASFTL)

Movement instruction	ASFTL	S	N1	N2	Applicable model
OP	DATA type	Available device / Description / Range			
<b>S</b>	BIT	Y, F, T, C, M, UB			Error
		Start bit position of the data to execute the operation			Zero
		Not applicable			Carry
<b>N1</b>	WORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer			Borrow
		The number of bits from the designated position as S			Step
		0 to 32			9
<b>N2</b>	WORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer			
		The number of bits to rotate left side			
		0 to 32			

#### <Ladder>




1. From the source bit, N1 bits moves to the left side as N2 in the range.
2. The low order bits, which are the number of movement, have "0" as their value.
3. If the value of N2 is greater than N1, the values of designated bits, from source bit to the N1, are shifted to "0".




### 3.2.108 Movement instruction(WSFTR)

Movement instruction	WSFTR	S	N1	N2	Applicable model										
<b>OP</b>	<b>DATA type</b>	<b>Available device / Description / Range</b>			LP-S044, LP-S070										
<b>S</b>	WORD	Y, F, Z, T, C, M, S, L, D, UW			<table border="1" style="margin-left: auto; margin-right: auto;"> <tr> <td>Error</td> <td>Zero</td> <td>Carry</td> <td>Borrow</td> <td>Step</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td>9</td> </tr> </table>	Error	Zero	Carry	Borrow	Step					9
		Error	Zero	Carry		Borrow	Step								
							9								
Data address to execute the operation															
0(h0000) to 65535(hFFFF)															
<b>N1</b>	WORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer													
		The number of words from the designated position as S													
		To the remained device range in corresponding S area													
<b>N2</b>	WORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer													
		The number of words to move to the right													
		To the range not greater than the N1 value													

#### <Ladder>




- From the source word, N1 words moves to the right side as N2 in the range by word unit.
- The high order words, which are the number of movement, have "0" as their value.




### 3.2.109 Movement instruction(WSFTL)

Movement instruction	WSFTL	S	N1	N2	Applicable model
OP	DATA type	Available device / Description / Range			
<b>S</b>	WORD	Y, F, Z, T, C, M, S, L, D, UW			Error
		Data address to execute the operation			Zero
		0(h0000) to 65535(hFFFF)			Carry
<b>N1</b>	WORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer			Borrow
		The number of words from the designated position as S			Step
		To the remained device range in corresponding S area			9
<b>N2</b>	WORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer			
		The number of words to move to the left			
		To the range not greater than the N1 value			

#### <Ladder>




- From the source word, N1 words moves to the left side as N2 in the range by word unit.
- The lower order words, which are the number of movement, have "0" as their value.




### 3.2.110 Arithmetic operation instruction(ADD)

Arithmetic operation instruction		ADD	S1	S2	D	Applicable model													
OP	DATA type	Available device / Description / Range																	
S1	INT	X, Y, F, Z, T, C, M, S, L, D, UW, integer																	
		Data address to execute the addition operation with S2 -32768(h8000) to 32767(h7FFF)																	
		X, Y, F, Z, T, C, M, S, L, D, UW, integer																	
S2	INT	Data address to execute the addition operation with S1 -32768(h8000) to 32767(h7FFF)																	
		Y, F, Z, T, C, M, S, L, D, UW																	
		Address to save the operation result -32768(h8000) to 32767(h7FFF)																	

&lt;Ladder&gt;




1. Adds the word values of S1 and S2, and then stores the result into the destination word D
2. Executes the Signed operation.  
(h8000(-32768) to hFFFF(-1) < 0 to h7FFF(32767))
3. If the result value exceeds 'h7FFF(32767)', carry flag is SET.
4. If the result value is h0000, zero flag is SET.




### 3.2.111 Arithmetic operation instruction(DADD)

Arithmetic operation instruction		DADD	S1	S2	D	Applicable model									
OP	DATA type	Available device / Description / Range					Error	Zero	Carry	Borrow	Step				
<b>S1</b>	DINT	X, Y, F, Z, T, C, M, S, L, D, UW, integer						<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	7				
		Data address to execute the addition operation with S2													
		-2147483648(h80000000) to 2147483647(h7FFFFFFF)													
<b>S2</b>	DINT	X, Y, F, Z, T, C, M, S, L, D, UW, integer						<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	7				
		Data address to execute the addition operation with S1													
		-2147483648(h80000000) to 2147483647(h7FFFFFFF)													
<b>D</b>	DINT	Y, F, Z, T, C, M, S, L, D, UW						<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	7				
		Address to save the operation result													
		-2147483648(h80000000) to 2147483647(h7FFFFFFF)													

&lt;Ladder&gt;




1. Adds the double word values of S1 and S2, and then stores the result into the destination double word D.
2. Executes the Signed operation.  
(h80000000(-2147483648) to hFFFFFFF(-1) < 0 to h7FFFFFF(2147483647))
3. If the result value exceeds 'h7FFFFFFF'(2147483647), carry flag is SET.
4. If the result value is 'h00000000', zero flag is SET.




### 3.2.112 Arithmetic operation instruction(ADDU)

Arithmetic operation instruction		ADDU	S1	S2	D	Applicable model												
OP	DATA type	Available device / Description / Range						LP-S044, LP-S070										
S1	WORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer						Error	Zero	Carry	Borrow	Step						
		Data address to execute the addition operation with S2																
		0(h0000) to 65535(hFFFF)																
S2	WORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer																
		Data address to execute the addition operation with S1																
		0(h0000) to 65535(hFFFF)																
D	WORD	Y, F, Z, T, C, M, S, L, D, UW																
		Address to save the operation result																
		0(h0000) to 65535(hFFFF)																

#### <Ladder>




1. Adds the word values of S1 and S2 and then stores the result into the destination word D.
2. Executes the Unsigned operation.
3. If the result value exceeds 'hFFFF(65535)', carry flag is SET.
4. If the result value is 'h0000', zero flag is SET.




### 3.2.113 Arithmetic operation instruction(DADDU)

Arithmetic operation instruction		DADDU	S1	S2	D	Applicable model									
OP	DATA type	Available device / Description / Range													
<b>S1</b>	DWORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer						Error	Zero	Carry	Borrow				
		Data address to execute the addition operation with S2													
		0(h0000) to 4294967295(hFFFFFFF)													
<b>S2</b>	DWORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer													
		Data address to execute the addition operation with S1													
		0(h0000) to 4294967295(hFFFFFFF)													
<b>D</b>	DWORD	Y, F, Z, T, C, M, S, L, D, UW													
		Address to save the operation result													
		0(h0000) to 4294967295(hFFFFFFF)													

&lt;Ladder&gt;



1. Adds the double word values of S1 and S2, and then stores the result into the destination double word D.
2. Executes the Unsigned operation.
3. If the result value exceeds 'hFFFFFFF' (4294967295), carry flag is SET.
4. If the result value is 'h0000', zero flag is SET.




### 3.2.114 Arithmetic operation instruction(ADDL)

**Arithmetic  
operation  
instruction**
**ADDL****S1 S2 D N**


Applicable model

LP-S044, LP-S070



OP	DATA type	Available device / Description / Range	
<b>S1</b>	INT	X, Y, F, Z, T, C, M, S, L, D, UW, integer	
		Data address to execute the addition operation with S2	
		-32768(h8000) to 32767(h7FFF)	
<b>S2</b>	INT	X, Y, F, Z, T, C, M, S, L, D, UW	
		Data address to execute the addition operation with S1	
		-32768(h8000) to 32767(h7FFF)	
<b>D</b>	INT	Y, F, Z, T, C, M, S, L, D, UW	
		Address to save the operation result	
		-32768(h8000) to 32767(h7FFF)	
<b>N</b>	WORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer	
		The number of S2 data address and saved address to execute the operation with S1	
		In the range within the corresponding device area of S2 and D	



## &lt;Ladder&gt;




- Adds the word value of S1 and the number of N word values beginning with S2 one by one, and then stores the number of N results into the number of N corresponding destination words beginning with word D.
- Executes the Signed operation.  
(h8000(-32768) to hFFFF(-1) < 0 to h7FFF(32767))
- If the result value is 'h0000', zero flag is SET.





### 3.2.115 Arithmetic operation instruction(DADDL)

Arithmetic operation instruction		DADDL	S1	S2	D	N	Applicable model									
OP	DATA type	Available device / Description / Range						Error	Zero	Carry	Borrow	Step				
<b>S1</b>	DINT	X, Y, F, Z, T, C, M, S, L, D, UW, integer							Error	Zero	Carry	Borrow				
		Data address to execute the addition operation with S2														
		-2147483648(h80000000) to 2147483647(h7FFFFFFF)														
<b>S2</b>	DINT	X, Y, F, Z, T, C, M, S, L, D, UW								Zero	Carry	Borrow				
		Data address to execute the addition operation with S1														
		-2147483648(h80000000) to 2147483647(h7FFFFFFF)														
<b>D</b>	DINT	Y, F, Z, T, C, M, S, L, D, UW								Carry	Borrow	Step				
		Address to save the operation result														
		-2147483648(h80000000) to 2147483647(h7FFFFFFF)														
<b>N</b>	WORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer								Borrow	Step	9				
		The number of S2 data address and saved address to execute the operation with S1														
		In the range within the corresponding device area of S2 and D														

#### <Ladder>




1. Adds the double word value of S1 and the number of N double word values beginning with S2 one by one, and then stores their results into the number of N corresponding destination double words beginning with double word D respectively.
2. Executes the Signed operation.  
(h80000000(-2147483648) to hFFFFFFF(-1) < 0 to hFFFFFFF(2147483647))
3. If the result value is 'h00000000', zero flag is SET.





### 3.2.116 Arithmetic operation instruction(ADDLU)

Arithmetic operation instruction		ADDLU	S1	S2	D	N	Applicable model
OP	DATA type	Available device / Description / Range					
S1	WORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer					
		Data address to execute the addition operation with S2					
		0(h0000) to 65535(hFFFF)					
S2	WORD	X, Y, F, Z, T, C, M, S, L, D, UW					
		Data address to execute the addition operation with S1					
		0(h0000) to 65535(hFFFF)					
D	WORD	Y, F, Z, T, C, M, S, L, D, UW					
		Address to save the operation result					
		0(h0000) to 65535(hFFFF)					
N	WORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer					
		The number of S2 data address and saved address to execute the operation with S1					
		In the range within the corresponding device area of S2 and D					

#### <Ladder>




1. Adds the word value of S1 and the number of N word values beginning with S2 one by one, and then stores their results into the number of N corresponding destination words beginning with word D respectively.
2. Executes the Unsigned operation.
3. If the result value exceeds 'hFFFF(65535)' carry flag is SET.
4. If the result value is 'h0000', zero flag is SET.





### 3.2.117 Arithmetic operation instruction(DADDLU)

Arithmetic operation instruction		DADDLU	S1	S2	D	N	Applicable model
OP	DATA type	Available device / Description / Range					
S1	DWORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer					Error Zero Carry Borrow Step 9
		Data address to execute the addition operation with S2					
		0(h0000) to 4294967295(hFFFFFFF)					
S2	DWORD	X, Y, F, Z, T, C, M, S, L, D, UW					Error Zero Carry Borrow Step 9
		Data address to execute the addition operation with S1					
		0(h0000) to 4294967295(hFFFFFFF)					
D	DWORD	Y, F, Z, T, C, M, S, L, D, UW					Error Zero Carry Borrow Step 9
		Address to save the operation result					
		0(h0000) to 4294967295(hFFFFFFF)					
N	WORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer					Error Zero Carry Borrow Step 9
		The number of S2 data address and saved address to execute the operation with S1					
		In the range within the corresponding device area of S2 and D					

#### <Ladder>




1. Adds the double word value of S1 and the number of N double word values beginning with S2 one by one, and then stores their results into the number of N corresponding destination double words beginning with double word D respectively.
2. Executes the Unsigned operation.
3. If the result value exceeds 'hFFFFFFF' (4294967295), carry flag is SET.
4. If the result value is 'h0000', zero flag is SET.




### 3.2.118 Arithmetic operation instruction(SUB)

Arithmetic operation instruction		SUB	S1	S2	D	Applicable model										
OP	DATA type	Available device / Description / Range					LP-S044, LP-S070	Error	Zero	Carry	Borrow	Step				
S1	INT	X, Y, F, Z, T, C, M, S, L, D, UW, integer					-32768(h8000) to 32767(h7FFF)									
		Data address to execute the subtraction operation with S2														
		-32768(h8000) to 32767(h7FFF)														
S2	INT	X, Y, F, Z, T, C, M, S, L, D, UW, integer					-32768(h8000) to 32767(h7FFF)									
		Data address to execute the subtraction operation with S1														
		-32768(h8000) to 32767(h7FFF)														
D	INT	Y, F, Z, T, C, M, S, L, D, UW					Address to save the operation result -32768(h8000) to 32767(h7FFF)									
		Address to save the operation result														
		-32768(h8000) to 32767(h7FFF)														

#### <Ladder>




1. Subtracts the word value of S2 from the word value of S1 and then stores the result into the destination word D.
2. Executes the Signed operation.  
(h8000(-32768) to hFFFF(-1) < 0 to h7FFF(32767))
3. If the result value is 'h0000', zero flag occurs.




### 3.2.119 Arithmetic operation instruction(DSUB)

Arithmetic operation instruction		DSUB	S1	S2	D	Applicable model									
OP	DATA type	Available device / Description / Range					Error	Zero	Carry	Borrow	Step				
<b>S1</b>	DINT	X, Y, F, Z, T, C, M, S, L, D, UW, integer						◎	◎	◎	7				
		Data address to execute the subtraction operation with S2													
		-2147483648(h80000000) to 2147483647(hFFFFFFF)													
<b>S2</b>	DINT	X, Y, F, Z, T, C, M, S, L, D, UW, integer						◎	◎	◎	7				
		Data address to execute the subtraction operation with S1													
		-2147483648(h80000000) to 2147483647(hFFFFFFF)													
<b>D</b>	DINT	Y, F, Z, T, C, M, S, L, D, UW						◎	◎	◎	7				
		Address to save the operation result													
		-2147483648(h80000000) to 2147483647(hFFFFFFF)													

#### <Ladder>




- Subtracts double word value of S2 from the double word value of S1 and then stores the result into the destination double word D.
- Executes the Signed operation.  
(h80000000(-2147483648) to hFFFFFFF(-1) < 0 to h7FFFFFF(2147483647))
- If the result value is 'h00000000', zero flag occurs.




### 3.2.120 Arithmetic operation instruction(SUBU)

Arithmetic operation instruction		SUBU	S1	S2	D	Applicable model									
OP	DATA type	Available device / Description / Range													
S1	WORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer						Error	Zero	Carry	Borrow				
		Data address to execute the subtraction operation with S2													
		0(h0000) to 65535(hFFFF)													
S2	WORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer													
		Data address to execute the subtraction operation with S1													
		0(h0000) to 65535(hFFFF)													
D	WORD	Y, F, Z, T, C, M, S, L, D, UW													
		Address to save the operation result													
		0(h0000) to 65535(hFFFF)													

#### <Ladder>




1. Subtracts the word value of S2 from the word value of S1 and then stores the result into the destination word D.
2. Executes the Unsigned operation.
3. If the result value is 'h0000' or out of this, borrow flag occurs.
4. If the result value is 'h0000', zero flag occurs.




### 3.2.121 Arithmetic operation instruction(DSUBU)

Arithmetic operation instruction		DSUBU	S1	S2	D	Applicable model									
OP	DATA type	Available device / Description / Range													
<b>S1</b>	DWORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer						Error	Zero	Carry	Borrow				
		Data address to execute the subtraction operation with S2													
		0(h0000) to 4294967295(hFFFFFFF)													
<b>S2</b>	DWORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer													
		Data address to execute the subtraction operation with S1													
		0(h0000) to 4294967295(hFFFFFFF)													
<b>D</b>	DWORD	Y, F, Z, T, C, M, S, L, D, UW													
		Address to save the operation result													
		0(h0000) to 4294967295(hFFFFFFF)													

&lt;Ladder&gt;




1. Subtract the double word value of S2 from the double word value of S1 and then store the result into the destination double word D.
2. Executes the Unsigned operation.
3. If the result value is 'h00000000' or out of this, borrow flag occurs.
4. If the result value 'h00000000', zero flag occurs.





### 3.2.122 Arithmetic operation instruction(SUBL)

Arithmetic operation instruction		SUBL	S1	S2	D	N	N	Applicable model	
OP	DATA type	Available device / Description / Range							
S1	INT	X, Y, F, Z, T, C, M, S, L, D, UW, integer						LP-S044, LP-S070	
		Data address to execute the subtraction operation with S2							
		-32768(h8000) to 32767(h7FFF)							
S2	INT	X, Y, F, Z, T, C, M, S, L, D, UW							
		Data address to execute the subtraction operation with S1							
		-32768(h8000) to 32767(h7FFF)							
D	INT	Y, F, Z, T, C, M, S, L, D, UW							
		Address to save the operation result							
		-32768(h8000) to 32767(h7FFF)							
N	WORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer							
		The number of S2 data address and saved address to execute the operation with S1							
		In the range within the corresponding device area of S2 and D							

#### <Ladder>




1. Subtracts the number of N word values, which are from S2 to S2(N-1), from the double word value of S1 respectively, and then stores the result into the number of N corresponding destination double words beginning with the word D.
2. Executes the Signed operation.  
(h8000(-32768) to hFFFF(-1) < 0 to h7FFF(32767))
3. If the result value is 'h0000', zero flag occurs.





### 3.2.123 Arithmetic operation instruction(DSUBL)

Arithmetic operation instruction		DSUBL	S2	D	N	Applicable model									
OP	DATA type	Available device / Description / Range													
<b>S1</b>	DINT	X, Y, F, Z, T, C, M, S, L, D, UW, integer						Error	Zero	Carry	Borrow				
		Data address to execute the subtraction operation with S2													
		-2147483648(h80000000) to 2147483647(h7FFFFFFF)													
<b>S2</b>	DINT	X, Y, F, Z, T, C, M, S, L, D, UW													
		Data address to execute the subtraction operation with S1													
		-2147483648(h80000000) to 2147483647(h7FFFFFFF)													
<b>D</b>	DINT	Y, F, Z, T, C, M, S, L, D, UW													
		Address to save the operation result													
		-2147483648(h80000000) to 2147483647(h7FFFFFFF)													
<b>N</b>	WORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer													
		The number of S2 data address and saved address to execute the operation with S1													
		In the range within the corresponding device area of S2 and D													

&lt;Ladder&gt;




- Subtracts the number of N double word values, which are from S2 to S2(N-1), from double word value of S1 respectively, and then stores the result into the number of N corresponding destination double words beginning with the double word D.
- Executes the Signed operation.  
(h80000000(-2147483648) to hFFFFFFF(-1) < 0 to hFFFFFFF(2147483647))
- If the result value is 'h00000000', zero flag occurs.





### 3.2.124 Arithmetic operation instruction(SUBLU)

Arithmetic operation instruction		SUBLU	S1	S2	D	N	Applicable model										
OP	DATA type	Available device / Description / Range															
S1	WORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer					LP-S044, LP-S070  <table border="1"><tr><td>Error</td><td>Zero</td><td>Carry</td><td>Borrow</td><td>Step</td></tr><tr><td><input checked="" type="checkbox"/></td><td><input checked="" type="checkbox"/></td><td><input checked="" type="checkbox"/></td><td><input checked="" type="checkbox"/></td><td>9</td></tr></table>	Error	Zero	Carry	Borrow	Step	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	9
Error	Zero	Carry	Borrow	Step													
<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	9													
Data address to execute the subtraction operation with S2																	
0(h0000) to 65535(hFFFF)																	
S2	WORD	X, Y, F, Z, T, C, M, S, L, D, UW															
		Data address to execute the subtraction operation with S1															
		0(h0000) to 65535(hFFFF)															
D	WORD	Y, F, Z, T, C, M, S, L, D, UW															
		Address to save the operation result															
		0(h0000) to 65535(hFFFF)															
N	WORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer															
		The number of S2 data address and saved address to execute the operation with S1															
		In the range within the corresponding device area of S2 and D															

#### <Ladder>




1. Subtracts the number of N word values, which are from S2 to S2(N-1), from word value of S1 respectively, and then stores the result into the number of N corresponding destination words beginning with the word D.
2. Executes the Unsigned operation.
3. If the result value is 'h0000' or or out of this, borrow flag occurs.
4. If the result value is 'h0000', zero flag occurs.




### 3.2.125 Arithmetic operation instruction(DSUBLU)

Arithmetic operation instruction		DSUBLU	S1	S2	D	N	Applicable model									
OP	DATA type	Available device / Description / Range						Error	Zero	Carry	Borrow	Step				
<b>S1</b>	DWORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer							<input checked="" type="radio"/>	<input checked="" type="radio"/>	<input checked="" type="radio"/>	<input checked="" type="radio"/>				
		Data address to execute the subtraction operation with S2														
		0(h0000) to 4294967295(hFFFFFFF)														
<b>S2</b>	DWORD	X, Y, F, Z, T, C, M, S, L, D, UW							<input checked="" type="radio"/>	<input checked="" type="radio"/>	<input checked="" type="radio"/>	<input checked="" type="radio"/>				
		Data address to execute the subtraction operation with S1														
		0(h0000) to 4294967295(hFFFFFFF)														
<b>D</b>	DWORD	Y, F, Z, T, C, M, S, L, D, UW							<input checked="" type="radio"/>	<input checked="" type="radio"/>	<input checked="" type="radio"/>	<input checked="" type="radio"/>				
		Address to save the operation result														
		0(h0000) to 4294967295(hFFFFFFF)														
<b>N</b>	WORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer							<input checked="" type="radio"/>	<input checked="" type="radio"/>	<input checked="" type="radio"/>	<input checked="" type="radio"/>				
		The number of S2 data address and saved address to execute the operation with S1														
		In the range within the corresponding device area of S2 and D														

&lt;Ladder&gt;




1. Subtracts the number of N double word values, which are from S2 to S2(N-1), from double word value of S1 respectively, and then stores the result into the number of N corresponding destination beginning with the double word D.
2. Executes the Unsigned operation.
3. If the result value is 'h00000000' or out of this, borrow flag occurs.
4. If the result value 'h00000000', zero flag occurs.




### 3.2.126 Arithmetic operation instruction(MUL)

Arithmetic operation instruction		MUL	S1	S2	D	Applicable model												
OP	DATA type	Available device / Description / Range					LP-S044, LP-S070	Error	Zero	Carry	Borrow	Step						
S1	INT	X, Y, F, Z, T, C, M, S, L, D, UW, integer					LP-S044, LP-S070	Error	Zero	Carry	Borrow	Step						
		Data address to execute the multiplication with S2																
		-32768(h8000) to 32767(h7FFF)																
S2	INT	X, Y, F, Z, T, C, M, S, L, D, UW, integer					LP-S044, LP-S070	Error	Zero	Carry	Borrow	Step						
		Data address to execute the multiplication with S1																
		-32768(h8000) to 32767(h7FFF)																
D	DINT	Y, F, Z, T, C, M, S, L, D, UW					LP-S044, LP-S070	Error	Zero	Carry	Borrow	Step						
		Address to save the operation result																
		-2147483648(h80000000) to 2147483647(hFFFFFFF)																

#### <Ladder>




1. Multiplies the word value of S1 and that of S2, and then stores the result into the destination double word "D".
2. Executes the Signed operation.
3. If the result value is '0', zero flag occurs.




### 3.2.127 Arithmetic operation instruction(DMUL)

Arithmetic operation instruction		DMUL	S1	S2	D	Applicable model											
OP	DATA type	Available device / Description / Range					LP-S044, LP-S070	Error	Zero	Carry	Borrow	Step					
<b>S1</b>	DINT	X, Y, F, Z, T, C, M, S, L, D, UW, integer						Error	Zero	Carry	Borrow	Step					
		Data address to execute the multiplication with S2															
		-2147483648(h80000000) to 2147483647(hFFFFFFF)															
<b>S2</b>	DINT	X, Y, F, Z, T, C, M, S, L, D, UW, integer															
		Data address to execute the multiplication with S1															
		-2147483648(h80000000) to 2147483647(hFFFFFFF)															
<b>D</b>	QWORD	Y, F, Z, T, C, M, S, L, D, UW															
		Address to save the operation result															

#### <Ladder>




1. Multiplies the double word value of S1 and that of S2, and then stores the result into the destination "Quad Word D".
2. Executes the Signed operation.
3. If the result value is '0', zero flag is SET.




### 3.2.128 Arithmetic operation instruction(MULU)

Arithmetic operation instruction		MULU	S1	S2	D	Applicable model													
OP	DATA type	Available device / Description / Range						LP-S044, LP-S070											
S1	WORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer						Error	Zero	Carry	Borrow	Step	7						
		Data address to execute the multiplication with S2																	
		0(h0000) to 65535(hFFFF)																	
S2	WORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer																	
		Data address to execute the multiplication with S1																	
		0(h0000) to 65535(hFFFF)																	
D	DWORD	Y, F, Z, T, C, M, S, L, D, UW																	
		Address to save the operation result																	
		0(h0000) to 4294967295(hFFFFFF)																	

#### <Ladder>




1. Multiplies the word value of S1 and that of S2, and then stores the result into the destination "Double Word DW".
2. Executes the Unsigned operation.
3. If the result value is '0', zero flag occurs.




### 3.2.129 Arithmetic operation instruction(DMULU)

Arithmetic operation instruction		DMULU	S1	S2	D	Applicable model									
OP	DATA type	Available device / Description / Range					Error	Zero	Carry	Borrow	Step				
<b>S1</b>	DWORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer						<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	7				
		Data address to execute the multiplication with S2													
		0(h0000) to 4294967295(hFFFFFFF)													
<b>S2</b>	DWORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer						<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	7				
		Data address to execute the multiplication with S1													
		0(h0000) to 4294967295(hFFFFFFF)													
<b>D</b>	QWORD	Y, F, Z, T, C, M, S, L, D, UW						Address to save the operation result							

#### <Ladder>




1. Multiplies the double word value of S1 and that of S2, and then stores the result into the destination "Quad Word D".
2. Executes the Unsigned operation.
3. If the result value is '0', zero flag occurs.





### 3.2.130 Arithmetic operation instruction(MULL)

Arithmetic operation instruction		MULL	S1	S2	D	N	Applicable model
OP	DATA type	Available device / Description / Range					
S1	INT	X, Y, F, Z, T, C, M, S, L, D, UW, integer					Error Zero Carry Borrow Step 9
		Data address to execute the multiplication with S2					
		-32768(h8000) to 32767(h7FFF)					
S2	INT	X, Y, F, Z, T, C, M, S, L, D, UW					Error Zero Carry Borrow Step 9
		Data address to execute the multiplication with S1					
		-32768(h8000) to 32767(h7FFF)					
D	DINT	Y, F, Z, T, C, M, S, L, D, UW					Error Zero Carry Borrow Step 9
		Address to save the operation result					
		-2147483648(h80000000) to 2147483647(hFFFFFFF)					
N	WORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer					Error Zero Carry Borrow Step 9
		The number of S2 data address and saved address to execute the operation with S1					
		In the range within the corresponding device area of S2 and D					

#### <Ladder>




1. Multiplies the word value of S1 and the number of N word values, which are from S2 to S2(N-1), respectively, and then stores the result into the number of corresponding destination double words beginning with double word D.
2. Executes the Signed operation.
3. Any one of the results is '0', zero flag occurs.





### 3.2.131 Arithmetic operation instruction(DMULL)

Arithmetic operation instruction		DMULL	S1	S2	D	N	Applicable model									
OP	DATA type	Available device / Description / Range						Error	Zero	Carry	Borrow	Step				
<b>S1</b>	DINT	X, Y, F, Z, T, C, M, S, L, D, UW, integer							Error	Zero	Carry	Borrow				
		Data address to execute the multiplication with S2														
		-2147483648(h80000000) to 2147483647(h7FFFFFFF)														
<b>S2</b>	DINT	X, Y, F, Z, T, C, M, S, L, D, UW								Zero	Carry	Borrow				
		Data address to execute the multiplication with S1														
		-2147483648(h80000000) to 2147483647(h7FFFFFFF)														
<b>D</b>	QINT	Y, F, Z, T, C, M, S, L, D, UW								Carry	Borrow	Step				
		Address to save the operation result														
<b>N</b>	WORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer								Borrow	Step	9				
		The number of S2 data address and saved address to execute the operation with S1														
		In the range within the corresponding device area of S2 and D														


#### <Ladder>




- Multiplies the double word value of S1 and the number of N double word values, which are from S2 to S2(N-1), respectively, and then stores the result into the number of corresponding destination quad words beginning with D.
- Executes the Signed operation.
- Any one of the results is '0', zero flag occurs.





### 3.2.132 Arithmetic operation instruction(MULLU)

Arithmetic operation instruction		MULLU	S1	S2	D	N	Applicable model
OP	DATA type	Available device / Description / Range					
S1	WORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer					LP-S044, LP-S070  
		Data address to execute the multiplication with S2					
		0(h0000) to 65535(hFFFF)					
S2	WORD	X, Y, F, Z, T, C, M, S, L, D, UW					
		Data address to execute the multiplication with S1					
		0(h0000) to 65535(hFFFF)					
D	DWORD	Y, F, Z, T, C, M, S, L, D, UW					
		Address to save the operation result					
		0(h0000) to 4294967295(hFFFFFFF)					
N	WORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer					
		The number of S2 data address and saved address to execute the operation with S1					
		In the range within the corresponding device area of S2 and D					

#### <Ladder>




1. Multiplies the word value of S1 and the number of N word values, which are from S2 to S2(N-1) respectively, and then stores the result into the number of corresponding destination double words beginning with double word D one by one.
2. Executes the Unsigned operation.
3. Any one of the results is '0', zero flag occurs.





### 3.2.133 Arithmetic operation instruction(DMULLU)

Arithmetic operation instruction		DMULLU	S1	S2	D	N	Applicable model
OP	DATA type	Available device / Description / Range					
<b>S1</b>	DWORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer					LP-S044, LP-S070 Error Zero Carry Borrow Step 9
		Data address to execute the multiplication with S2					
		0(h0000) to 4294967295(hFFFFFFF)					
<b>S2</b>	DWORD	X, Y, F, Z, T, C, M, S, L, D, UW					
		Data address to execute the multiplication with S1					
		0(h0000) to 4294967295(hFFFFFFF)					
<b>D</b>	QWORD	Y, F, Z, T, C, M, S, L, D, UW					
		Address to save the operation result					
<b>N</b>	WORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer					
		The number of S2 data address and saved address to execute the operation with S1					
		In the range within the corresponding device area of S2 and D					

#### <Ladder>




1. Multiplies the double word value of S1 and the number of N double word values, which are from S2 to S2(N-1), and then stores the result into the number of N corresponding destination quad words beginning with quad word D one by one.
2. Executes the Unsigned operation.
3. Any one of the results is '0', zero flag occurs.




### 3.2.134 Arithmetic operation instruction(DIV)

Arithmetic operation instruction		DIV	S1	S2	D	Applicable model												
OP	DATA type	Available device / Description / Range						LP-S044, LP-S070										
S1	INT	X, Y, F, Z, T, C, M, S, L, D, UW, integer						Error	Zero	Carry	Borrow	Step 7						
		Data address to execute the division operation with S2																
		-32768(h8000) to 32767(h7FFF)																
S2	INT	X, Y, F, Z, T, C, M, S, L, D, UW, integer																
		Data address to execute the division operation with S1																
		-32768(h8000) to 32767(h7FFF)																
D	INT	Y, F, Z, T, C, M, S, L, D, UW																
		Address to save the operation result																
		-32768(h8000) to 32767(h7FFF)																

#### <Ladder>




- Divides the word value of S1 by that of S2 and then stores the quotient and the remainder into the destination "Word D" and "Word D+1" respectively.
- Executes the Signed operation.
- If the divisor is 0, error flag is SET.
- If the dividend is 0, zero flag is SET.




### 3.2.135 Arithmetic operation instruction(DDIV)

Arithmetic operation instruction		DDIV	S1	S2	D	Applicable model											
OP	DATA type	Available device / Description / Range					LP-S044, LP-S070	Error	Zero	Carry	Borrow	Step					
<b>S1</b>	DINT	X, Y, F, Z, T, C, M, S, L, D, UW, integer						<input checked="" type="radio"/>	<input checked="" type="radio"/>	<input type="checkbox"/>	<input type="checkbox"/>	7					
		Data address to execute the division operation with S2															
		-2147483648(h80000000) to 2147483647(hFFFFFFF)															
<b>S2</b>	DINT	X, Y, F, Z, T, C, M, S, L, D, UW, integer						<input checked="" type="radio"/>	<input checked="" type="radio"/>	<input type="checkbox"/>	<input type="checkbox"/>	7					
		Data address to execute the division operation with S1															
		-2147483648(h80000000) to 2147483647(hFFFFFFF)															
<b>D</b>	DINT	Y, F, Z, T, C, M, S, L, D, UW						<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	7					
		Address to save the operation result															
		-2147483648(h80000000) to 2147483647(hFFFFFFF)															

#### <Ladder>




- Divides the double word value of S1 by that of S2 and then stores the quotient and the remainder into the destination “Double Word D” and “Double Word D+1” respectively.
- Executes the Signed operation.
- If the divisor is 0, error flag is SET.
- If the dividend is 0, zero flag is SET.




### 3.2.136 Arithmetic operation instruction(DIVU)

Arithmetic operation instruction		DIVU	S1	S2	D	Applicable model										
OP	DATA type	Available device / Description / Range														
S1	WORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer					Error	Zero	Carry	Borrow	Step 7					
		Data address to execute the division operation with S2														
		0(h0000) to 65535(hFFFF)														
S2	WORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer														
		Data address to execute the division operation with S1														
		0(h0000) to 65535(hFFFF)														
D	WORD	Y, F, Z, T, C, M, S, L, D, UW														
		Address to save the operation result														
		0(h0000) to 65535(hFFFF)														

#### <Ladder>




- Divides the word value of S1 by that of S2 and then stores the quotient and the remainder into the destination “Word D” and “Word D+1” respectively.
- Executes the Unsigned operation.
- If the divisor is 0, error flag is SET.
- If the dividend is 0, zero flag is SET.




### 3.2.137 Arithmetic operation instruction(DDIVU)

Arithmetic operation instruction		DDIVU	S1	S2	D	Applicable model									
OP	DATA type	Available device / Description / Range					Error	Zero	Carry	Borrow	Step				
<b>S1</b>	DWORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer						<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	7				
		Data address to execute the division operation with S2													
		0(h0000) to 4294967295(hFFFFFFF)													
<b>S2</b>	DWORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer						<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	7				
		Data address to execute the division operation with S1													
		0(h0000) to 4294967295(hFFFFFFF)													
<b>D</b>	DWORD	Y, F, Z, T, C, M, S, L, D, UW						<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	7				
		Address to save the operation result													
		0(h0000) to 4294967295(hFFFFFFF)													

#### <Ladder>




- Divides the double word value of S1 by that of S2 and then stores the quotient and the remainder into the destination “Double Word D” and “Double Word D+1” respectively.
- Executes the Unsigned operation.
- If the divisor is 0, error flag is SET.
- If the dividend is 0, zero flag is SET.





### 3.2.138 Arithmetic operation instruction(DIVL)

Arithmetic operation instruction		DIVL	S1	S2	D	N	Applicable model										
OP	DATA type	Available device / Description / Range															
S1	INT	X, Y, F, Z, T, C, M, S, L, D, UW, integer					LP-S044, LP-S070  <table border="1"><tr><td>Error</td><td>Zero</td><td>Carry</td><td>Borrow</td><td>Step</td></tr><tr><td><input checked="" type="radio"/></td><td><input checked="" type="radio"/></td><td></td><td></td><td>9</td></tr></table>	Error	Zero	Carry	Borrow	Step	<input checked="" type="radio"/>	<input checked="" type="radio"/>			9
Error	Zero	Carry	Borrow	Step													
<input checked="" type="radio"/>	<input checked="" type="radio"/>			9													
Data address to execute the division operation with S2																	
-32768(h8000) to 32767(h7FFF)																	
S2	INT	X, Y, F, Z, T, C, M, S, L, D, UW															
		Data address to execute the division operation with S1															
		-32768(h8000) to 32767(h7FFF)															
D	INT	Y, F, Z, T, C, M, S, L, D, UW															
		Address to save the operation result															
		-32768(h8000) to 32767(h7FFF)															
N	WORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer															
		The number of S2 data address and saved address to execute the operation with S1															
		In the range within the corresponding device area of S2 and D															

#### <Ladder>




- Divides the word value of S1 by the number of N word values beginning with S2 and then stores the quotient and the remainder into the destination "Word D" and "Word D+1" respectively.
- Executes the Signed operation.
- If the divisor is 0, error flag is SET.
- If the dividend is 0, zero flag is SET.





### 3.2.139 Arithmetic operation instruction(DDIVL)

Arithmetic operation instruction		DDIVL	S1	S2	D	N	Applicable model									
OP	DATA type	Available device / Description / Range						Error	Zero	Carry	Borrow	Step				
<b>S1</b>	DINT	X, Y, F, Z, T, C, M, S, L, D, UW, integer							<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	9				
		Data address to execute the division operation with S2														
		-2147483648(h80000000) to 2147483647(hFFFFFFF)														
<b>S2</b>	DINT	X, Y, F, Z, T, C, M, S, L, D, UW							<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	9				
		Data address to execute the division operation with S1														
		-2147483648(h80000000) to 2147483647(hFFFFFFF)														
<b>D</b>	DINT	Y, F, Z, T, C, M, S, L, D, UW							<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	9				
		Address to save the operation result														
		-2147483648(h80000000) to 2147483647(hFFFFFFF)														
<b>N</b>	WORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer							<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	9				
		The number of S2 data address and saved address to execute the operation with S1														
		In the range within the corresponding device area of S2 and D														

&lt;Ladder&gt;




- Divides the double word value of S1 by the number of N double word values beginning with S2 and then stores the quotient and the remainder into the destination “Double Word D” and “Double Word D+1” respectively.
- Executes the Signed operation.
- If the divisor is 0, error flag is SET.
- If the dividend is 0, zero flag is SET.





### 3.2.140 Arithmetic operation instruction(DIVLU)

Arithmetic operation instruction		DIVLU	S1	S2	D	N	Applicable model										
OP	DATA type	Available device / Description / Range															
S1	WORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer					LP-S044, LP-S070  <table border="1"><tr><td>Error</td><td>Zero</td><td>Carry</td><td>Borrow</td><td>Step</td></tr><tr><td><input checked="" type="radio"/></td><td><input checked="" type="radio"/></td><td></td><td></td><td>9</td></tr></table>	Error	Zero	Carry	Borrow	Step	<input checked="" type="radio"/>	<input checked="" type="radio"/>			9
Error	Zero	Carry	Borrow	Step													
<input checked="" type="radio"/>	<input checked="" type="radio"/>			9													
Data address to execute the division operation with S2																	
0(h0000) to 65535(hFFFF)																	
S2	WORD	X, Y, F, Z, T, C, M, S, L, D, UW															
		Data address to execute the division operation with S1															
		0(h0000) to 65535(hFFFF)															
D	WORD	Y, F, Z, T, C, M, S, L, D, UW															
		Address to save the operation result															
		0(h0000) to 65535(hFFFF)															
N	WORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer															
		The number of S2 data address and saved address to execute the operation with S1															
		In the range within the corresponding device area of S2 and D															

#### <Ladder>




- Divides the word value of S1 by the number of N word values beginning with S2 and then stores the quotient and the remainder into the destination "Word D" and "Word D+1" respectively.
- Executes the Unsigned operation.
- If the divisor is 0, error flag is SET.
- If the dividend is 0, zero flag is SET.





### 3.2.141 Arithmetic operation instruction(DDIVLU)

Arithmetic operation instruction		DDIVLU	S1	S2	D	N	Applicable model									
OP	DATA type	Available device / Description / Range						Error	Zero	Carry	Borrow	Step				
<b>S1</b>	DWORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer							Error ◎	Zero ◎	Carry	Borrow				
		Data address to execute the division operation with S2														
		0(h0000) to 4294967295(hFFFFFFF)														
<b>S2</b>	DWORD	X, Y, F, Z, T, C, M, S, L, D, UW								Step 9						
		Data address to execute the division operation with S1														
		0(h0000) to 4294967295(hFFFFFFF)														
<b>D</b>	DWORD	Y, F, Z, T, C, M, S, L, D, UW														
		Address to save the operation result														
		0(h0000) to 4294967295(hFFFFFFF)														
<b>N</b>	WORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer														
		The number of S2 data address and saved address to execute the operation with S1														
		In the range within the corresponding device area of S2 and D														

#### <Ladder>




- Divides the double word value of S1 by the number of N double word values beginning with S2 and then stores the quotient and the remainder into the destination “Double Word D” and “Double Word D+1” respectively.
- Executes the Unsigned operation.
- If the divisor is 0, error flag is SET.
- If the dividend is 0, zero flag is SET.




### 3.2.142 Arithmetic operation instruction(INC)

<b>Arithmetic operation instruction</b>	<b>INC</b>	<b>D</b>	Applicable model
			LP-S044, LP-S070
<b>OP</b>	<b>DATA type</b>	<b>Available device / Description / Range</b>	
<b>D</b>	WORD	Y, F, Z, T, C, M, S, L, D, UW Data address to execute the operation 0(h0000) to 65535(hFFFF)	Error    Step 3

#### <Ladder>



- Increases the value of destination word D by '1'.
- If the value is increased from the maximum value by 1 and then becomes 0, zero flag and carry flag are SET.



### 3.2.143 Arithmetic operation instruction(DINC)

**Arithmetic  
operation  
instruction**

**DINC**


**D**

Applicable model


LP-S044, LP-S070

OP	DATA type	Available device / Description / Range	Error	Zero	Carry	Borrow	Step
<b>D</b>	DWORD	Y, F, Z, T, C, M, S, L, D, UW Data address to execute the operation 0(h0000) to 4294967295(hFFFFFFF)	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	3

<Ladder>




- Increases the value of destination double word D by '1'.
- If the value is increased from the maximum value by 1 and then D value becomes 0, zero flag and carry flag are SET.




### 3.2.144 Arithmetic operation instruction(DEC)

<b>Arithmetic operation instruction</b>	<b>DEC</b>	<b>D</b>	Applicable model
			LP-S044, LP-S070
<b>OP</b>	<b>DATA type</b>	<b>Available device / Description / Range</b>	
<b>D</b>	WORD	Y, F, Z, T, C, M, S, L, D, UW Data address to execute the operation 0(h0000) to 65535(hFFFF)	Error <input checked="" type="checkbox"/> Zero <input type="checkbox"/> Carry <input type="checkbox"/> Borrow Step 3

#### <Ladder>




1. Decreases the value of destination word D by '1'.
2. If D value is '0', zero flag is SET.
3. If D value is decreased again from '0', borrow flag is SET.



### 3.2.145 Arithmetic operation instruction(DDEC)

Arithmetic operation Instruction	DDEC	D	Applicable model
			LP-S044, LP-S070
OP	DATA type	Available device / Description / Range	
D		Y, F, Z, T, C, M, S, L, D, UW Data address to execute the operation 0(h0000) to 4294967295(hFFFFFFF)	
			Error  Zero  Carry  Borrow  Step

&lt;Ladder&gt;




- Decreases the value of destination double word D by '1'.
- If D value is '0', zero flag is SET.
- If D value is decreased again from '0', carry flag is SET.




### 3.2.146 Arithmetic operation instruction(ADDB)

Arithmetic operation instruction		ADDB	S1	S2	D	Applicable model										
OP	DATA type	Available device / Description / Range					LP-S044, LP-S070									
S1	WORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer					Error	Zero	Carry	Borrow	Step 7					
		Data address to execute the BCD addition operation with S2														
		h0000 to h9999														
S2	WORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer														
		Data address to execute the BCD addition operation with S1														
		h0000 to h9999														
D	WORD	Y, F, Z, T, C, M, S, L, D, UW														
		Address to save the operation result														
		h0000 to h9999														

#### <Ladder>




1. Adds the word value of S1 and that of S2, both are composed of BCD codes, and then stores the result into the destination word D as BCD code.
2. If any of the value not composed of the BCD code is detected in S1 and S2, error flag is SET. (Except 0 to 9999)
3. If the result value is out of the range of D, carry flag is SET.
4. If the result value is '0', zero flag is SET.




### 3.2.147 Arithmetic operation instruction(DADDB)

Arithmetic operation instruction		DADDB	S1	S2	D	Applicable model											
OP	DATA type	Available device / Description / Range					LP-S044, LP-S070	Error	Zero	Carry	Borrow	Step					
<b>S1</b>	DWORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer						<input checked="" type="radio"/>	<input checked="" type="radio"/>	<input checked="" type="radio"/>	<input checked="" type="radio"/>	7					
		Data address to execute the BCD addition operation with S2															
		h00000000 to h99999999															
<b>S2</b>	DWORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer						<input checked="" type="radio"/>	<input checked="" type="radio"/>	<input checked="" type="radio"/>	<input checked="" type="radio"/>	7					
		Data address to execute the BCD addition operation with S1															
		h00000000 to h99999999															
<b>D</b>	DWORD	Y, F, Z, T, C, M, S, L, D, UW						<input checked="" type="radio"/>	<input checked="" type="radio"/>	<input checked="" type="radio"/>	<input checked="" type="radio"/>	7					
		Address to save the operation result															
		h00000000 to h99999999															

#### <Ladder>




1. Adds the double word values of S1 and S2, both are composed of BCD codes, and then stores the result into the destination double word D as BCD codes.
2. If any of the value not composed of the BCD code is detected in S1 and S2, error flag is SET.  
(Except 0 to 99999999)
3. If the result value is out of the range of D, carry flag is SET.
4. If the result value is '0' , zero flag is SET.





### 3.2.148 Arithmetic operation instruction(ADDBL)

Arithmetic operation instruction		ADDBL	S1	S2	D	N	Applicable model										
OP	DATA type	Available device / Description / Range															
S1	WORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer					LP-S044, LP-S070  <table border="1"><tr><td>Error</td><td>Zero</td><td>Carry</td><td>Borrow</td><td>Step</td></tr><tr><td><input checked="" type="radio"/></td><td><input checked="" type="radio"/></td><td><input checked="" type="radio"/></td><td><input type="radio"/></td><td>9</td></tr></table>	Error	Zero	Carry	Borrow	Step	<input checked="" type="radio"/>	<input checked="" type="radio"/>	<input checked="" type="radio"/>	<input type="radio"/>	9
		Error	Zero	Carry	Borrow	Step											
		<input checked="" type="radio"/>	<input checked="" type="radio"/>	<input checked="" type="radio"/>	<input type="radio"/>	9											
Data address to execute the BCD addition operation with S2																	
h0000 to h9999																	
S2	WORD	X, Y, F, Z, T, C, M, S, L, D, UW															
		Data address to execute the BCD addition operation with S1															
		h0000 to h9999															
D	WORD	Y, F, Z, T, C, M, S, L, D, UW															
		Address to save the operation result															
		h0000 to h9999															
N	WORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer															
		The number of S2 data address and saved address to execute the operation with S1															
		In the range within the corresponding device area of S2 and D															

#### <Ladder>




1. Adds the word value of S1 composed of BCD code and the number of N word values beginning with S2 also composed of BCD code, respectively, and then stores the result into the number of N destination words beginning with D as BCD code.
2. If any of the value not composed of the BCD code is detected in S1 and S2, error flag is SET.
3. If any of the result value from D to D+N is out of the D range, carry flag is SET.
4. If any of the result value from D to D+N is 0, zero flag is SET.





### 3.2.149 Arithmetic operation instruction(DADDBL)

Arithmetic operation instruction		DADDBL	S1	S2	D	N	Applicable model					
OP	DATA type	Available device / Description / Range						Error	Zero	Carry	Borrow	Step
<b>S1</b>	DWORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer										
		Data address to execute the BCD addition operation with S2										
		h00000000 to h99999999										
<b>S2</b>	DWORD	X, Y, F, Z, T, C, M, S, L, D, UW										
		Data address to execute the BCD addition operation with S1										
		h00000000 to h99999999										
<b>D</b>	DWORD	Y, F, Z, T, C, M, S, L, D, UW										
		Address to save the operation result										
		h00000000 to h99999999										
<b>N</b>	WORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer										
		The number of S2 data address and saved address to execute the operation with S1										
		In the range within the corresponding device area of S2 and D										

#### <Ladder>




1. Adds the double word values S1 composed of BCD code and the number of N double word values beginning with S2 also composed of BCD code, respectively, and then stores the result into the number of N destination double words beginning with D double word as BCD code.
2. If any of the value not composed of the BCD code is detected in S1 and S2 error flag is SET.
3. If any of the result value from D and D+N is out of the D range, carry flag is SET.
4. If any of the result value from D and D+N is 0, zero flag is SET.




### 3.2.150 Arithmetic operation instruction(SUBB)

Arithmetic operation instruction		SUBB	S1	S2	D	Applicable model					
OP	DATA type	Available device / Description / Range									
S1	WORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer						Error	Zero	Carry	Borrow
		Data address to execute the BCD subtraction operation with S2						<input checked="" type="radio"/>	<input checked="" type="radio"/>	<input type="checkbox"/>	<input checked="" type="radio"/>
		h0000 to h9999									Step 7
S2	WORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer									
		Data address to execute the BCD subtraction operation with S1									
		h0000 to h9999									
D	WORD	Y, F, Z, T, C, M, S, L, D, UW									
		Address to save the operation result									
		h0000 to h9999									

#### <Ladder>




1. Subtracts the word value of S2 composed of BCD code from the word value of S1 composed of BCD code, and then stores the result into the destination word D as BCD code.
2. If any of the value not composed of the BCD code is detected in S1 and S2, error flag is SET. (Except 0 to 9999)
3. If the result value is negative number, it is stored as 'h9999'.
4. If the result value is '0', zero flag is SET.





### 3.2.151 Arithmetic operation instruction(DSUBB)

Arithmetic operation instruction		DSUBB	S1	S2	D	Applicable model									
OP	DATA type	Available device / Description / Range					Error	Zero	Carry	Borrow	Step				
<b>S1</b>	DWORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer						<input checked="" type="radio"/>	<input checked="" type="radio"/>	<input type="checkbox"/>	7				
		Data address to execute the BCD subtraction operation with S2													
		h00000000 to h99999999													
<b>S2</b>	DWORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer						<input checked="" type="radio"/>	<input checked="" type="radio"/>	<input type="checkbox"/>	7				
		Data address to execute the BCD subtraction operation with S1													
		h00000000 to h99999999													
<b>D</b>	DWORD	Y, F, Z, T, C, M, S, L, D, UW						<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	7				
		Address to save the operation result													
		h00000000 to h99999999													

#### <Ladder>




1. Subtracts the double word value of S2 from double word value of S1, both are composed of BCD code, and then stores the result into the destination double word D as BCD code.
2. If any of the value not composed of the BCD code is detected in S1 and S2, error flag is SET. (Except 0 to 99999999)
3. If the result value is negative number, it is stored as 'h9999'.
4. If the result value is '0', zero flag is SET.





### 3.2.152 Arithmetic operation instruction(SUBBL)

Arithmetic operation instruction		SUBBL	S1	S2	D	N	Applicable model
OP	DATA type	Available device / Description / Range					
S1	WORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer					LP-S044, LP-S070  Error      Zero      Carry      Borrow      Step ○      ○      ○      ○      9
		Data address to execute the BCD subtraction operation with S2					
		h0000 to h9999					
S2	WORD	X, Y, F, Z, T, C, M, S, L, D, UW					
		Data address to execute the BCD subtraction operation with S1					
		h0000 to h9999					
D	WORD	Y, F, Z, T, C, M, S, L, D, UW					
		Address to save the operation result					
		h0000 to h9999					
N	WORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer					
		The number of S2 data address and saved address to execute the operation with S1					
		In the range within the corresponding device area of S2 and D					

#### <Ladder>




- Subtracts the number of N words values composed of BCD code beginning with S2 from word value of S1 composed of BCD code and then stores the result into the number of N destination words beginning with D as BCD code.
- If any of the value not composed of the BCD code is detected in S1 and S2, error flag is SET.
- If any of the result value in the range from D to D+N is negative number in word area, it is stored as 'h9999'.
- If any of the result value in the range from D to D+N is '0', zero flag is SET.





### 3.2.153 Arithmetic operation instruction(DSUBBL)

Arithmetic operation instruction		DSUBBL	S1	S2	D	N	Applicable model									
OP	DATA type	Available device / Description / Range						Error	Zero	Carry	Borrow	Step				
S1	DWORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer							<input checked="" type="radio"/>	<input checked="" type="radio"/>	<input type="radio"/>	9				
		Data address to execute the BCD subtraction operation with S2														
		h00000000 to h99999999														
S2	DWORD	X, Y, F, Z, T, C, M, S, L, D, UW							<input checked="" type="radio"/>	<input checked="" type="radio"/>	<input type="radio"/>	9				
		Data address to execute the BCD subtraction operation with S1														
		h00000000 to h99999999														
D	DWORD	Y, F, Z, T, C, M, S, L, D, UW							<input checked="" type="radio"/>	<input checked="" type="radio"/>	<input type="radio"/>	9				
		Address to save the operation result														
		h00000000 to h99999999														
N	WORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer							<input checked="" type="radio"/>	<input checked="" type="radio"/>	<input type="radio"/>	9				
		The number of S2 data address and saved address to execute the operation with S1														
		In the range within the corresponding device area of S2 and D														

&lt;Ladder&gt;




1. Subtracts the number of N double word values from S2 to S2(N-1), composed of BCD code, from the double word value of S1 composed of BCD code respectively, and then stores the result into the number of N destination double words beginning with D as BCD code.
2. If any of the value not composed of the BCD code is detected in S1 and S2, error flag is SET.
3. If any of the result value in the range from D to D+N is out of the D range, carry flag is SET.
4. If any of the result value in the range from D to D+N is '0', zero flag is SET.




### 3.2.154 Arithmetic operation instruction(MULB)

Arithmetic operation instruction		MULB	S1	S2	D	Applicable model										
OP	DATA type	Available device / Description / Range					LP-S044, LP-S070									
S1	WORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer					Error	Zero	Carry	Borrow	Step 7					
		Data address to execute the BCD multiplication with S2														
		h0000 to h9999														
S2	WORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer														
		Data address to execute the BCD multiplication with S1														
		h0000 to h9999														
D	DWORD	Y, F, Z, T, C, M, S, L, D, UW														
		Address to save the operation result														
		h00000000 to h99999999														

#### <Ladder>




1. Multiplies the word value of S1 and that of S2, both are composed of BCD code and then stores the result into the destination double word D as BCD code.
2. If any of the value not composed of the BCD code is detected in S1 and S2, error flag is SET. (Except 0 to 9999)
3. If the result value is out of the D range, carry flag is SET.
4. If the result value is '0', zero flag is SET.




### 3.2.155 Arithmetic operation instruction(DMULB)

Arithmetic operation instruction		DMULB	S1	S2	D	Applicable model									
OP	DATA type	Available device / Description / Range					Error	Zero	Carry	Borrow	Step				
<b>S1</b>	DWORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer						<input checked="" type="radio"/>	<input checked="" type="radio"/>	<input checked="" type="radio"/>	7				
		Data address to execute the BCD multiplication with S2													
		h00000000 to h99999999													
<b>S2</b>	DWORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer						<input checked="" type="radio"/>	<input checked="" type="radio"/>	<input checked="" type="radio"/>	7				
		Data address to execute the BCD multiplication with S1													
		h00000000 to h99999999													
<b>D</b>	QWORD	Y, F, Z, T, C, M, S, L, D, UW						<input checked="" type="radio"/>	<input checked="" type="radio"/>	<input checked="" type="radio"/>	7				
		Address to save the operation result													

#### <Ladder>




1. Multiplies the double word value of S1 and that of S2, both are composed of BCD code, and then stores the result into the destination quad word D as BCD code.
2. If any of the value not composed of the BCD code is detected in S1 and S2, error flag is SET.  
(Except 0 to 99999999)
3. If the result value is out of the D range, carry flag is SET.
4. If the result value is '0', zero flag is SET.





### 3.2.156 Arithmetic operation instruction(MULBL)

Arithmetic operation instruction		MULBL	S1	S2	D	N	Applicable model				
OP	DATA type	Available device / Description / Range									
S1	WORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer Data address to execute the BCD multiplication with S2 h0000 to h9999					Error	Zero	Carry	Borrow	Step 9
S2	WORD	X, Y, F, Z, T, C, M, S, L, D, UW Data address to execute the BCD multiplication with S1 h0000 to h9999									
D	WORD	Y, F, Z, T, C, M, S, L, D, UW Address to save the operation result h00000000 to h99999999									
N	WORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer The number of S2 data address and saved address to execute the operation with S1 In the range within the corresponding device area of S2 and D									

&lt;Ladder&gt;




1. Multiplies the word value of S1 and the number of N word values from S2 to S2(N-1), both are composed of BCD code, one by one, and then stores the result into the number of N destination double words beginning with D as BCD code.
2. If any of the value not composed of the BCD code is detected in S1 and S2, error flag is SET.
3. If any of the result value in the range from D to D+N is out of the D range, carry flag is SET.
4. If any of the result value in the range from D to D+N is '0', zero flag is SET.





### 3.2.157 Arithmetic operation instruction(DMULBL)

Arithmetic operation instruction		DMULBL	S1	S2	D	N	Applicable model									
OP	DATA type	Available device / Description / Range						Error	Zero	Carry	Borrow	Step				
<b>S1</b>	DWORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer							<input checked="" type="radio"/>	<input checked="" type="radio"/>	<input checked="" type="radio"/>	9				
		Data address to execute the BCD multiplication with S2														
		h00000000 to h99999999														
<b>S2</b>	DWORD	X, Y, F, Z, T, C, M, S, L, D, UW							<input checked="" type="radio"/>	<input checked="" type="radio"/>	<input checked="" type="radio"/>	9				
		Data address to execute the BCD multiplication with S1														
		h00000000 to h99999999														
<b>D</b>	QWORD	Y, F, Z, T, C, M, S, L, D, UW							<input checked="" type="radio"/>	<input checked="" type="radio"/>	<input checked="" type="radio"/>	9				
		Address to save the operation result														
<b>N</b>	WORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer							<input checked="" type="radio"/>	<input checked="" type="radio"/>	<input checked="" type="radio"/>	9				
		The number of S2 data address and saved address to execute the operation with S1														
		In the range within the corresponding device area of S2 and D														

&lt;Ladder&gt;




1. Multiplies the double word value of S1 composed of BCD code and the number of N double words from S2 to S2(N-1) composed of BCD code, one by one, and then stores the result into the number of N destination quad words beginning with D as BCD code.
2. If any of the value not composed of the BCD code is detected in S1 and S2, error flag is SET.
3. If any of the result value in the range from D to D+N is out of the D range, carry flag is SET.
4. If any of the result value in the range from D to D+N is '0', zero flag is SET.




### 3.2.158 Arithmetic operation instruction(DIVB)

Arithmetic operation instruction		DIVB	S1	S2	D	Applicable model					
OP	DATA type	Available device / Description / Range									
S1	WORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer									
		Data address to execute the BCD division operation with S2									
		h0000 to h9999									
S2	WORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer									
		Data address to execute the BCD division operation with S1									
		h0000 to h9999									
D	WORD	Y, F, Z, T, C, M, S, L, D, UW									
		Address to save the operation result									
		h0000 to h9999									

&lt;Ladder&gt;




- Divides the word value of S1 composed of BCD code by the word value of S2 composed of BCD code, and then stores the quotient and the remainder into the D and D+1 words respectively.
- If S2 is 0, or either S1 or S2 is not the BCD code, error flag is SET.
- If the quotient is '0', zero flag is SET.




### 3.2.159 Arithmetic operation instruction(DDIVB)

Arithmetic operation instruction		DDIVB	S1	S2	D	Applicable model									
OP	DATA type	Available device / Description / Range													
S1	DWORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer						Error	Zero	Carry	Borrow				
		Data address to execute the BCD division operation with S2													
		h00000000 to h99999999													
S2	DWORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer													
		Data address to execute the BCD division operation with S1													
		h00000000 to h99999999													
D	DWORD	Y, F, Z, T, C, M, S, L, D, UW													
		Address to save the operation result													
		h00000000 to h99999999													

&lt;Ladder&gt;




- Divides the double word value of S1 composed of BCD code by the double word value of S2 composed of BCD code, and then stores the quotient and the remainder into the D and D+1 double words respectively.
- If S2 is 0, or either S1 or S2 is not the BCD code,error flag is SET.
- If the quotient is '0', zero flag is SET.





### 3.2.160 Arithmetic operation instruction(DIVBL)

Arithmetic operation instruction		DIVBL	S1	S2	D	N	Applicable model				
OP	DATA type	Available device / Description / Range									
S1	WORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer Data address to execute the BCD division operation with S2 h0000 to h9999					Error	Zero	Carry	Borrow	Step 9
S2	WORD	X, Y, F, Z, T, C, M, S, L, D, UW Data address to execute the BCD division operation with S1 h0000 to h9999									
D	WORD	Y, F, Z, T, C, M, S, L, D, UW Address to save the operation result h0000 to h9999									
N	WORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer The number of S2 data address and saved address to execute the operation with S1 In the range within the corresponding device area of S2 and D									

## &lt;Ladder&gt;




1. Divides the word value of S1 composed of BCD code by the number of N word values from S2 to S2(N-1) composed of BCD code, and then stores the quotient and the remainder into the D and D+1 double words respectively.
2. If S2 is 0, or either S1 or S2 is not the BCD code,error flag is SET.
3. If the quotient is '0', zero flag is SET.





### 3.2.161 Arithmetic operation instruction(DDIVBL)

Arithmetic operation instruction		DDIVBL	S1	S2	D	N	Applicable model									
OP	DATA type	Available device / Description / Range						Error	Zero	Carry	Borrow	Step				
<b>S1</b>	DWORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer							Error ◎	Zero ◎	Carry	Borrow				
		Data address to execute the BCD division operation with S2														
		h00000000 to h99999999														
<b>S2</b>	DWORD	X, Y, F, Z, T, C, M, S, L, D, UW								Step 9						
		Data address to execute the BCD division operation with S1														
		h00000000 to h99999999														
<b>D</b>	DWORD	Y, F, Z, T, C, M, S, L, D, UW														
		Address to save the operation result														
		h00000000 to h99999999														
<b>N</b>	WORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer														
		The number of S2 data address and saved address to execute the operation with S1														
		In the range within the corresponding device area of S2 and D														

#### <Ladder>




- Divides the double word value of S1 composed of BCD code by the number of N double word values from S2 to S2(N-1), composed of BCD code, and then stores the quotient and the remainder into the D and D+1 double words respectively.
- If S2 is 0, or either S1 or S2 is not the BCD code, error flag is SET.
- If the quotient is '0', zero flag is SET.




### 3.2.162 Arithmetic operation instruction(INCB)

<b>Arithmetic operation instruction</b>	<b>INCB</b>	<b>D</b>	Applicable model
			LP-S044, LP-S070
<b>OP</b>	<b>DATA type</b>	<b>Available device / Description / Range</b>	
<b>D</b>	WORD	Y, F, Z, T, C, M, S, L, D, UW BCD data address to execute the operation h0000 to h9999	Error <input checked="" type="checkbox"/> Zero <input checked="" type="checkbox"/> Carry <input checked="" type="checkbox"/> Borrow <input type="checkbox"/> Step 3

#### <Ladder>



1. Increases the word value of D composed of BCD code by 1 as BCD code.
2. If the word value of D is not the BCD code, error flag is SET.
3. If the increased result is 0(BCD), zero flag is SET.
4. If the result value is out of the D word range, carry flag is SET.



### 3.2.163 Arithmetic operation instruction(DINCB)

**Arithmetic  
operation  
instruction**

**DINCB**


**D**

Applicable model

LP-S044, LP-S070

OP	DATA type	Available device / Description / Range	Error	Zero	Carry	Borrow	Step
<b>D</b>	DWORD	Y, F, Z, T, C, M, S, L, D, UW	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
		BCD data address to execute the operation	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
		h00000000 to h99999999	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	3

#### <Ladder>




1. Increases the double word value of D composed of BCD code by 1 as BCD code.
2. If the double word value of D is not the BCD code, error flag is SET.
3. If the increased result is 0(BCD), zero flag is SET.
4. If the result value is out of the D double word range, carry flag is SET.




### 3.2.164 Arithmetic operation instruction(DECB)

<b>Arithmetic operation instruction</b>	<b>DECB</b>	<b>D</b>	Applicable model
			LP-S044, LP-S070
<b>OP</b>	<b>DATA type</b>	<b>Available device / Description / Range</b>	
<b>D</b>	WORD	Y, F, Z, T, C, M, S, L, D, UW	Error
		BCD data address to execute the operation	Zero
		h0000 to h9999	Carry
	Borrow		
	Step		
			3

#### <Ladder>




1. Decreases the word value of D composed of BCD code by 1 as BCD code.
2. If the word value of D is not the BCD code, error flag is SET.
3. If the decreased result is 0(BCD), zero flag is SET.
4. If the result value is out of D word range, borrow flag is SET.



### 3.2.165 Arithmetic operation instruction(DDECB)

<b>Arithmetic operation instruction</b>	<b>DDECB</b>	<b>D</b>	Applicable model
			LP-S044, LP-S070
<b>OP</b>	<b>DATA type</b>	<b>Available device / Description / Range</b>	
<b>D</b>	DWORD	Y, F, Z, T, C, M, S, L, D, UW BCD data address to execute the operation h00000000 to h99999999	Error <input checked="" type="radio"/> Zero <input checked="" type="radio"/> Carry <input type="radio"/> Borrow <input checked="" type="radio"/> Step 3

#### <Ladder>




1. Decreases the double word of D composed of BCD code by 1 as BCD code.
2. If the double word value of D is not BCD code, error flag is SET.
3. If the decreased result is 0(BCD), zero flag is SET.
4. If the result value is out of the D double word range, borrow flag is SET.




### 3.2.166 Logical operation instruction(WAND)

Logical operation instruction		WAND	S1	S2	D	Applicable model										
OP	DATA type	Available device / Description / Range					Error	Zero	Carry	Borrow	Step					
S1	WORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer					Error	Zero	Carry	Borrow	Step					
		Data address to execute the '&' operation with S2														
		0(h0000) to 65535(hFFFF)														
S2	WORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer									7					
		Data address to execute the '&' operation with S1														
		0(h0000) to 65535(hFFFF)														
D	WORD	Y, F, Z, T, C, M, S, L, D, UW														
		Address to save the operation result														
		0(h0000) to 65535(hFFFF)														

#### <Ladder>




1. Executes the '&' operation for every bit of S1 word and the corresponding bit of S2 word and then stores the result into the D word.
2. If the result value is '0', zero flag is SET.



### 3.2.167 Logical operation instruction(DAND)


Logical operation instruction		DAND	S1	S2	D	Applicable model										
OP	DATA type	Available device / Description / Range					Error	Zero	Carry	Borrow	Step					
<b>S1</b>	DWORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer					Error	Zero	Carry	Borrow	Step					
		Data address to execute the '&' operation with S2														
		0(h0000) to 4294967295(hFFFFFFF)														
<b>S2</b>	DWORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer					Error	Zero	Carry	Borrow	Step					
		Data address to execute the '&' operation with S1														
		0(h0000) to 4294967295(hFFFFFFF)														
<b>D</b>	DWORD	Y, F, Z, T, C, M, S, L, D, UW					Error	Zero	Carry	Borrow	Step					
		Address to save the operation result														
		0(h0000) to 4294967295(hFFFFFFF)														

#### <Ladder>



1. Executes the '&' operation for every bit of S1 double word and the corresponding bit of S2 double word and then stores the result into the D double word.


2. If the result value is '0', zero flag is SET.




### 3.2.168 Logical operation instruction(AAND)

Logical operation instruction		AAND	S1	S2	D	N	Applicable model										
OP	DATA type	Available device / Description / Range															
S1	BIT	X, Y, F, T, C, M, UB					LP-S044, LP-S070  <table border="1"><tr><td>Error</td><td>Zero</td><td>Carry</td><td>Borrow</td><td>Step</td></tr><tr><td></td><td>(○)</td><td></td><td></td><td>9</td></tr></table>	Error	Zero	Carry	Borrow	Step		(○)			9
Error	Zero	Carry	Borrow	Step													
	(○)			9													
Start address of the bit device to execute the '&' operation with S2																	
Not applicable																	
S2	BIT	X, Y, F, T, C, M, UB															
		Start address of the bit device to execute the '&' operation with S1															
		Not applicable															
D	BIT	Y, F, T, C, M, UB															
		Start address of the bit device to store the operation result															
		Not applicable															
N	WORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer															
		The number of bit device to execute the operation including the start address															
		As many as the number of devices remained in the corresponding S1, S2, and D area															

#### <Ladder>




Executes the '&' operation for the number of N bits, from S1 to SN, and the number of N bits, from S2 to S2(N-1), and then stores the result into the number of N bits beginning with D.





### 3.2.169 Logical operation instruction(WANDL)

Logical operation instruction		WANDL	S1	S2	D	N	Applicable model
OP	DATA type	Available device / Description / Range					
<b>S1</b>	WORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer					Error Zero Carry Borrow Step 9
		Data address to execute the '&' operation with S2					
		0(h0000) to 65535(hFFFF)					
<b>S2</b>	WORD	X, Y, F, Z, T, C, M, S, L, D, UW					
		Data address to execute the '&' operation with S1					
		0(h0000) to 65535(hFFFF)					
<b>D</b>	WORD	Y, F, Z, T, C, M, S, L, D, UW					
		Address to save the operation result					
		0(h0000) to 65535(hFFFF)					
<b>N</b>	WORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer					
		The number of S2 data address and saved address to execute the operation with S1					
		In the range within the corresponding device area of S2 and D					

#### <Ladder>




1. Executes the bitwise '&' operation for every bit of S1 word and the number of N words from S2 to S2(N-1) and then stores the result into the number of N words beginning with D.
2. If the result value is '0' word, zero flag is SET.





### 3.2.170 Logical operation instruction(DANDL)

Logical operation instruction		DANDL	S1	S2	D	N	Applicable model				
<b>OP</b>	<b>DATA type</b>	<b>Available device / Description / Range</b>					Error	Zero	Carry	Borrow	Step
<b>S1</b>	DWORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer									
		Data address to execute the '&' operation with S2									
		0(h0000) to 4294967295(hFFFFFFF)									9
<b>S2</b>	DWORD	X, Y, F, Z, T, C, M, S, L, D, UW									
		Data address to execute the '&' operation with S1									
		0(h0000) to 4294967295(hFFFFFFF)									
<b>D</b>	DWORD	Y, F, Z, T, C, M, S, L, D, UW									
		Address to save the operation result									
		0(h0000) to 4294967295(hFFFFFFF)									
<b>N</b>	WORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer									
		The number of S2 data address and saved address to execute the operation with S1									
		In the range within the corresponding device area of S2 and D									

## &lt;Ladder&gt;




1. Executes the bitwise '&' operation for every bit of S1 double words and the number of N words from S2 to S2(N-1) and then stores the result into the number of N words beginning with D.
2. If the result value is '0' double word, zero flag is SET.





### 3.2.171 Logical operation instruction(WOR)

Logical operation instruction		WOR	S1	S2	D	Applicable model									
OP	DATA type	Available device / Description / Range													
<b>S1</b>	WORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer						Error	Zero	Carry	Borrow				
		Data address to execute the 'OR' operation with S2													
		0(h0000) to 65535(hFFFF)													
<b>S2</b>	WORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer													
		Data address to execute the 'OR' operation with S1													
		0(h0000) to 65535(hFFFF)													
<b>D</b>	WORD	Y, F, Z, T, C, M, S, L, D, UW													
		Address to save the operation result													
		0(h0000) to 65535(hFFFF)													

&lt;Ladder&gt;




1. Executes the logical 'OR' operation for every bit in S1 words and the corresponding bit of S2 words, and then stores the result into the D word.
2. If the result value is '0', zero flag is SET.



### 3.2.172 Logical operation instruction(DOR)


Logical operation instruction		OP	DATA type	Available device / Description / Range	S1	S2	D	Applicable model
S1	DWORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer						LP-S044, LP-S070
		Data address to execute the 'OR' operation with S2						
		0(h0000) to 4294967295(hFFFFFFF)						
S2	DWORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer						
		Data address to execute the 'OR' operation with S1						
		0(h0000) to 4294967295(hFFFFFFF)						
D	DWORD	Y, F, Z, T, C, M, S, L, D, UW						
		Address to save the operation result						
		0(h0000) to 4294967295(hFFFFFFF)						

#### <Ladder>



1. Executes the logical 'OR' operation for every bit of S1 double words and the corresponding bit of S2 double words, and then stores the result into the D double word.


2. If the result value is '0', zero flag is SET.




### 3.2.173 Logical operation instruction(AOR)

Logical operation instruction		AOR	S1	S2	D	N	Applicable model					
OP	DATA type	Available device / Description / Range						Error	Zero	Carry	Borrow	Step
<b>S1</b>	BIT	X, Y, F, T, C, M, UB										
		Data address to execute the 'OR' operation with S2										
		Not applicable										
<b>S2</b>	BIT	X, Y, F, T, C, M, UB										
		Data address to execute the 'OR' operation with S1										
		Not applicable										
<b>D</b>	BIT	Y, F, T, C, M, UB										
		Start address of the bit device to save the operation result										
		Not applicable										
<b>N</b>	WORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer										
		The number of bit devices to execute the operation including the start address										
		As many as the number of devices remained in the corresponding S1, S2, and D area										

#### <Ladder>




Executes the logical 'OR' operation for the number of N bits from S1 to SN and the number of N bits from S2 to S2(N-1), and then stores the result into the the number of N bits beginning with D.




### 3.2.174 Logical operation instruction(WORL)

Logical operation instruction		WORL	S1	S2	D	N	Applicable model										
OP	DATA type	Available device / Description / Range						Error	Zero	Carry	Borrow	Step					
S1	WORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer						Error	Zero	Carry	Borrow	Step					
		Data address to execute the 'OR' operation with S2															
		0(h0000) to 65535(hFFFF)															
S2	WORD	X, Y, F, Z, T, C, M, S, L, D, UW															
		Data address to execute the 'OR' operation with S1															
		0(h0000) to 65535(hFFFF)															
D	WORD	Y, F, Z, T, C, M, S, L, D, UW															
		Address to save the operation result															
		0(h0000) to 65535(hFFFF)															
N	WORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer															
		The number of S2 data address and saved address to execute the operation with S1															
		In the range within the corresponding device area of S2 and D															

#### <Ladder>




1. Executes the bitwise logical 'OR' operation for every bit of S1 words and the number of N words from S2 to S2(N-1), and then stores the result into the D word.
2. If the result value is '0' word, zero flag is SET.



### 3.2.175 Logical operation instruction(DORL)


Logical operation instruction		DORL	S1	S2	D	N	Applicable model									
OP	DATA type	Available device / Description / Range						Error	Zero	Carry	Borrow	Step				
<b>S1</b>	DWORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer							◎			9				
		Data address to execute the 'OR' operation with S2														
		0(h0000) to 4294967295(hFFFFFFF)														
<b>S2</b>	DWORD	X, Y, F, Z, T, C, M, S, L, D, UW														
		Data address to execute the 'OR' operation with S1														
		0(h0000) to 4294967295(hFFFFFFF)														
<b>D</b>	DWORD	Y, F, Z, T, C, M, S, L, D, UW														
		Address to save the operation result														
		0(h0000) to 4294967295(hFFFFFFF)														
<b>N</b>	WORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer														
		The number of S2 data address and saved address to execute the operation with S1														
		In the range within the corresponding device area of S2 and D														

&lt;Ladder&gt;



1. Executes the bitwise logical 'OR' operation for every bit of S1 double word and the number of N double words from S2 to S2(N-1) respectively and then stores the result into the number of N double words beginning with D double word.


2. If the result value is '0' double word, zero flag is SET.




### 3.2.176 Logical operation instruction(XOR)

Logical operation instruction		XOR	S1	S2	D	Applicable model									
OP	DATA type	Available device / Description / Range													
S1	WORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer						Error	Zero	Carry	Borrow				
		Data address to execute the 'XOR' operation with S2													
		0(h0000) to 65535(hFFFF)													
S2	WORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer													
		Data address to execute the 'XOR' operation with S1													
		0(h0000) to 65535(hFFFF)													
D	WORD	Y, F, Z, T, C, M, S, L, D, UW													
		Address to save the operation result													
		0(h0000) to 65535(hFFFF)													

#### <Ladder>




1. Executes the logical 'XOR' operation for every bit of S1 word and the corresponding bit of S2 word and then stores the result into the D word.
2. If the result value is '0', zero flag is SET.




### 3.2.177 Logical operation instruction(DXOR)

Logical operation instruction		DXOR	S1	S2	D	Applicable model									
OP	DATA type	Available device / Description / Range						LP-S044, LP-S070							
<b>S1</b>	DWORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer						Error	Zero	Carry	Borrow				
		Data address to execute the 'XOR' operation with S2													
		0(h0000) to 4294967295(hFFFFFFF)													
<b>S2</b>	DWORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer													
		Data address to execute the 'XOR' operation with S1													
		0(h0000) to 4294967295(hFFFFFFF)													
<b>D</b>	DWORD	Y, F, Z, T, C, M, S, L, D, UW													
		Address to save the operation result													
		0(h0000) to 4294967295(hFFFFFFF)													

#### <Ladder>





1. Executes the logical 'XOR' operation for every bit of S1 double word and the corresponding bit of S2 double word and then stores the result into the D double word.
2. If the result value is '0', zero flag is SET.



### 3.2.178 Logical operation instruction(AXOR)

Logical operation instruction		AXOR	S1	S2	D	N	Applicable model
OP	DATA type	Available device / Description / Range					
S1	BIT	X, Y, F, T, C, M, UB					Error Zero Carry Borrow Step 9
		Start address of the bit device to execute the 'XOR' operation with S2					
		Not applicable					
S2	BIT	X, Y, F, T, C, M, UB					Error Zero Carry Borrow Step 9
		Start address of the bit device to execute the 'XOR' operation with S1					
		Not applicable					
D	BIT	Y, F, T, C, M, UB					Error Zero Carry Borrow Step 9
		Address to save the operation result					
		Not applicable					
N	WORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer					Error Zero Carry Borrow Step 9
		The number of bit devices including the start address to execute the operation					
		As many as the number of devices remained in S1, S2 and D area					


#### <Ladder>





### 3.2.179 Logical operation instruction(XORL)

Logical operation instruction		XORL	S1	S2	D	N	Applicable model					
OP	DATA type	Available device / Description / Range						Error	Zero	Carry	Borrow	Step
<b>S1</b>	WORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer										
		Data address to execute the 'XOR' operation with S2										
		0(h0000) to 65535(hFFFF)										
<b>S2</b>	WORD	X, Y, F, Z, T, C, M, S, L, D, UW										
		Data address to execute the 'XOR' operation with S1										
		0(h0000) to 65535(hFFFF)										
<b>D</b>	WORD	Y, F, Z, T, C, M, S, L, D, UW										
		Address to save the operation result										
		0(h0000) to 65535(hFFFF)										
<b>N</b>	WORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer										
		The number of S2 data address and saved address to execute the operation with S1										
		In the range within the corresponding device area of S2 and D										

#### <Ladder>




1. Executes the bitwise logical 'XOR' operation for every bit of S1 word and the number of N words, from S2 to S2(N-1), then stores the result into the number of N words beginning with D.
2. If the result value is '0' word, zero flag is SET.





### 3.2.180 Logical operation instruction(DXORL)

Logical operation instruction		DXORL	S1	S2	D	N	Applicable model												
OP	DATA type	Available device / Description / Range						LP-S044, LP-S070	Error	Zero	Carry	Borrow	Step 9						
S1	DWORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer						LP-S044, LP-S070	Error	Zero	Carry	Borrow	Step 9						
		Data address to execute the 'XOR' operation with S2																	
		0(h0000) to 4294967295(hFFFFFFF)																	
S2	DWORD	X, Y, F, Z, T, C, M, S, L, D, UW						LP-S044, LP-S070	Error	Zero	Carry	Borrow	Step 9						
		Data address to execute the 'XOR' operation with S1																	
		0(h0000) to 4294967295(hFFFFFFF)																	
D	DWORD	Y, F, Z, T, C, M, S, L, D, UW						LP-S044, LP-S070	Error	Zero	Carry	Borrow	Step 9						
		Address to save the operation result																	
		0(h0000) to 4294967295(hFFFFFFF)																	
N	WORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer						LP-S044, LP-S070	Error	Zero	Carry	Borrow	Step 9						
		The number of S2 data address and saved address to execute the operation with S1																	
		In the range within the corresponding device area of S2 and D																	

#### <Ladder>




1. Executes the bitwise logical 'XOR' operation for every bit of S1 double word and the number of N double words from S2 to S2(N-1), and then stores the result into the number of N double words beginning with D.
2. If the result value is '0' double word, zero flag is SET.




### 3.2.181 Logical operation instruction(XNR)

Logical operation instruction		XNR	S1	S2	D	Applicable model									
OP	DATA type	Available device / Description / Range													
<b>S1</b>	WORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer						Error	Zero	Carry	Borrow				
		Data address to execute the 'XNR' operation with S2													
		0(h0000) to 65535(hFFFF)													
<b>S2</b>	WORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer													
		Data address to execute the 'XNR' operation with S1													
		0(h0000) to 65535(hFFFF)													
<b>D</b>	WORD	Y, F, Z, T, C, M, S, L, D, UW													
		Address to save the operation result													
		0(h0000) to 65535(hFFFF)													

&lt;Ladder&gt;




1. Executes the logical 'XNR' operation for every bit of S1 word and the corresponding bit of S2 word, bit by bit, and then stores the result into the D word.
2. If the result value is '0', zero flag is SET.




### 3.2.182 Logical operation instruction(DXNR)

Logical operation instruction		DXNR	S1	S2	D	Applicable model												
OP	DATA type	Available device / Description / Range					LP-S044, LP-S070	Error	Zero	Carry	Borrow	Step						
S1	DWORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer					LP-S044, LP-S070	Error	Zero	Carry	Borrow	Step						
		Data address to execute the 'XNR' operation with S2																
		0(h0000) to 4294967295(hFFFFFFF)																
S2	DWORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer					LP-S044, LP-S070	Error	Zero	Carry	Borrow	Step						
		Data address to execute the 'XNR' operation with S1																
		0(h0000) to 4294967295(hFFFFFFF)																
D	DWORD	Y, F, Z, T, C, M, S, L, D, UW					LP-S044, LP-S070	Error	Zero	Carry	Borrow	Step						
		Address to save the operation result																
		0(h0000) to 4294967295(hFFFFFFF)																

#### <Ladder>




1. Executes the logical 'XNR' operation for every bit of S1 double word and the corresponding bit of S2 double word, and then stores the result into the D double word.
2. If the result value is '0', zero flag is SET.




### 3.2.183 Logical operation instruction(AXNR)

Logical operation instruction		AXNR	S1	S2	D	N	Applicable model									
OP	DATA type	Available device / Description / Range						Error	Zero	Carry	Borrow	Step				
<b>S1</b>	BIT	X, Y, F, T, C, M, UB							◎	◎	◎	9				
		Start address of the bit device to execute the 'XNR' operation with S2														
		Not applicable														
<b>S2</b>	BIT	X, Y, F, T, C, M, UB							◎	◎	◎	9				
		Start address of the bit device to execute the 'XNR' operation with S1														
		Not applicable														
<b>D</b>	BIT	Y, F, T, C, M, UB							◎	◎	◎	9				
		Start address of the bit device to save the operation result														
		Not applicable														
<b>N</b>	WORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer							◎	◎	◎	9				
		The number of bit devices to execute the operation including the start address														
		As many as the number of devices remained in the corresponding S1, S2, and D area														

#### <Ladder>




Executes the logical 'XNR' operation for the number of N bits from S1 to SN and the number of N bits from S2 to S2(N-1), and then stores the result into the number of N bits beginning with D destination bit.




### 3.2.184 Logical operation instruction(XNRL)

Logical operation instruction		XNRL	S1	S2	D	N	Applicable model					
OP	DATA type	Available device / Description / Range					LP-S044, LP-S070	Error	Zero	Carry	Borrow	Step
S1	WORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer										
		Data address to execute the 'XNR' operation with S2										
		0(h0000) to 65535(hFFFF)						9				
S2	WORD	X, Y, F, Z, T, C, M, S, L, D, UW										
		Data address to execute the 'XNR' operation with S1										
		0(h0000) to 65535(hFFFF)										
D	WORD	Y, F, Z, T, C, M, S, L, D, UW										
		Address to save the operation result										
		0(h0000) to 65535(hFFFF)										
N	WORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer										
		The number of S2 data address and saved address to execute the operation with S1										
		In the range within the corresponding device area of S2 and D										

#### <Ladder>




1. Executes the bitwise logical 'XNR' operation for every bit of S1 word and the number of N words from S2 to S2(N-1) bit by bit, and then stores the result into the number of N words from D word.
2. If the result value is '0' word, zero flag is SET.





### 3.2.185 Logical operation instruction(DXNRL)

Logical operation instruction		DXNRL	S1	S2	D	N	Applicable model									
OP	DATA type	Available device / Description / Range						Error	Zero	Carry	Borrow	Step				
<b>S1</b>	DWORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer							◎	◎	◎	9				
		Data address to execute the 'XNR' operation with S2														
		0(h0000) to 4294967295(hFFFFFFF)														
<b>S2</b>	DWORD	X, Y, F, Z, T, C, M, S, L, D, UW														
		Data address to execute the 'XNR' operation with S1														
		0(h0000) to 4294967295(hFFFFFFF)														
<b>D</b>	DWORD	Y, F, Z, T, C, M, S, L, D, UW														
		Address to save the operation result														
		0(h0000) to 4294967295(hFFFFFFF)														
<b>N</b>	WORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer														
		The number of S2 data address and saved address to execute the operation with S1														
		In the range within the corresponding device area of S2 and D														

#### <Ladder>




1. Executes the logical 'XNR' operation for every bit of S1 double word and the number of N double words from S2 to S2(N-1), bit by bit, and then stores the result into the number of N double words beginning with D.
2. If the result value is '0' double word, zero flag is SET.




### 3.2.186 BIN/BCD conversion instruction(BIN2BCD)

<b>BIN/BCD conversion instruction</b>	<b>BIN2BCD</b>	<b>S</b>	<b>D</b>	Applicable model
		X, Y, F, Z, T, C, M, S, L, D, UW, integer		LP-S044, LP-S070
<b>S</b>	WORD	Device number which has to be transmitted data or data		Error
		0 to 9999(h0000 to h270F)		Zero
<b>D</b>	WORD	Y, F, Z, T, C, M, S, L, D, UW		Carry
		Device address to save converted data		Borrow
		h0000 to h9999		Step 5

&lt;Ladder&gt;




- Converts the BINARY data (0 to h270F) stored in S device into the BCD data and then stores the result into the D word.
- If the converted value is out of the range between 0 to 9999(BIN data 0 to h270F), error flag is SET.




### 3.2.187 BIN/BCD conversion instruction(DBIN2BCD)

BIN/BCD conversion instruction				DBIN2BCD	S	D	Applicable model										
OP	DATA type	Available device / Description / Range															
S	DWORD	X, Y, F, Z, T, C, M, S, L, D, UW, integer						Error	Zero	Carry	Borrow	Step					
		Device number which has to be transmitted data or data															
		0 to 99999999(h00000000 to h05F5E0FF)															
D	DWORD	Y, F, Z, T, C, M, S, L, D, UW															
		Device address to save converted data															
		h00000000 to h99999999															

#### <Ladder>




- Converts the BINARY data (0 to h05F5E0FF) stored in S double word into the BCD data, and then stores the result into the D double word.
- If the converted value is out of the range from 0 to 99999999(BIN data 0 to h05F5E0FF), error flag is SET.




### 3.2.188 BIN/BCD conversion instruction(BCD2BIN)

BIN/BCD conversion instruction			BCD2BIN	S	D	Applicable model													
OP	DATA type	Available device / Description / Range																	
S	WORD	X, Y, M, S, T, C, D, Z, F, UW, integer																	
		Device address which saves BCD data to be converted as BIN value																	
		h0000 to h9999																	
D	WORD	Y, M, S, T, C, D, Z, F, UW																	
		Device address to save converted data																	
		0 to 9999(h0000 to h270F)																	

&lt;Ladder&gt;




- Converts the BCD code (0 to 9999) stored in S word into the BINARY data, and then stores the result into the D word.
- If the S word is not the BCD code, error flag is SET.




### 3.2.189 BIN/BCD conversion instruction(DBCD2BIN)

BIN/BCD conversion instruction				DBCD2BIN	S	D	Applicable model										
OP	DATA type	Available device / Description / Range															
S	DWORD	X, Y, M, S, T, C, D, Z, F, UW, integer						Error	Zero	Carry	Borrow	Step 5					
		Device address which saves BCD data to be converted as BIN value															
		h00000000 to h99999999															
D	DWORD	Y, M, S, T, C, D, Z, F, UW															
		Device address to save converted data															
		0 to 99999999(h00000000 to h05F5E0FF)															


#### <Ladder>




- Converts the BCD data stored in S double word into the BINARY data, and then stores the result into the D double word.
- If the S double word is not the BCD code, error flag is SET.




### 3.2.190 String conversion instruction(BIN2HASC)

<b>String conversion instruction</b> <b>BIN2HASC</b> <b>S</b> <b>D</b>			Applicable model
			LP-S044, LP-S070
<b>OP</b>	<b>DATA type</b>	<b>Available device / Description / Range</b>	
<b>S</b>	WORD	X, Y, M, S, T, C, D, Z, F, UW, integer	
		Device address which saves to be converted data as ASCII value	
		h0000 to hFFFF	
<b>D</b>	WORD	Y, M, S, T, C, D, Z, F, UW	   
		Device address to save converted data	
		Allowable range per byte(h30 to h39, h41 to h46)	

&lt;Ladder&gt;




- Converts the BINARY data stored in S word into the HEX ASCII one by one in order from the upper order value.
- The converted value is sequentially stored in D double word beginning with D, by 2 digits per word.
- The operation range is 'h0000 to hFFFF'.




### 3.2.191 String conversion instruction(DBIN2HASC)

String conversion instruction DBIN2HASC S D				Applicable model
OP	DATA type	Available device / Description / Range		
<b>S</b>	DWORD	X, Y, M, S, T, C, D, Z, F, UW, integer		LP-S044, LP-S070 Error Zero Carry Borrow Step 5
		Device address which saves to be converted data as ASCII value		
		h00000000 to hFFFFFFF		
<b>D</b>	QWORD	Y, M, S, T, C, D, Z, F, UW		
		Device address to save converted data		
		Allowable range per byte (h30 to h39, h41 to h46)		

#### <Ladder>




1. Converts the BINARY data stored in S double word into the HEX ASCII one by one in order from the upper order value.
2. The converted value is sequentially stored in D quad word beginning with D, by 2 digits per word.
3. The operation range is h00000000 to HFFFFFFF.




### 3.2.192 String conversion instruction(HASC2BIN)

String conversion instruction		HASC2BIN	S	D	Applicable model
		X, Y, M, S, T, C, D, Z, F, UW			LP-S044, LP-S070
<b>S</b>	WORD	Device address which saves HEX ASCII value to be converted data as BIN value			Error
		Allowable range per byte (h30 to h39, h41 to h46)			Zero
<b>D</b>	WORD	Y, M, S, T, C, D, Z, F, UW			Carry
		Device address to save converted data			Borrow
		h0000 to hFFFF			Step 5

&lt;Ladder&gt;




1. Recognizes the double word value of S as ASCII and stores the corresponding value into the D word.
2. If the converted value is not the HEX ASCII, error bit (F34) is SET. (h30 to h39, h41 to h46)




### 3.2.193 String conversion instruction(DHASC2BIN)

String conversion instruction DHASC2BIN S D				Applicable model
OP	DATA type	Available device / Description / Range		
<b>S</b>	DWORD	X, Y, M, S, T, C, D, Z, F, UW		
		Device address which saves HEX ASCII value to be converted data as BIN value		
		Allowable range per byte (h30 to h39, h41 to h46)	Error ◎	Zero Carry Borrow Step 5
<b>D</b>	DWORD	Y, M, S, T, C, D, Z, F, UW		
		Device address to save converted data		
		h00000000 to hFFFFFFF		

#### <Ladder>




1. Recognizes the quad word value of S as ASCII and stores the corresponding value into the D double word.
2. If the converted value is not the HEX ASCII, error bit (F34) is SET. (h30 to h39, h41 to h46)




### 3.2.194 String conversion instruction(BCD2DASC)

String conversion instruction    BCD2DASC    S    D				Applicable model
OP	DATA type	Available device / Description / Range		
S	WORD	X, Y, M, S, T, C, D, Z, F, UW, integer		LP-S044, LP-S070 Error Zero Carry Borrow Step 5
		Device address which saves the data to be converted data as ASCII value		
		h0000 to hFFFF		
D	DWORD	Y, M, S, T, C, D, Z, F, UW		
		Device address to save converted data		
		Allowable range per byte (h30 to h39, h41 to h46)		

&lt;Ladder&gt;




1. Recognizes BCD data stored in S word as decimal number, converts each digit into the ASCII value and then stores them sequentially into the D double word.
2. The operation range is 'h0000 to h9999'.
3. If the S word is not the BCD code, error flag is SET.




### 3.2.195 String conversion instruction(DBCD2DASC)

String conversion instruction DBCD2DASC S D				Applicable model
OP	DATA type	Available device / Description / Range		
S	DWORD	X, Y, M, S, T, C, D, Z, F, UW, integer Device address which saves the BCD data to be converted data as ASCII value h00000000 to h99999999	Error Zero Carry Borrow	LP-S044, LP-S070 Step 5
D	QWORD	Y, M, S, T, C, D, Z, F, UW Device address to save converted data Allowable range per byte (h30 to h39, h41 to h46)		

&lt;Ladder&gt;




1. Recognizes BCD data stored in S double word as decimal number, converts each digit into the ASCII value and then stores them sequentially into the D word.
2. The operation range is h00000000 to h99999999.
3. If the S word is not the BCD code, error flag is SET.




### 3.2.196 String conversion instruction(DASC2BIN)

<b>String conversion instruction</b> <b>DASC2BIN</b> <b>S      D</b>	<b>Applicable model</b> LP-S044, LP-S070																			
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: left; padding: 2px;">OP</th> <th style="text-align: left; padding: 2px;">DATA type</th> <th style="text-align: left; padding: 2px;">Available device / Description / Range</th> </tr> </thead> <tbody> <tr> <td style="text-align: center; padding: 2px;"><b>S</b></td> <td style="text-align: center; padding: 2px;">WORD</td> <td style="padding: 2px;"> X, Y, M, S, T, C, D, Z, F, UW  Device address which saves the Dec ASCII data to be converted as BIN value  h30 to h39 per byte except sign bit (h2D, h28) </td></tr> <tr> <td style="text-align: center; padding: 2px;"><b>D</b></td> <td style="text-align: center; padding: 2px;">WORD</td> <td style="padding: 2px;"> Y, M, S, T, C, D, Z, F, UW  Device address to save converted data  -32768(h8000) to 32767(h7FFF) </td></tr> </tbody> </table>	OP	DATA type	Available device / Description / Range	<b>S</b>	WORD	X, Y, M, S, T, C, D, Z, F, UW Device address which saves the Dec ASCII data to be converted as BIN value h30 to h39 per byte except sign bit (h2D, h28)	<b>D</b>	WORD	Y, M, S, T, C, D, Z, F, UW Device address to save converted data -32768(h8000) to 32767(h7FFF)	<table border="1" style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td style="text-align: center; padding: 2px;">Error</td> <td style="text-align: center; padding: 2px;">Zero</td> <td style="text-align: center; padding: 2px;">Carry</td> <td style="text-align: center; padding: 2px;">Borrow</td> <td style="text-align: center; padding: 2px;">Step</td> </tr> <tr> <td style="text-align: center; padding: 2px;">(◎)</td> <td style="text-align: center; padding: 2px;"></td> <td style="text-align: center; padding: 2px;"></td> <td style="text-align: center; padding: 2px;"></td> <td style="text-align: center; padding: 2px;">5</td> </tr> </table>	Error	Zero	Carry	Borrow	Step	(◎)				5
OP	DATA type	Available device / Description / Range																		
<b>S</b>	WORD	X, Y, M, S, T, C, D, Z, F, UW Device address which saves the Dec ASCII data to be converted as BIN value h30 to h39 per byte except sign bit (h2D, h28)																		
<b>D</b>	WORD	Y, M, S, T, C, D, Z, F, UW Device address to save converted data -32768(h8000) to 32767(h7FFF)																		
Error	Zero	Carry	Borrow	Step																
(◎)				5																

&lt;Ladder&gt;




1. Recognizes the ASCII data stored in S word as decimal number, convert each digit into the BINARy value, and then stores them into the D word.
2. The lower order byte of the first source word determines the sign of the BINARy value.
3. The sign value is +(H2B), -(H2D).
4. If the sign value is positive, it can be omitted.
5. The D word is stored as Signed.
6. The operation range is -32768(h8000) to 32767(h7FFF).
7. If the S word is not in the valid ASCII(h30 to h39) range, corresponding to 0 to 9, error bit (F34) is SET.




### 3.2.197 String conversion instruction(DDASC2BIN)

String conversion instruction DDASC2BIN S D				Applicable model
OP	DATA type	Available device / Description / Range		
S	WORD	X, Y, M, S, T, C, D, Z, F, UW, integer		
		Device address which saves the Dec ASCII data to be converted as BIN value		
		h30 to h39 per byte except sign bit (h2D, h28)	Error ◎	Zero Carry Borrow Step 5
D	DINT	Y, M, S, T, C, D, Z, F, UW		
		Device address to save converted data		
		-2147483648(h80000000) to 2147483647(hFFFFFFF)		

&lt;Ladder&gt;




- Recognizes the ASCII data stored in S word as decimal number and convert each digit into the BINARY value then stores them into the D word.
- The lower order byte of the first source word determines the sign of the BINARY value.
- The sign value is +(H2B), -(H2D).
- If the sign value is positive, it can be omitted.
- The D word is stored as Signed.
- The operation range is -2147483648 (h80000000) to 2147483647 (h7FFFFFFF).
- If the S word is not in the valid ASCII(h30 to h39) range, corresponding to 0 to 9, error bit (F34) is SET.




### **3.2.198 String conversion instruction(STR2ASC)**

## **<Ladder>**




1. Converts STRING into the ASCII and then stores it sequentially into the D.
  2. It is available to input up to 128 characters.




### 3.2.199 String conversion instruction(DASC2BCD)

String conversion instruction			DASC2BCD	S	D	Applicable model									
OP	DATA type	Available device / Description / Range													
S	WORD	X, Y, M, S, T, C, D, Z, F, UW, integer						Error	Zero	Carry	Borrow				
		Device address which saves the Dec ASCII data to be converted as BCD value													
		h30 to h39 per byte except sign bit (h2D, h28)													
D	WORD	Y, M, S, T, C, D, Z, F, UW													
		Device address to save converted data													
		h0000 to h9999													

&lt;Ladder&gt;




1. Recognizes the ASCII data stored in S word as decimal number and convert it into the BCD code then stores it into the D word.
2. The converted value is stored as Unsigned and the operation range is h0000 to h9999.
3. If the converted result is not in the valid ASCII range(h30 to h39), error flag is SET.




### 3.2.200 String conversion instruction(DDASC2BCD)

String conversion instruction DDASC2BCD S D				Applicable model
OP	DATA type	Available device / Description / Range		
S	WORD	X, Y, M, S, T, C, D, Z, F, UW, integer		LP-S044, LP-S070 Error Zero Carry Borrow Step 5
		Device address which saves the Dec ASCII data to be converted as BCD value		
		Allowable range per byte (h30 to h39)		
D	DWORD	Y, M, S, T, C, D, Z, F, UW		
		Device address to save converted data		
		h00000000 to h99999999		

&lt;Ladder&gt;




1. Recognizes the ASCII data stored in S word as decimal number and convert it into the BCD code, then stores it into the D word one by one.
2. The converted value is stored as Unsigned, and the operation range is 'h00000000 to h99999999'.
3. If the converted result is not in the valid ASCII range (h30 to h39), error flag is SET. (BCD range: 0 to 9)




### 3.2.201 String conversion instruction(BIN2DASC)

String conversion instruction BIN2DASC S D					Applicable model	
OP	DATA type	Available device / Description / Range				
<b>S</b>	WORD	X, Y, M, S, T, C, D, Z, F, UW, integer				
		Device address which saves the data to be converted as ASCII value				
		-32768(h8000) to 32767(h7FFF)				
<b>D</b>	WORD	Y, M, S, T, C, D, Z, F, UW				
		Device address to save converted data				
		h30 to h39 per byte except sign bit (h2D, h28)				
			Error	Zero	Carry	
			Borrow	Step	5	

#### <Ladder>




- Recognizes the BIN data stored in S word as decimal number and converts it into the ASCII code, then stores it sequentially into the D, beginning with D word, by 2 digits per word.
- If the word value of S is negative, the sign value '-(H2D)' will firstly be output on the first byte of D word.
- Executes the Signed operation, and the operation range is -32768(h8000) to 32767(h7FFF).




### 3.2.202 String conversion instruction(DBIN2DASC)

String conversion instruction DBIN2DASC S D				Applicable model		
OP	DATA type	Available device / Description / Range				
S	DINT	X, Y, M, S, T, C, D, Z, F, UW, integer				
		Device address which saves the data to be converted as ASCII value				
		-2147483648(h80000000) to 2147483647(hFFFFFFF)				
D	WORD	Y, M, S, T, C, D, Z, F, UW				
		Device address to save converted data				
		h30 to h39 per byte except sign bit (h2D, h28)				

#### <Ladder>




- Recognizes the BIN data stored in S double word as decimal number and converts it into the ASC II, then stores it into the D word beginning with D, by 2 digits per word.
- If the word value of S is negative, the sign value ‘-(H2D)’ will firstly be output on the first byte of D word.
- Executes the Signed operation, and the operation range is -2147483648 (h80000000) to 2147483647(h7FFFFFFF).




### 3.2.203 Code conversion instruction(GRY2BIN)

Code conversion instruction		GRY2BIN	S	D	Applicable model							
OP	DATA type	Available device / Description / Range										
S	WORD	X, Y, M, S, T, C, D, Z, F, UW, integer					Error	Zero	Carry			
		Device address which saves the GRAY code data to be converted as BIN value										
		0(h0000) to 65535(hFFFF)										
D	WORD	Y, M, S, T, C, D, Z, F, UW					Borrow	Step	5			
		Device address to save converted data										
		0(h0000) to 65535(hFFFF)										

#### <Ladder>




Converts the GRAY code data stored in S word into the BINARY data and stores it into the D.




### 3.2.204 Code conversion instruction(DGRY2BIN)

<b>Code conversion instruction</b> <b>DGRY2BIN</b> <b>S</b> <b>D</b>	<b>Applicable model</b> LP-S044, LP-S070																			
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: left; padding: 2px;">OP</th> <th style="text-align: left; padding: 2px;">DATA type</th> <th style="text-align: left; padding: 2px;">Available device / Description / Range</th> </tr> </thead> <tbody> <tr> <td style="text-align: center; padding: 2px;"><b>S</b></td> <td style="text-align: center; padding: 2px;">DWORD</td> <td style="padding: 2px;"> X, Y, M, S, T, C, D, Z, F, UW, integer  Device address which saves the GRAY code data to be converted as BIN value  0(h00000000) to 4294967295(hFFFFFFF) </td></tr> <tr> <td style="text-align: center; padding: 2px;"><b>D</b></td> <td style="text-align: center; padding: 2px;">DWORD</td> <td style="padding: 2px;"> Y, M, S, T, C, D, Z, F, UW  Device address to save converted data  0(h00000000) to 4294967295(hFFFFFFF) </td></tr> </tbody> </table>	OP	DATA type	Available device / Description / Range	<b>S</b>	DWORD	X, Y, M, S, T, C, D, Z, F, UW, integer Device address which saves the GRAY code data to be converted as BIN value 0(h00000000) to 4294967295(hFFFFFFF)	<b>D</b>	DWORD	Y, M, S, T, C, D, Z, F, UW Device address to save converted data 0(h00000000) to 4294967295(hFFFFFFF)	<table border="1" style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td style="text-align: center; padding: 2px;">Error</td> <td style="text-align: center; padding: 2px;">Zero</td> <td style="text-align: center; padding: 2px;">Carry</td> <td style="text-align: center; padding: 2px;">Borrow</td> <td style="text-align: center; padding: 2px;">Step</td> </tr> <tr> <td style="text-align: center; padding: 2px;"></td> <td style="text-align: center; padding: 2px;">5</td> </tr> </table>	Error	Zero	Carry	Borrow	Step					5
OP	DATA type	Available device / Description / Range																		
<b>S</b>	DWORD	X, Y, M, S, T, C, D, Z, F, UW, integer Device address which saves the GRAY code data to be converted as BIN value 0(h00000000) to 4294967295(hFFFFFFF)																		
<b>D</b>	DWORD	Y, M, S, T, C, D, Z, F, UW Device address to save converted data 0(h00000000) to 4294967295(hFFFFFFF)																		
Error	Zero	Carry	Borrow	Step																
				5																

#### <Ladder>




Converts the GRAY code data stored in S double word into the BINARY data and stores it into the D double word.




### 3.2.205 Code conversion instruction(BIN2GRY)

Code conversion instruction		BIN2GRY	S	D	Applicable model							
OP	DATA type	Available device / Description / Range										
S	WORD	X, Y, M, S, T, C, D, Z, F, UW, integer					Error	Zero	Carry			
		Device address which saves the data to be converted as GRAY code value										
		0(h0000) to 65535(hFFFF)										
D	WORD	Y, M, S, T, C, D, Z, F, UW					Borrow	Step	5			
		Device address to save converted data										
		0(h0000) to 65535(hFFFF)										

#### <Ladder>




Converts the BINARY code data stored in S word into the GRAY code data and then stores it into the D word.




### 3.2.206 Code conversion instruction(DBIN2GRY)

<b>Code conversion instruction</b> <b>DBIN2GRY S D</b>	<b>Applicable model</b> LP-S044, LP-S070																			
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: left;">OP</th> <th style="text-align: left;">DATA type</th> <th style="text-align: left;">Available device / Description / Range</th> <th style="text-align: right;"></th> </tr> </thead> <tbody> <tr> <td rowspan="3" style="text-align: center;"><b>S</b></td> <td rowspan="3" style="text-align: center;">DWORD</td> <td>X, Y, M, S, T, C, D, Z, F, UM, integer</td> <td style="text-align: right; vertical-align: bottom;">           Error  </td> </tr> <tr> <td>Device address which saves the data to be converted as GRAY code value</td> <td style="text-align: right; vertical-align: bottom;">           Zero  </td> </tr> <tr> <td>0(h00000000) to 4294967295(hFFFFFFF)</td> <td style="text-align: right; vertical-align: bottom;">           Carry  </td> </tr> <tr> <td rowspan="3" style="text-align: center;"><b>D</b></td> <td rowspan="3" style="text-align: center;">DWORD</td> <td>Y, M, S, T, C, D, Z, F, UW</td> <td style="text-align: right; vertical-align: bottom;">           Borrow  </td> </tr> <tr> <td>Device address to save converted data</td> <td style="text-align: right; vertical-align: bottom;">           Step  </td> </tr> <tr> <td>0(h00000000) to 4294967295(hFFFFFFF)</td> <td style="text-align: right; vertical-align: bottom;">           5  </td> </tr> </tbody> </table>	OP	DATA type	Available device / Description / Range		<b>S</b>	DWORD	X, Y, M, S, T, C, D, Z, F, UM, integer	Error 	Device address which saves the data to be converted as GRAY code value	Zero 	0(h00000000) to 4294967295(hFFFFFFF)	Carry 	<b>D</b>	DWORD	Y, M, S, T, C, D, Z, F, UW	Borrow 	Device address to save converted data	Step 	0(h00000000) to 4294967295(hFFFFFFF)	5 
OP	DATA type	Available device / Description / Range																		
<b>S</b>	DWORD	X, Y, M, S, T, C, D, Z, F, UM, integer	Error 																	
		Device address which saves the data to be converted as GRAY code value	Zero 																	
		0(h00000000) to 4294967295(hFFFFFFF)	Carry 																	
<b>D</b>	DWORD	Y, M, S, T, C, D, Z, F, UW	Borrow 																	
		Device address to save converted data	Step 																	
		0(h00000000) to 4294967295(hFFFFFFF)	5 																	

&lt;Ladder&gt;



Converts the BINARY code data stored in S double word into the GRAY code data and then stores it into the D double word.




### 3.2.207 Sign reversal instruction(NEG)

<b>Sign reversal instruction</b>	<b>NEG</b>	<b>D</b>	Applicable model LP-S044, LP-S070
<b>OP</b>	<b>DATA type</b>	<b>Available device / Description / Range</b>	

D WORD Y, M, S, T, C, D, Z, F, UW  
 Device address to convert sign  
 0(h0000) to 65535(hFFFF)

Error	Zero	Carry	Borrow	Step
				3

&lt;Ladder&gt;




Reverses the sign of D word.




### 3.2.208 Sign reversal instruction(DNEG)

Sign reversal instruction		DNEG	D	Applicable model LP-S044, LP-S070					
OP	DATA type	Available device / Description / Range			Error	Zero	Carry	Borrow	Step
D	DWORD	Y, M, S, T, C, D, Z, F, UW			Error	Zero	Carry	Borrow	Step
		Device address to convert sign							
		0(h00000000) to 4294967295(hFFFFFFF)							3

&lt;Ladder&gt;




Reverses the sign of D double word.




### 3.2.209 Data conversion instruction(DECO)

Data conversion Instruction			DECO	S	D	N	Applicable model					
OP	DATA type	Available device / Description / Range						Error	Zero	Carry	Borrow	Step
<b>S</b>	WORD	X, Y, M, S, T, C, D, Z, F, UW										7
		Data address to execute the decoder operation										
		0(h0000) to 65535(hFFFF)										
<b>D</b>	WORD	Y, M, S, T, C, D, Z, F, UW										7
		Address to save the operation result										
		0(h0000) to 65535(hFFFF)										
<b>N</b>	WORD	X, Y, M, S, T, C, D, Z, F, UW, integer										7
		The number of bits to be decoded										
		0 to 8										

#### <Ladder>




- Decodes the number of B bits stored in S word from 0 to N and stores the result into the D word.
- If the N is 0, it does not execute the instruction.
- If the decoded value is not in the range from 0 to 8, error flag is SET.




### 3.2.210 Data conversion instruction(ENCO)

Data conversion instruction ENCO S D N				Applicable model		
OP	DATA type	Available device / Description / Range				
S	WORD	X, Y, M, S, T, C, D, Z, F, UW				
		Data address to execute the encoder operation				
		0(h0000) to 65535(hFFFF)				
D	WORD	Y, M, S, T, C, D, Z, F, UW				
		Address to save the operation result				
		0(h0000) to 65535(hFFFF)				
N	WORD	X, Y, M, S, T, C, D, Z, F, UW, integer				
		The number of words to be encoded				
		0 to 8				

&lt;Ladder&gt;




1. Encodes the number of N words from S to N and stores them into the D.
2. If the N is not in the range from 0 to 8, error flag is SET.
3. If the encoded value is 0, zero flag is SET.
4. If N is 0, it does not execute the instruction.




### 3.2.211 Data conversion instruction(EXT)

Data conversion instruction	EXT	D	Applicable model
D	INT	Y, M, S, D, UW Data address to execute the operation -32768(h8000) to 32767(h7FFF)	LP-S044, LP-S070 Error Zero Carry Borrow Step 3

#### <Ladder>




1. Extends the value of D word to 32bit.
2. Executes the Signed operation.



### 3.2.212 Refresh instruction(REF)

Refresh instruction		REF	D	N	Applicable model LP-S044, LP-S070				
OP	DATA type	Available device / Description / Range			Error	Zero	Carry	Borrow	Step
D	BIT	X, Y							
		Input/Output bit device							
		Not applicable							5
N	WORD	X, Y, M, S, T, C, D, Z, F, UW, integer							
		The number of bit devices to refresh from D bit							
		0 to 65535							

#### <Ladder>




Refreshes the number of N bit devices beginning with I/O D bit device.

### 3.2.213 Display instruction(SEG)

Display instruction		SEG	S	D	N	Applicable model										
OP	DATA type	Available device / Description / Range					Error	Zero	Carry	Borrow	Step					
S	BIT	X, Y, M, UB					Error	Zero	Carry	Borrow	Step 7					
		Address which saves the data to be decoded as 7 segment														
		Not applicable														
D	BIT	Y, M, UB					Error	Zero	Carry	Borrow	Step 7					
		Address to save the decoded data														
		Not applicable														
N	WORD	X, Y, M, S, T, C, D, Z, F, UW, integer\					Error	Zero	Carry	Borrow	Step 7					
		The number of data to be decoded														


#### <Ladder>



Decodes the number of N data composed of 4 bit per each to the 7 segment data, one by one, and stores it as the number of N data composed of 8 bit per each.

[Segment structure]											
4 input bit		Segment structure		DECODE							Segment display
Hex.	Bit	a	b	h	g	f	e	d	c	b	a
0	0000			0	0	1	1	1	1	1	0
1	0001			0	0	0	0	0	1	1	1
2	0010			0	1	0	1	1	0	1	1
3	0011			0	1	0	0	1	1	1	1
4	0100			0	1	1	0	0	1	1	0
5	0101			0	1	1	0	1	1	0	1
6	0110			0	1	1	1	1	1	0	1
7	0111			0	0	1	0	0	1	1	1
8	1000			0	1	1	1	1	1	1	1
9	1001			0	1	1	0	0	1	1	1
A	1010			0	1	1	1	0	1	1	1
B	1011			0	1	1	1	1	1	0	0
C	1100			0	0	1	1	1	0	0	1
D	1101			0	1	0	1	1	1	1	0
E	1110			0	1	1	1	1	0	0	1
F	1111			0	1	1	1	0	0	0	1

Segment data decode →



[The structure when connecting AUTONICS display unit]

Display		Negative logic input						Positive logic input						
Hex.	Dec.	S+3BIT	S+2BIT	S+1BIT	S BIT	BI	LATCH	S+3BIT	S+2BIT	S+1BIT	S BIT	BI	LATCH	
Zero	Zero	1	1	1	1	1	1	0	0	0	0	0	1	0
Blank	Blank													
0	0	1	1	1	1	0	1	0	0	0	0	0	0	0
1	1	1	1	1	0	x	1	0	0	0	0	1	x	0
2	2	1	1	0	1	x	1	0	0	0	1	0	x	0
3	3	1	1	0	0	x	1	0	0	0	1	1	x	0
4	4	1	0	1	1	x	1	0	1	0	0	0	x	0
5	5	1	0	1	0	x	1	0	1	0	1	0	x	0
6	6	1	0	0	1	x	1	0	1	1	1	0	x	0
7	7	1	0	0	0	x	1	0	1	1	1	1	x	0
8	8	0	1	1	1	x	1	1	0	0	0	0	x	0
9	9	0	1	1	0	x	1	1	0	0	0	1	x	0
A	Blank	0	1	0	1	x	1	1	0	1	0	0	x	0
B	Blank	0	1	0	0	x	1	1	0	1	1	0	x	0
C	Blank	0	0	1	1	x	1	1	1	0	0	0	x	0
D	Blank	0	0	1	0	x	1	1	1	0	1	0	x	0
E	Blank	0	0	0	1	x	1	1	1	1	0	0	x	0
F	Blank	0	0	0	0	x	1	1	1	1	1	1	x	0
HOLD		x	x	x	x	x	0	x	x	x	x	x	H	

"X" : It does not matter whether you input HIGH or LOW level signal.

Blank: It does not display anything even if you input the signal by using input data.


If you connect BI terminal to the VCC(HIGH level)D, it executes the Zero blanking, and if you connect BI terminal to the GND(LOW level) terminal, it displays 0.

\*AUTONICS display unit has embedded DECODER DRIVER, therefore you can use S bit without D(Destination) bit.

### 3.2.214 Clock instruction(TCMP)

Clock instruction		TCMP	S1	S2	S3	S4	D	Applicable model					
OP	DATA type	Available device / Description / Range							Error	Zero	Carry	Borrow	Step
S1	WORD	X, Y, M, S, T, C, D, Z, F, UW, integer						<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	7	
		Device address which saves the data to be compared with 'hour' data of S4											
		0(h0000) to 23(h0017)											
S2	WORD	X, Y, M, S, T, C, D, Z, F, UW, integer						<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	7	
		Device address which saves the data to be compared with 'minute' data of S4											
		0(h0000) to 59(h0038)											
S3	WORD	X, Y, M, S, T, C, D, Z, F, UW, integer						<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	7	
		Device address which saves the data to be compared with 'second' data of S4											
		0(h0000) to 59(h0038)											
S4	WORD	X, Y, M, S, T, C, D, Z, F, UW						<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	7	
		Device address which saves the data to be compared with the data of S1, S2 and S3.											
		Time data range											
D	BIT	Y, M, S, T, C, Z, F, UB						<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	7	
		Bit device address to save the comparision result											
		Not applicable											

#### <Ladder>




Compares a data composed of S1(hour), S2(minute), and S3(second) with a data composed of S4 to S4+2 word, andas a result;

1. If the two values are equal, D bit turns ON.
2. If S4 is less than the former, D+1 bit turns ON.
3. If S4 is larger than the former, D+2 bit turns ON.
4. If S4 value is read as TRD instruction and available.
5. If the input value is not time data (hour:0 to 23, minute:0 to 59, second:0 to 59) error flag is SET.


### 3.2.215 Clock instruction(TADD)

Clock instruction		TADD	S1	S2	D	Applicable model LP-S044, LP-S070										
OP	DATA type	Available device / Description / Range														
S1	WORD	X, Y, M, S, T, C, D, Z, F, UW														
		Device address which saves the data to execute the time addition operation with S2														
		Time data range														
S2	WORD	X, Y, M, S, T, C, D, Z, F, UW														
		Device address which saves the data to execute the time addition operation with S1														
		Time data range														
D	WORD	Y, M, S, T, C, D, Z, F, UW														
		Address to save the operation result														
		Time data range														

#### <Ladder>




1. Executes the addition operation for each word of S1 device, in which S1(hour), S1+1(minute), or S1+2(second), is stored, and the corresponding word of S2 device, in which S2(hour), S2+1(minute), or S2+2(second) is stored, and store the result into the designated word of D device respectively.
2. If the time exceeds 24 o'clock, carry flag occurs and the data is stored from 0 again.
3. If the input value is not time data (hour:0 to 23, minute:0 to 59, second:0 to 59) error flag is SET.  
(Note) Recognizes and displays the data as binary value.




### 3.2.216 Clock instruction(TSUB)

Clock instruction		TSUB	S1	S2	D	Applicable model										
OP	DATA type	Available device / Description / Range					Error	Zero	Carry	Borrow	Step					
S1	WORD	X, Y, M, S, T, C, D, Z, F, UW					<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	7					
		Device address which saves the data to execute the time subtraction operation with S2														
		Time data range														
S2	WORD	X, Y, M, S, T, C, D, Z, F, UW					<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	7					
		Device address which saves the data to execute the time subtraction operation with S1														
		Time data range														
D	WORD	Y, M, S, T, C, D, Z, F, UW					<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	7					
		Address to save the operation result														
		Time data range														

#### <Ladder>




1. Executes the subtraction operation for each word of S1 device, in which S1(hour)/S1+1(minute)/S1+2(second) is stored, and the corresponding word of S2 in which S2(hour), S2+1(minute) or S2+2(second) is stored, and then stores the result into the designated word of D device.
2. If the time is less than 0 o'clock, borrow flag occurs and stores the result after converting into 24-hour data.
3. If the input value is not time data (hour:0 to 23, minute:0 to 59, second:0 to 59) error flag is SET.  
(Note) Recognizes and displays the data as binary value.



### 3.2.217 Clock instruction(TRD)


Clock instruction	TRD	D	Applicable model
OP	DATA type	Available device / Description / Range	
		Y, M, S, T, C, D, Z, F, UW	
<b>D</b>	WORD	Device address to save the real time value	Error
		Not applicable	Zero
			Carry
			Borrow
			Step
			3

&lt;Ladder&gt;



The real time value is stored as below.


1. Year in D word
2. Month in D+1 word
3. Date in D+2 word
4. Hour in D+3 word
5. Minute in D+4 word
6. Second in D+5 word
7. Day of week in D+6 word




### 3.2.218 Clock instruction(TWR)

Clock instruction TWR D			Applicable model LP-S044, LP-S070				
OP	DATA type	Available device / Description / Range	Error	Zero	Carry	Borrow	Step
D	WORD	Y, M, S, T, C, D, Z, F, UW Device address which saves the time data to write on special register Time data range					3

&lt;Ladder&gt;




1. Year in D word
2. Month in D+1 word (1 to 12)
3. Date in D+2 word (1 to 31)
4. Hour in D+3 word (1 to 23)
5. Minute in D+4 word (1 to 59)
6. Second in D+5 word (1 to 59)
7. Day of week in D+6 word (0-sunday to 6-saturday) are stored respectively.
8. Stores the time value into the corresponding position of special register.
9. The special register (time setting) is also been running along with executing TWR instruction.
10. If the input data is out of the valid time range, error flag occurs.




### 3.2.219 Clock instruction(HOUR)

Clock instruction		HOUR	S	D1	D2	Applicable model LP-S044, LP-S070											
OP	DATA type	Available device / Description / Range						Error	Zero	Carry	Borrow	Step					
S	WORD	X, Y, M, S, T, C, D, Z, F, UW, integer			Data device address to designate the accumulated time			Error	Zero	Carry	Borrow	Step 7					
		0(h0000) to 65535(hFFFF)															
		Y, M, S, T, C, D, Z, F, UW			Data device address which saves the executed time value												
D1	WORD	0(h0000) to 65535(hFFFF)															
		Y, M, UB			The compared result between the executed time (D1) and the designated accumulated time(S)												
		Not applicable															

#### <Ladder>




1. If the input contact retains ON status for the designated time (time unit) in S word device, D2 bit turns ON.
2. The ON time value in D1 word device
3. The current value of less than 1 hour is displayed in D1+1 word device at per one second.



### 3.2.220 Clock instruction(TZCP)


Clock instruction	TZCP	S1	S2	S3	D	Applicable model
OP	DATA type	Available device / Description / Range				
S1	WORD	X, Y, M, S, T, C, D, Z, F, UW				Error
		Device address which saves the data to compare with S2 and S3 data				Zero
		Time data range				Carry
S2	WORD	X, Y, M, S, T, C, D, Z, F, UW				Borrow
		Device address which saves the data to compare with S1 and S3 data				Step
		Time data range				9
S3	WORD	X, Y, M, S, T, C, D, Z, F, UW				
		Device address which saves the data to compare with S1 and S2 data				
		Time data range				
D	BIT	Y, M, S, T, C, Z, F, UB				
		Bit device address to save comparision result				
		Not applicable				

#### <Ladder>



Hour in S1 word, minute in S1+1 word, second in S1+2 word,  
 hour in S2 word, minute in S2+1 word, second in S2+2 word,  
 hour in S3 word, minute in S3+1 word, second in S3+2 word,  
 are stored respectively and compares the S3 device value between S1 device and S2 device. As a result:


1. If S3 value is less than S1 and S2 value, D bit turns ON.
2. If S3 value is equal to the smaller value of S1 or S2, D+1 bit turns ON.
3. If S3 value is between the values of S1 value and S2 value, D+2 bit turns ON.
4. If S3 value is equal to the bigger value of S1 or S2, D+3 bit turns ON.
5. If S3 value is larger than S1 value and S2 value, D+4 bit turns ON.
6. If the source data is out of the time range (hour: 0 to 23, min: 0 to 59, sec: 0 to 59), error flag occurs.




### 3.2.221 Motion instruction(MTVDM)

Motion instruction	MTVDM	S	S1	S2	S3	S4	S5	Applicable model
<b>OP</b>	<b>DATA type</b>	<b>Available device / Description / Range</b>						LP-S070
<b>S</b>	WORD	X, M, D, Z, UW, integer Channel(Ch1, Ch2) 1 to 2						Error Zero Carry Borrow Step 9
<b>S1</b>	BIT	X, M, Z, UB Motion drive direction 1: Forward, 0: Backword						
<b>S2</b>	DWORD	X, M, D, Z, UW, integer Drive speed 0 to 100,000						
<b>S3</b>	WORD	X, M, D, Z, UW, integer Dwell time 0 to 65536ms						
<b>S4</b>	WORD	X, M, D, Z, UW, integer Acceleration time Select acceleration time 1 to 5 in common configuration						
<b>S5</b>	WORD	X, M, D, Z, UW, integer Deceleration time Select deceleration time 1 to 5 in common configuration						

#### <Ladder>



Speed direct drive instruction: You can designate direct drive data(drive speed, drive direction, etc) directly and it executes speed drive.



#### [Note]


1. For utilize direct instruction, set 'TRUE' at 'Enable Ch' of common configuration from [Parameter]-[MOTION]tab in SmartStudio.
2. Select accel/deceleration time 1 to 5 in common configuration from [Parameter]-[MOTION]tab in SmartStudio.
3. You should check whether the correspond channel is using or not before using direct drive instruction.
4. If using channel is input the other instruction, using channel error occurs.

※ For more information, refer to Motion of SmartStudio user manual.


### 3.2.222 Motion instruction(MTPDM)

Motion instruction	MTPDM	S	S1	S2	S3	S4	S5	Applicable model
<b>OP</b>	<b>DATA type</b>	<b>Available device / Description / Range</b>						LP-S070
<b>S</b>	WORD	X, M, D, Z, UW, integer Channel (Ch1, Ch2) 1 to 256						Error Zero Carry Borrow Step 9
<b>S1</b>	DWORD	X, M, D, Z, UW, integer Target position -2,147,483,648 to 2,147,483,647 (Enable to set the range)						
<b>S2</b>	DWORD	X, M, D, Z, UW, integer Drive speed 0 to 100,000						
<b>S3</b>	WORD	X, M, D, Z, UW, integer Dwell time 0 to 65536ms						
<b>S4</b>	WORD	X, M, D, Z, UW, integer Acceleration time Select acceleration time 1 to 5 in common configuration						
<b>S5</b>	WORD	X, M, D, Z, UW, integer Deceleration time Select deceleration time 1 to 5 in common configuration						

#### <Ladder>



Position direct drive instruction: You can designate direct drive data(drive speed, drive direction, etc) directly and it executes position drive.



#### [Note]


1. For utilize direct instruction, set 'TRUE' at 'Enable Ch' of common configuration from [Parameter]-[MOTION]tab in SmartStudio.
2. Select accel/deceleration time 1 to 5 in common configuration from [Parameter]-[MOTION]tab in SmartStudio.
3. You should check whether the correspond channel is using or not before using direct drive instruction.
4. If using channel is input the other instruction, using channel error occurs.

※ For more information, refer to Motion of SmartStudio user manual.

### 3.2.223 Motion instruction(MTIDM)

Motion instruction	MTIDM	S	S1	Applicable model	
OP	DATA type	Available device / Description / Range		LP-S070	
<b>S</b>	WORD	X, M, D, Z, UW, integer			
		Channel(Ch1, Ch2)			
		1 to 2			
<b>S1</b>	WORD	X, M, D, Z, UW, integer			
		Step number			
		1 to 99			

#### <Ladder>



Indirect designate drive instruction: It operates with the number of scripted string in the specified pattern from pattern list.

#### [Note]

1. For utilize indirect drive instruction, set 'TRUE' at 'Enable Ch' of common configuration from [Parameter]-[MOTION]tab in SmartStudio.
2. There should be pattern number to execute of pattern list from [Parameter]-[MOTION]tab in SmartStudio.
3. You should check whether the correspond channel is using or not before using drive instruction.

#### [Pattern stop method]

##### 1) F400 or F402 (Action list stop) + MTSRS

: During pattern drive, if currently executed action list type is speed drive and this instruction is executed, speed drive is finish and it executes the next action list.

##### 2) F401 or F403 (Group stop) + MTSRS

: During group drive, this instruction is executed, it escapes the group and executes the other action list following the group.

##### 3) Not to set special flag


: Pattern drive is finish.

※ For more information, refer to Motion of SmartStudio user manual.

### 3.2.224 Motion instruction(MTMEC)

Motion instruction MTMEC S			Applicable model LP-S070				
OP	DATA type	Available device / Description / Range	Error	Zero	Carry	Borrow	Step
S	WORD	X, M, D, Z, UW, integer					
		Channel(Ch1, Ch2)					
		1 to 2	(◎)				5

#### <Ladder>




Error remove instruction: This instruction removes the error when error flag occurs by error during motion drive.

※ For more information, refer to Motion of SmartStudio user manual.

### 3.2.225 Motion instruction(MTEMS)

Motion instruction	MTEMS	S	Applicable model
OP	DATA type	Available device / Description / Range	
S	WORD	X, M, D, Z, UW, integer Channel(Ch1, Ch2) 1 to 2	Error Zero Carry Borrow Step 5

#### <Ladder>



Emergency stop instruction: If there is emergency during motion position driving, you can stop all motion actions by emergency stop instruction.

#### [Note]


When executing emergency stop instruction, all currently executing motion instructions stop.

\* For more information, refer to Motion of SmartStudio user manual.

### 3.2.226 Motion instruction(MTCPP)

Motion instruction MTCPP S S1			Applicable model LP-S070				
OP	DATA type	Available device / Description / Range	Error	Zero	Carry	Borrow	Step
S	WORD	X, M, D, Z, UW, integer					
		Channel(Ch1, Ch2)					
		1 to 2					5
S1	DWORD	X, M, D, Z, UW, integer					
		Setting value of new position					
		-2,147,483,648 to 2,147,483,647					

#### <Ladder>



Current position preset instruction: This motion instruction is for re-set the current position.

#### [Note]


During motion driving, if this instruction is executed, error occurs.

\* For more information, refer to Motion of SmartStudio user manual.

### 3.2.227 Motion instruction(MTFOS)

Motion instruction	MTFOS	S	Applicable model
OP	DATA type	Available device / Description / Range	
<b>S</b>	WORD	X, M, D, Z, UW, integer Channel(Ch1, Ch2) 1 to 2	Error Zero Carry Borrow Step 5

#### <Ladder>




Forced home setting instruction: This instruction sets the specified position as the set home position value in SmartStudio.

\* For more information, refer to Motion of SmartStudio user manual.

### 3.2.228 Motion instruction(MTSRS)

Motion instruction MTSRS S			Applicable model
OP	DATA type	Available device / Description / Range	LP-S070
S	WORD	X, M, D, Z, UW, integer	Error
		Channel(Ch1, Ch2)	Zero
		1 to 2	Carry
			Borrow
			Step
			5

#### <Ladder>



Normal stop instruction: It executes normal stop instruction to the currently motion driving channel.

#### [Pattern stop method with combining special flag]

##### 1. F400 or F402 (Action list stop) + MTSRS

: During pattern drive, if currently executed action list type is speed drive and this instruction is executed, speed drive is finish and it executes the next action list.

##### 2. F401 or F403 (Group stop) + MTSRS

: During group drive, this instruction is executed, it escapes the group and executes the other action list following the group.

##### 3. Not to set special flag

: Pattern drive is finish.

##### 4. MTSRS during linear interpolation drive

: Two axies decelerately stop at the same time.

\* For more information, refer to Motion of SmartStudio user manual.

### 3.2.229 Motion instruction(MTOBC)

Motion instruction MTOBC S			Applicable model	
OP	DATA type	Available device / Description / Range		
S	WORD	X, M, D, Z, UW, integer	Error	
		Channel(Ch1, Ch2)	Zero	
		1 to 2	Carry	
			Borrow	
			Step 5	

#### <Ladder>







Origin back instruction: During motion position drive, if you want to return to origin, it goes back to the preset origin point.

LP-S070 has two methods for returning the origin.

- H/W origin back: It is the origin back method by home search direction, upper/lower H/W limit, and home sensing which are set in SmartStudio.
- S/W origin back: It is the origin back method to move directly to the known origin by S/W.

#### [Origin back type by home search direction during H/W origin back]






The position of the origin point is set in SmartStudio.

※ For more information, refer to Motion of SmartStudio user manual.


### 3.2.230 Motion instruction(MTOVV)

Motion instruction MTOVV S S1			Applicable model LP-S070
OP	DATA type	Available device / Description / Range	
<b>S</b>	WORD	X, M, D, Z, UW, integer	
		Channel(Ch1, Ch2)	
		1 to 2	
<b>S1</b>	DWORD	X, M, D, Z, UW, integer	
		Drive speed	
		0 to 100kpps	

#### <Ladder>



Speed override: It converts the currently operating speed set (unit set) to the other speed and operates with the converted speed.



- Operating speed  $>>$  Chaged speed: It converts to changed speed and operates with the changed speed.
- Operating speed  $\leq$  Changed speed: It converts to changed speed and operates with the changed speed.
- Changed speed  $<$  Initial speed: When changing speed to the slower than initial speed, it operates constant speed drive without accel/deceleration.

#### [Note]


- If the currently not operated channel is executed this instruction, position/speed override change error occurs.
- If the currently operated channel is executed the other instruction, enable channel error occurs.
- Be sure that rapid speed changing may cause the pull-out of motor.

\* For more information, refer to Motion of SmartStudio user manual.


### 3.2.231 Motion instruction(MTOVP)

Motion instruction MTOVP S S1				Applicable model LP-S070	
OP	DATA type	Available device / Description / Range			
S	WORD	X, M, D, Z, UW, integer			
		Channel(Ch1, Ch2)			
		1 to 2			
S1	WORD	X, M, D, Z, UW, integer		Error	
		Changed position		Zero	
		-2147483647 to 2147483647		Carry	
			Borrow	Step	
				5	

#### <Ladder>



Position override:.. It changes the set target position to the designated position by the instruction.



1. Current position ≥ Changed position: It stops with deceleration.
2. Current position << Changed position: It stops with deceleration at the changed position.

#### [Note]


1. If the currently not operated channel is executed this instruction, position/speed override change error occurs.
2. If the currently operated channel is executed the other instruction, enable channel error occurs.

\* For more information, refer to Motion of SmartStudio user manual.


### 3.2.232 Motion instruction(MTIPT)

Motion instruction	MTIPT	S	S1	S4	S4	Applicable model
<b>OP</b>	<b>DATA type</b>	<b>Available device / Description / Range</b>				
<b>S</b>	WORD	Integer				LP-S070 Error Zero Carry Borrow Step 7
		Channel number of the first axis(Ch1, Ch2)				
		1 to 2				
<b>S1</b>	WORD	X, M, D, Z, UW, integer				
		Action number of the first axis(it is not pattern number)				
		0 to 65535				
<b>S3</b>	WORD	Integer				
		Channel number of the second axis (Ch0, Ch1)				
		1 to 2				
<b>S4</b>	WORD	X, M, D, Z, UW, integer				
		Action number of the second axis(it is not pattern number)				
		0 to 65535				

#### <Ladder>



Line interpolation instruction: It executes line interpolation drive with two axes.



#### [Note]


- The action list designated as speed drive is not available as the axis between line interpolation.
- The axis which is more distance than the other is set as main axis.
- Drive data of sub axis is decided by the calculating from the drive data of main axis.
- If each distance of two axes is same, CH1 becomes main axis.

\* For more information, refer to Motion of SmartStudio user manual.

### 3.2.233 Motion instruction(MTUAI)

Motion instruction MTUAI S S1				Applicable model LP-S070
OP	DATA type	Available device / Description / Range		
S	WORD	X, M, D, Z, UW, integer		
		Channel(Ch1, Ch2)		
		1 to 2		Error Zero Carry Borrow Step 5
S1	WORD	X, M, D, Z, UW, integer		
		Step number		
		1 to 99		

#### <Ladder>



Action item drive instruction

: It operates one action of motion referring the number of action item.

#### [Note]

1. For utilize indirect drive instruction, set 'TRUE' at 'Enable Ch' of common configuration from [Parameter]-[MOTION]tab in SmartStudio.
  2. There should be pattern number to execute of pattern list from [Parameter]-[MOTION]tab in SmartStudio.
  3. If the currently operated channel is executed the other instruction, enable channel error occurs..
- \* For more information, refer to Motion of SmartStudio user manual.



# Autonics

Sensors & Controllers

## Distributor

[www.autonics.com](http://www.autonics.com)

### ■ Major Products

- Photoelectric Sensors-Fiber Optic Sensors-Door Sensors-Door Side Sensors-Area Sensors
- Proximity Sensors-Pressure Sensors-Connectors/Sockets-Rotary Encoders-Panel Meters
- Counters-Timers-Temperature Controllers-SSRs/Power Controllers-Sensor Controllers
- Graphic/Logic Panels-Temperature/Humidity Transducers-Switching Mode Power Supplies
- Stepper Motors/Drivers/Motion Controllers-I/O Terminal Blocks & Cables-Display Units
- Control Switches/Lamps/Buzzers-Field Network Devices-Tachometer/Pulse(Rate) Meters
- Laser Marking System(Fiber, CO<sub>2</sub>, Nd:YAG)-Laser Welding/Cutting System

■ Any proposal for a product improvement and development: [Product@autonics.com](mailto:Product@autonics.com)

Dimensions or specifications on this manual are subject to change and  
some models may be discontinued without notice.

### ■ Corporate Headquarters

18, Bansong-ro 513 Beon-gil, Haewundae-gu, Busan, South Korea 48002

### ■ Brazil - Autonics do Brasil Comercial Importadora e Exportadora LTDA

Tel: 55-11-2307-8480 / 3195-4610 / Fax: 55-11-2309-7784 / E-mail: [comercial@autonics.com.br](mailto:comercial@autonics.com.br)

### ■ China - Autonics electronic(Jiaxing) Corporation

Tel: 86-21-5422-5969 / Fax: 86-21-5422-5961 / E-mail: [china@autonics.com](mailto:china@autonics.com)

### ■ India - Autonics Automation India Private Limited

Tel: 91-22-2768-2570 / E-mail: [india@autonics.com](mailto:india@autonics.com)

### ■ Indonesia - PT. Autonics Indonesia

Tel: 62-21-8088-8814/5 / Fax: 62-21-8088-4442/0 / E-mail: [indonesia@autonics.com](mailto:indonesia@autonics.com)

### ■ Iran - Autonics Corp. Iran Representative Office

Tel: 98-21-8872-7251/2 / Fax: 98-21-8872-8556 / E-mail: [iran@autonics.com](mailto:iran@autonics.com)

### ■ Japan - Autonics Japan Corporation

Tel: 81-3-6435-8380 / Fax: 81-3-6435-8381 / E-mail: [ja@autonics.com](mailto:ja@autonics.com)

### ■ Malaysia - Mal-Autonics Sensor Sdn. Bhd.

Tel: 60-3-7805-7190 / Fax: 60-3-7805-7193 / E-mail: [malaysia@autonics.com](mailto:malaysia@autonics.com)

### ■ Mexico - Autonics Mexico S.A. DE C.V.

Tel: 52-55-5207-0019 / Fax : 52-55-1663-0712 / E-mail: [ventas@autonics.com.mx](mailto:ventas@autonics.com.mx)

### ■ Russia - Autonics Rus LLC

Tel/Fax : 7-495-660-10-88 / E-mail: [russia@autonics.com](mailto:russia@autonics.com)

### ■ Turkey - Autonics Otomasyon Ticaret Ltd. Sti.

Tel: 90-216-365-9117/3/4 / Fax: 90-216-365-9112 / E-mail: [turkey@autonics.com](mailto:turkey@autonics.com)

### ■ USA - Autonics USA, Inc.

Tel: 1-847-680-8160 / Fax: 1-847-680-8155 / E-mail: [sales@autonicsusa.net](mailto:sales@autonicsusa.net)

### ■ Vietnam - Cong Ty Tnhh Autonics Vina

Tel: 84-28-3771-2662 / Fax: 84-28-3771-2663 / E-mail: [vietnam@autonics.com](mailto:vietnam@autonics.com)