



### Working Conditions

Working Environment	-25°C ~ + 60°C	Installation Type	III Class
Class Of Pollution	3 <sup>rd</sup> Class	Maximum Installing Height	≤ 2000m
Anti-Vibration	10 ~ 2000Hz · 1mm · 15g	Relative Air Humidity	≤ 98%
Protection Level	IP65 Products with the mark "TH" can work normally under the environment of moist and tropical zone		

### Main Technical Indexes

Rated Insulation Voltage: AC600V      Conventional Thermal Current: 10A  
 Power Frequency Voltage Withstand :2500V/min      Use Type:AC-15, DC-13


Use Category	Rated Insulation Voltage U <sub>IV</sub>	Rated Working Voltage U <sub>eV</sub>	Rated Working Current I <sub>eA</sub>	Conventional Thermal Current I <sub>thA</sub>
AC-15	600	220 380	6 4	10
DC-13	600	110 220	1 0.6	10

### Machi Life

Structure Type	Machine Life (Ten Thousand Times)	Operation Frequency (Times/Hour)
standard, Mushroom Type, Illuminated	100	1200
Knob Type, Key Type, Self-Locking	30	120

### Electrical Endurance

Use Type	Electrical Endurance (Ten Thousand Times)	Operation Frequency (Times/Hour)
AC-15	60	1200
DC-13	25	1200

<p>Potentiometer</p> 		<p>1K <b>LA42DWQ1K</b> 10K <b>LA42DWQ10K</b></p>		
--------------------------------------------------------------------------------------------------------	-----------------------------------------------------------------------------------	--------------------------------------------------------------	--	--