



PFI2000



PTF3000



PTF3000

New
FILTER FANS
175m³/h

| MODELS | UNIT | PFI2000 | PTF3000 |
|------------------------|-------------------|------------------------------|------------------------------|
| AIR FLOW RATE | m ³ /h | - | 175 (245) |
| POWER SUPPLY | V/Hz | - | 230V 50-60Hz |
| DIMENSIONS | mm | 210x210x31 | 210x210x92 |
| POWER CONSUMPTION | W | - | 37 (35) |
| CURRENT CONSUMPTION | A | - | 0.23/0.22 |
| OVERCURRENT PROTECTION | - | - | IMPEDANCE |
| ELECTRICAL CONNECTION | - | - | 3-POLE TERMINAL |
| OPERATING TEMPERATURE | °C | -10/+70 | -10/+70 |
| PROTECTION DEGREE | - | IP54 | IP54 / CLASS I |
| NOISE LEVEL | dB(A) | - | 52 (53) |
| FLOW DIRECTION | - | - | OUTSIDE-IN |
| BEARING | - | - | BALL |
| PLASTIC MATERIAL | - | UL94 V0 ABS FLAME RETARDANT | UL94 V0 ABS FLAME RETARDANT |
| GASKET | - | POLYURETHANE SEALING | POLYURETHANE SEALING |
| COLOUR | - | RAL7035 (RAL7032 ON REQUEST) | RAL7035 (RAL7032 ON REQUEST) |
| WEIGHT | kg | 0.35 | 1.45 |
| MOUNTING | - | FAST CLIP-ON | FAST CLIP-ON |
| CONFORMITY | - | CE | CE |

