

HI-TOOL NGK WIRE GRIPS (20-KN) (MADE IN JAPAN)

HI-TOOL CO., LTD

SPECIFICATION



AL 20KN GRIP

For Bare ACSR, AL & COPPER Cable

WLL (kN)	Min. Cable (mm)	Max. Cable (mm)	Jaw Length (mm)	Eye Size (mm)	Wt (kg)
20	5	22	90	32x42	1.5



H-20KN GRIP

For Bare ACSR, AL & COPPER Cable, Guy Wire

WLL (kN)	Min. Cable (mm)	Max. Cable (mm)	Jaw Length (mm)	Eye Size (mm)	Wt (kg)
20	5	22	90	32x42	1.5



MIGHTY20 GRIP

For Covered Cable, Bare Copper Cable, Guy Wire

WLL (kN)	Min. Cable (mm)	Max. Cable (mm)	Jaw Length (mm)	Eye Size (mm)	Wt (kg)
20	5	28	120	32x42	1.9



AL MIGHTY20 GRIP

For Bare ACSR, AL & COPPER Cable

WLL (kN)	Min. Cable (mm)	Max. Cable (mm)	Jaw Length (mm)	Eye Size (mm)	Wt (kg)
20	5	28	120	32x42	1.9



H MIGHTY20 GRIP

For Bare ACSR, AL & COPPER Cable, Guy Wire

WLL (kN)	Min. Cable (mm)	Max. Cable (mm)	Jaw Length (mm)	Eye Size (mm)	Wt (kg)
20	5	28	120	32x42	1.9



FEATURES

- Patented one handed trigger grip operation.
- All models are fitted with swing down safety latch as standard.
- Conveniently sized and special shaped pulling eyes to suit all brands of strap hoists.
- All gripping jaws are produced with new technology to increase jaw life.
- Grips are designed to be used over a wider range of cable diameters



LOCKING GRIP

Optional Locking Type Grip Available on the below models (Add suffix "-LK" to model no, example 20KN-GRIP-LK)

- MIGHTY20-GRIP
- 20KN-GRIP
- LARGE-20-GRIP
- 30KN-GRIP
- 40KN-GRIP



NEW

LOCK OPEN NOTCH

This feature allows the Grip to be held in the open position for easy insertion of cable, available on the below models (Add suffix "-NS" to the model no. example 20KN-GRIP-NS):

- AL 20KN GRIP
- AL 30KN GRIP
- MIGHTY20-GRIP
- AL-MIGHTY-20-GRIP,
- LARGE20-GRIP
- LARGE30-GRIP
- AL-LARGE20-GRIP
- AL-LARGE30-GRIP,
- ABC-M-GRIP
- ABC-L-GRIP

HI-TOOL TRIGGER GRIP-PATENT PENDING