

**HI-TOOL NGK WIRE GRIPS (20-30KN) (MADE IN JAPAN)**

**HI-TOOL** CO., LTD

**SPECIFICATION**



**LARGE20 GRIP**

For Covered Cable, Bare Copper Cable

WLL (kN)	Min. Cable (mm)	Max. Cable (mm)	Jaw Length (mm)	Eye Size (mm)	Wt (kg)
20	16	35	120	32x42	2.1



**AL LARGE20 GRIP**

For Bare ACSR, AL & COPPER Cable

WLL (kN)	Min. Cable (mm)	Max. Cable (mm)	Jaw Length (mm)	Eye Size (mm)	Wt (kg)
20	16	35	120	32x42	2.1



**H LARGE20 GRIP**

For Bare ACSR, AL & COPPER Cable, Guy Wire

WLL (kN)	Min. Cable (mm)	Max. Cable (mm)	Jaw Length (mm)	Eye Size (mm)	Wt (kg)
20	16	35	120	32x42	2.1



**30KN GRIP**

For Bare Copper Cable, Guy Wire, Trolley Wire, Wire Rope

WLL (kN)	Min. Cable (mm)	Max. Cable (mm)	Jaw Length (mm)	Eye Size (mm)	Wt (kg)
30	5	22	90	32x42	1.7



**AL 30KN GRIP**

For Bare ACSR, AL & COPPER Cable

WLL (kN)	Min. Cable (mm)	Max. Cable (mm)	Jaw Length (mm)	Eye Size (mm)	Wt (kg)
30	5	22	90	32x42	1.7



**NEW**

**LOCK OPEN NOTCH**

This feature allows the Grip to be held in the open position for easy insertion of cable, available on the below models (Add suffix "-NS" to the model no. example 20KN-GRIP-NS):

- AL 20KN GRIP
- AL 30KN GRIP
- MIGHTY20-GRIP
- AL-MIGHTY-20-GRIP,
- LARGE20-GRIP
- LARGE30-GRIP
- AL-LARGE20-GRIP
- AL-LARGE30-GRIP,
- ABC-M-GRIP
- ABC-L-GRIP



**FEATURES**

- Patented one handed trigger grip operation.
- All models are fitted with swing down safety latch as standard.
- Conveniently sized and special shaped pulling eyes to suit all brands of strap hoists.
- All gripping jaws are produced with new technology to increase jaw life.
- Grips are designed to be used over a wider range of cable diameters



**NEW**

**LOCKING GRIP**

Optional Locking Type Grip Available on the below models (Add suffix "-LK" to model no, example 20KN-GRIP-LK)

- MIGHTY20-GRIP
- 20KN-GRIP
- LARGE-20-GRIP
- 30KN-GRIP
- 40KN-GRIP