

# FLEXIBLE AC CURRENT CLAMP METER

CL150



3000A ~

**True RMS**  
Measurement  
Technology



**KLEIN TOOLS** 

# FLEXIBLE AC CURRENT CLAMP METER

This convenient, stand-alone meter features an 18" flexible clamp that allows access into panels and hard to reach areas (bundled wires, awkward conductors, and PLC cabinets).



**3000A** ~

**18" Flexible Clamp**

### RADIUS MEASUREMENTS

- r1. 1.38" (35 mm):  
1% error
- r2. 2" (50 mm):  
1.5% error
- r3. 2.38" (60 mm):  
2.0% error



**Coil Lock Clamp**

**3000 Count LCD Display**

**Low Battery Indicator**

**MAX/MIN Button**

**HOLD/Backlight Button**

**Power Button**

- **True RMS CAT IV 600V, CAT III 1000V meter**
- **Auto-ranging** with direct readout from 0.1 to 3000A
- **Auto-power off** after 15 minutes of non-usage conserves battery life

Measurement	CL150	
AC Current		3000A
True RMS		●
Backlight		●
Auto-Ranging		●
Data Hold		●
Max/Min Value		●
Auto Power-Off		15 Min.
LCD Display Count		3000
<b>Durability</b>		
Drop Protection		6.6 ft. (2 m)
Safety Rating		CAT III 1000V CAT IV 600V

### Includes:

- Owner's Manual
- Storage Pouch,
- 2 x AAA Batteries



**NOTE:** There are no user-serviceable parts inside meter.

Cat. No.	UPC# 0-92644+	Batteries	Height	Width	Depth	Weight (oz.)
CL150	69099-0	2 x AAA	10.5" (266 mm)	4.12" (104 mm)	1.06" (27 mm)	15.0 (425 g)

See our complete line of Test & Measure and HVAC products

[www.kleintools.com](http://www.kleintools.com)



© 2018 Klein Tools, Inc.  
Lincolnshire, IL 60069-1418  
96534 Rev. 03/18 A

