

## 4-WIRES EARTH RESISTANCE TESTER



96242

### FEATURES

- ▶ Auto ranging microprocessor controlled.
- ▶ Earth testing at 2 Ohm, 20 Ohm, 200 Ohm, 2k Ohm.
- ▶ Earth voltage measuring : 0~300V AC.
- ▶ Automatic C spike check.
- ▶ Automatic P spike check.
- ▶ 2-Wire test.
- ▶ 3-Wire test.
- ▶ 4-Wire test.
- ▶ LCM display.
- ▶ Auto power OFF.
- ▶ Data hold.
- ▶ Robust, Compact and easy to carry.
- ▶ EN 61010-1 CAT IV 300V, EN 61557-1, EN 61557-5

### SPECIFICATIONS

Measuring Ranges	Earth Resistance : 0-2 Ohm, 0-20 Ohm, 0-200 Ohm, 0-2k Ohm
	Earth VOLTAGE : 0-300V AC
Accuracy	Earth Resistance : +/- (2%rdg+/-3dgt)
	Earth Voltage : +/- (2%rdg+/-3dgt)
Earth Resistance Resolution	0-2 Ohm (0.01 Ohm)
	0-20 Ohm (0.1 Ohm)
	0-200 Ohm (1 Ohm)
	0-2k Ohm (10 Ohm)
Temperature & Humidity	Operating : 0 degree C ~ 50 degree C <=80% R.H.
	Storage : -10 degree C ~ 60 degree C <=80% R.H.
Power Source	1.5V (AA) x 8
Dimensions	250(L) x 190(W) x 110(D) mm
Weight	Approx. 1430g (battery included)
Accessories	Test leads (red-15m, black-10m, yellow-10m, green-5m)
	Auxiliary earth bars
	Carrying case
	Instruction manual
	batteries